

# Chapter 3

## SPECIFICATIONS

---

1. MODEL LINE-UP
2. WEIGHTS AND DIMENSIONS
3. WEIGHT DISTRIBUTION OF THE OPTION EQUIPMENT
4. BODY TYPE

## 1. MODEL LINE-UP

SERIES NE, NJ, NF, NV &amp; NH

Unit : mm (in.)

				Wheelbase								
Model	Engine	Rr suspension	Transmission (T/M)	G	J	L	M	N	P	R	T	V
				3,861 (152)	4,445 (175)	4,750 (187)	5,207 (205)	5,385 (212)	5,512 (217)	5,969 (235)	6,426 (253)	6,883 (271)
NE8J	J08E-VC	LEAF	MANUAL T/M (Eaton FS-5406A)	●	●	●	●	●	●	●	●	●
			AUTO T/M (Allison 2200HS)									
		AIR	MANUAL T/M (Eaton FS-5406A)	●	●	●	●	●	●	●	●	●
			AUTO T/M (Allison 2200HS)									
NJ8J	J08E-VC	LEAF	MANUAL T/M (Eaton FS-5406A)	●	●	●	●		●	●	●	●
			AUTO T/M (Allison 2200HS)	●	●	●	●	●	●	●	●	●
		AIR	MANUAL T/M (Eaton FS-5406A)	●	●	●	●	●	●	●	●	●
			AUTO T/M (Allison 2200HS)									
	J08E-VB	LEAF	AUTO T/M (Allison 2500RDS)	●	●	●	●	●	●	●	●	●
		AIR	AUTO T/M (Allison 2500RDS)	●	●	●	●	●	●	●	●	●
NF8J	J08E-VB	LEAF	MANUAL T/M (Eaton FS-6406A)		●	●	●		●	●	●	●
			AUTO T/M (Allison 2500RDS)									
		AIR	MANUAL T/M (Eaton FS-6406A)		●	●	●		●	●	●	●
			AUTO T/M (Allison 2500RDS)									
NV8J & NH8J	J08E-VB	LEAF	MANUAL T/M (Eaton FS-6406A)	●	●	●	●		●	●	●	●
			AUTO T/M (Allison 3000RDS)									
		AIR	MANUAL T/M (Eaton FS-6406A)	●	●	●	●		●	●	●	●
			AUTO T/M (Allison 3000RDS)									

## 2. WEIGHTS AND DIMENSIONS

---

GVW Capacity and GAW Capacity listed in the table below must not be exceeded.

Chassis weight: On CANADA Market Spec. filled with lubricants coolant and fuel, but without spare tire and Std. tool sets.

All specifications of the products are with normal manufacturing allowances and tolerances.

## NE8J

Fr. Axl : MFS10 Fr. Spg : 12,000 lbs

Rr. Axl : RS19 Rr. Spg : 19,000 lbs

Model			NE8JGSA	NE8JJSA	NE8JLSA	NE8JMSA	NE8JNSA
<b>CAPACITY</b>							
GVWR	Manual T/M	kg (lb.)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)
	Auto T/M	kg (lb.)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)
GAWR	Front	kg (lb.)	4,540 (10,000)	4,540 (10,000)	4,540 (10,000)	4,540 (10,000)	4,540 (10,000)
	Rear	kg (lb.)	8,620 (19,000)	8,620 (19,000)	8,620 (19,000)	8,620 (19,000)	8,620 (19,000)
<b>DIMENSIONS</b> (On standard specifications)							
Wheelbase		mm (in.)	3,861 (152.0)	4,445 (175.0)	4,750 (187.0)	5,207 (205.0)	5,385 (212.0)
Overall length		mm (in.)	6,162 (242.6)	7,076 (278.6)	7,686 (302.6)	8,143 (320.6)	7,686 (302.6)
Overall width		mm (in.)	2,445 (96.3)	2,445 (96.3)	2,445 (96.3)	2,445 (96.3)	2,445 (96.3)
Overall height		mm (in.)	2,715 (106.9)	2,715 (106.9)	2,715 (106.9)	2,715 (106.9)	2,715 (106.9)
BBC		mm (in.)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)
Cab to axle		mm (in.)	2,149 (84.6)	2,733 (107.6)	3,038 (119.6)	3,495 (137.6)	3,673 (144.6)
Rear overhang		mm (in.)	1,270 (50.0)	1,600 (63.0)	1,905 (75.0)	1,905 (75.0)	1,270 (50.0)
Frame height at	Front axle	mm (in.)	940 (37.0)	940 (37.0)	940 (37.0)	940 (37.0)	940 (37.0)
	Rear axle	mm (in.)	1,010 (39.8)	1,010 (39.8)	1,010 (39.8)	1,010 (39.8)	1,010 (39.8)
Road clearance (at diff. case)		mm (in.)	285 (11.2)	285 (11.2)	285 (11.2)	285 (11.2)	285 (11.2)
Tread	Front	mm (in.)	2,005 (78.9)	2,005 (78.9)	2,005 (78.9)	2,005 (78.9)	2,005 (78.9)
	Rear	mm (in.)	1,830 (72.0)	1,830 (72.0)	1,830 (72.0)	1,830 (72.0)	1,830 (72.0)
Turning radius Tire		mm (in.)	6,390 (251.6)	7,240 (285.0)	7,680 (302.4)	8,340 (328.3)	8,600 (338.6)
Turning radius Swept		mm (in.)	6,920 (272.4)	7,770 (305.9)	8,210 (323.2)	8,870 (349.2)	9,130 (359.4)
<b>CHASSIS WEIGHTS</b> (on std. spec., without spare tire & std. tool set)							
<b>MANUAL T/M</b>							
Total weight	MT	kg (lb.)	4,530 (9,988)	4,500 (9,923)	4,530 (9,988)	4,580 (10,098)	4,560 (10,053)
Front axle	MT	kg (lb.)	2,835 (6,253)	2,890 (6,373)	2,910 (6,418)	2,955 (6,518)	2,990 (6,593)
Rear axle	MT	kg (lb.)	1,695 (3,735)	1,610 (3,550)	1,620 (3,570)	1,625 (3,580)	1,570 (3,460)
Unsprung weight	Front	kg (lb.)	610 (1,345)	610 (1,345)	610 (1,345)	610 (1,345)	610 (1,345)
	Rear	kg (lb.)	1,020 (2,250)	1,020 (2,250)	1,020 (2,250)	1,020 (2,250)	1,020 (2,250)
<b>AUTO T/M</b>							
Total weight	ATM	kg (lb.)	4,490 (9,900)	4,465 (9,845)	4,495 (9,910)	4,540 (10,010)	4,520 (9,965)
Front axle	ATM	kg (lb.)	2,795 (6,165)	2,855 (6,295)	2,880 (6,350)	2,915 (6,430)	2,950 (6,505)
Rear axle	ATM	kg (lb.)	1,695 (3,735)	1,610 (3,550)	1,615 (3,560)	1,625 (3,580)	1,570 (3,460)
Unsprung weight	Front	kg (lb.)	610 (1,345)	610 (1,345)	610 (1,345)	610 (1,345)	610 (1,345)
	Rear	kg (lb.)	1,020 (2,250)	1,020 (2,250)	1,020 (2,250)	1,020 (2,250)	1,020 (2,250)
Center of gravity height from the ground		mm (in.)	790 (31.1)	790 (31.1)	790 (31.1)	790 (31.1)	790 (31.1)

Model			NE8JPSA	NE8JRSA	NE8JTSA	NE8JVSA
<b>CAPACITY</b>						
GVWR	Manual T/M	kg (lb.)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)
	Auto T/M	kg (lb.)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)
GAWR	Front	kg (lb.)	4,540 (10,000)	4,540 (10,000)	4,540 (10,000)	4,540 (10,000)
	Rear	kg (lb.)	8,620 (19,000)	8,620 (19,000)	8,620 (19,000)	8,620 (19,000)
<b>DIMENSIONS</b> (On standard specifications)						
Wheelbase		mm (in.)	5,512 (217.0)	5,969 (235.0)	6,426 (253.0)	6,883 (271.0)
Overall length		mm (in.)	9,007 (354.6)	9,464 (372.6)	9,921 (390.6)	9,921 (390.6)
Overall width		mm (in.)	2,445 (96.3)	2,445 (96.3)	2,445 (96.3)	2,445 (96.3)
Overall height		mm (in.)	2,715 (106.9)	2,715 (106.9)	2,715 (106.9)	2,715 (106.9)
BBC		mm (in.)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)
Cab to axle		mm (in.)	3,800 (149.6)	4,257 (167.6)	4,714 (185.6)	5,171 (203.6)
Rear overhang		mm (in.)	2,464 (97.0)	2,464 (97.0)	2,464 (97.0)	2,007 (79.0)
Frame height at	Front axle	mm (in.)	940 (37.0)	940 (37.0)	940 (37.0)	940 (37.0)
	Rear axle	mm (in.)	1,010 (39.8)	1,010 (39.8)	1,010 (39.8)	1,010 (39.8)
Road clearance (at diff. case)		mm (in.)	285 (11.2)	285 (11.2)	285 (11.2)	285 (11.2)
Tread	Front	mm (in.)	2,005 (78.9)	2,005 (78.9)	2,005 (78.9)	2,005 (78.9)
	Rear	mm (in.)	1,830 (72.0)	1,830 (72.0)	1,830 (72.0)	1,830 (72.0)
Turning radius Tire		mm (in.)	8,790 (346.1)	9,450 (372.0)	10,120 (398.4)	10,780 (424.4)
Turning radius Swept		mm (in.)	9,320 (366.9)	9,980 (392.9)	10,650 (419.3)	11,310 (445.3)
<b>CHASSIS WEIGHTS</b> (on std. spec., without spare tire & std. tool set)						
<b>MANUAL T/M</b>						
Total weight	MT	kg (lb.)	4,630 (10,208)	4,650 (10,253)	4,665 (10,283)	4,690 (10,338)
Front axle	MT	kg (lb.)	2,960 (6,528)	2,985 (6,583)	3,030 (6,678)	3,030 (6,678)
Rear axle	MT	kg (lb.)	1,670 (3,680)	1,665 (3,670)	1,635 (3,605)	1,660 (3,660)
Unsprung weight	Front	kg (lb.)	610 (1,345)	610 (1,345)	610 (1,345)	610 (1,345)
	Rear	kg (lb.)	1,020 (2,250)	1,020 (2,250)	1,020 (2,250)	1,020 (2,250)
<b>AUTO T/M</b>						
Total weight	ATM	kg (lb.)	4,590 (10,120)	4,610 (10,165)	4,625 (10,195)	4,655 (10,260)
Front axle	ATM	kg (lb.)	2,920 (6,440)	2,945 (6,495)	2,990 (6,590)	2,995 (6,600)
Rear axle	ATM	kg (lb.)	1,670 (3,680)	1,665 (3,670)	1,635 (3,605)	1,660 (3,660)
Unsprung weight	Front	kg (lb.)	610 (1,345)	610 (1,345)	610 (1,345)	610 (1,345)
	Rear	kg (lb.)	1,020 (2,250)	1,020 (2,250)	1,020 (2,250)	1,020 (2,250)
Center of gravity height from the ground		mm (in.)	790 (31.1)	790 (31.1)	790 (31.1)	790 (31.1)

## NE8J

Fr. Axl : MFS8 Fr. Spg : 8,000 lbs

Rr. Axl : RS19 Rr. Spg : 19,000 lbs

Model			NE8JGSA	NE8JJSA	NE8JLSA	NE8JMSA	NE8JNSA
<b>CAPACITY</b>							
GVWR	Manual T/M	kg (lb.)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)
	Auto T/M	kg (lb.)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)
GAWR	Front	kg (lb.)	3,630 (8,000)	3,630 (8,000)	3,630 (8,000)	3,630 (8,000)	3,630 (8,000)
	Rear	kg (lb.)	8,620 (19,000)	8,620 (19,000)	8,620 (19,000)	8,620 (19,000)	8,620 (19,000)
<b>DIMENSIONS</b> (On standard specifications)							
Wheelbase		mm (in.)	3,861 (152.0)	4,445 (175.0)	4,750 (187.0)	5,207 (205.0)	5,385 (212.0)
Overall length		mm (in.)	6,162 (242.6)	7,076 (278.6)	7,686 (302.6)	8,143 (320.6)	7,686 (302.6)
Overall width		mm (in.)	2,445 (96.3)	2,445 (96.3)	2,445 (96.3)	2,445 (96.3)	2,445 (96.3)
Overall height		mm (in.)	2,720 (107.1)	2,720 (107.1)	2,720 (107.1)	2,720 (107.1)	2,720 (107.1)
BBC		mm (in.)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)
Cab to axle		mm (in.)	2,149 (84.6)	2,733 (107.6)	3,038 (119.6)	3,495 (137.6)	3,673 (144.6)
Rear overhang		mm (in.)	1,270 (50.0)	1,600 (63.0)	1,905 (75.0)	1,905 (75.0)	1,270 (50.0)
Frame height at	Front axle	mm (in.)	950 (37.4)	950 (37.4)	950 (37.4)	950 (37.4)	950 (37.4)
	Rear axle	mm (in.)	1,010 (39.8)	1,010 (39.8)	1,010 (39.8)	1,010 (39.8)	1,010 (39.8)
Road clearance (at diff. case)		mm (in.)	285 (11.2)	285 (11.2)	285 (11.2)	285 (11.2)	285 (11.2)
Tread	Front	mm (in.)	1,980 (78.0)	1,980 (78.0)	1,980 (78.0)	1,980 (78.0)	1,980 (78.0)
	Rear	mm (in.)	1,830 (72.0)	1,830 (72.0)	1,830 (72.0)	1,830 (72.0)	1,830 (72.0)
Turning radius Tire		mm (in.)	6,440 (253.5)	7,290 (287.0)	7,740 (304.7)	8,410 (331.1)	8,670 (341.3)
Turning radius Swept		mm (in.)	6,970 (274.4)	7,820 (307.9)	8,270 (325.6)	8,940 (352.0)	9,200 (362.2)
<b>CHASSIS WEIGHTS</b> (on std. spec., without spare tire & std. tool set)							
<b>MANUAL T/M</b>							
Total weight	MT	kg (lb.)	4,470 (9,853)	4,445 (9,798)	4,475 (9,863)	4,520 (9,963)	4,505 (9,933)
Front axle	MT	kg (lb.)	2,775 (6,118)	2,835 (6,248)	2,855 (6,293)	2,895 (6,383)	2,935 (6,473)
Rear axle	MT	kg (lb.)	1,695 (3,735)	1,610 (3,550)	1,620 (3,570)	1,625 (3,580)	1,570 (3,460)
Unsprung weight	Front	kg (lb.)	555 (1,225)	555 (1,225)	555 (1,225)	555 (1,225)	555 (1,225)
	Rear	kg (lb.)	1,020 (2,250)	1,020 (2,250)	1,020 (2,250)	1,020 (2,250)	1,020 (2,250)
<b>AUTO T/M</b>							
Total weight	ATM	kg (lb.)	4,435 (9,775)	4,405 (9,710)	4,435 (9,775)	4,485 (9,890)	4,465 (9,845)
Front axle	ATM	kg (lb.)	2,740 (6,040)	2,795 (6,160)	2,820 (6,215)	2,860 (6,310)	2,895 (6,385)
Rear axle	ATM	kg (lb.)	1,695 (3,735)	1,610 (3,550)	1,615 (3,560)	1,625 (3,580)	1,570 (3,460)
Unsprung weight	Front	kg (lb.)	555 (1,225)	555 (1,225)	555 (1,225)	555 (1,225)	555 (1,225)
	Rear	kg (lb.)	1,020 (2,250)	1,020 (2,250)	1,020 (2,250)	1,020 (2,250)	1,020 (2,250)
Center of gravity height from the ground		mm (in.)	790 (31.1)	790 (31.1)	790 (31.1)	790 (31.1)	790 (31.1)

Model			NE8JPSA	NE8JRSA	NE8JTSA	NE8JVSA
<b>CAPACITY</b>						
GVWR	Manual T/M	kg (lb.)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)
	Auto T/M	kg (lb.)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)
GAWR	Front	kg (lb.)	3,630 (8,000)	3,630 (8,000)	3,630 (8,000)	3,630 (8,000)
	Rear	kg (lb.)	8,620 (19,000)	8,620 (19,000)	8,620 (19,000)	8,620 (19,000)
<b>DIMENSIONS</b> (On standard specifications)						
Wheelbase		mm (in.)	5,512 (217.0)	5,969 (235.0)	6,426 (253.0)	6,883 (271.0)
Overall length		mm (in.)	9,007 (354.6)	9,464 (372.6)	9,921 (390.6)	9,921 (390.6)
Overall width		mm (in.)	2,445 (96.3)	2,445 (96.3)	2,445 (96.3)	2,445 (96.3)
Overall height		mm (in.)	2,720 (107.1)	2,720 (107.1)	2,720 (107.1)	2,720 (107.1)
BBC		mm (in.)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)
Cab to axle		mm (in.)	3,800 (149.6)	4,257 (167.6)	4,714 (185.6)	5,171 (203.6)
Rear overhang		mm (in.)	2,464 (97.0)	2,464 (97.0)	2,464 (97.0)	2,007 (79.0)
Frame height at	Front axle	mm (in.)	950 (37.4)	950 (37.4)	950 (37.4)	950 (37.4)
	Rear axle	mm (in.)	1,010 (39.8)	1,010 (39.8)	1,010 (39.8)	1,010 (39.8)
Road clearance (at diff. case)		mm (in.)	285 (11.2)	285 (11.2)	285 (11.2)	285 (11.2)
Tread	Front	mm (in.)	1,980 (78.0)	1,980 (78.0)	1,980 (78.0)	1,980 (78.0)
	Rear	mm (in.)	1,830 (72.0)	1,830 (72.0)	1,830 (72.0)	1,830 (72.0)
Turning radius Tire		mm (in.)	8,860 (348.8)	9,530 (375.2)	10,200 (401.6)	10,870 (428.0)
Turning radius Swept		mm (in.)	9,390 (369.7)	10,060 (396.1)	10,730 (422.4)	11,400 (448.8)
<b>CHASSIS WEIGHTS</b> (on std. spec., without spare tire & std. tool set)						
<b>MANUAL T/M</b>						
Total weight	MT	kg (lb.)	4,575 (10,088)	4,590 (10,118)	4,605 (10,153)	4,635 (10,218)
Front axle	MT	kg (lb.)	2,905 (6,408)	2,925 (6,448)	2,970 (6,548)	2,975 (6,558)
Rear axle	MT	kg (lb.)	1,670 (3,680)	1,665 (3,670)	1,635 (3,605)	1,660 (3,660)
Unsprung weight	Front	kg (lb.)	555 (1,225)	555 (1,225)	555 (1,225)	555 (1,225)
	Rear	kg (lb.)	1,020 (2,250)	1,020 (2,250)	1,020 (2,250)	1,020 (2,250)
<b>AUTO T/M</b>						
Total weight	ATM	kg (lb.)	4,535 (10,000)	4,555 (10,040)	4,570 (10,075)	4,595 (10,130)
Front axle	ATM	kg (lb.)	2,865 (6,320)	2,890 (6,370)	2,935 (6,470)	2,935 (6,470)
Rear axle	ATM	kg (lb.)	1,670 (3,680)	1,665 (3,670)	1,635 (3,605)	1,660 (3,660)
Unsprung weight	Front	kg (lb.)	555 (1,225)	555 (1,225)	555 (1,225)	555 (1,225)
	Rear	kg (lb.)	1,020 (2,250)	1,020 (2,250)	1,020 (2,250)	1,020 (2,250)
Center of gravity height from the ground		mm (in.)	790 (31.1)	790 (31.1)	790 (31.1)	790 (31.1)

## NE8J

Fr. Axl : MFS8 Fr. Spg : 8,000 lbs

Rr. Axl : RS17 Rr. Spg : 19,000 lbs

Model			NE8JGSA	NE8JJSA	NE8JLSA	NE8JMSA	NE8JNSA
<b>CAPACITY</b>							
GVWR	Manual T/M	kg (lb.)	—	—	—	—	—
	Auto T/M	kg (lb.)	10,430 (23,000)	10,430 (23,000)	10,430 (23,000)	10,430 (23,000)	10,430 (23,000)
GAWR	Front	kg (lb.)	3,630 (8,000)	3,630 (8,000)	3,630 (8,000)	3,630 (8,000)	3,630 (8,000)
	Rear	kg (lb.)	7,940 (17,500)	7,940 (17,500)	7,940 (17,500)	7,940 (17,500)	7,940 (17,500)
<b>DIMENSIONS</b> (On standard specifications)							
Wheelbase		mm (in.)	3,861 (152.0)	4,445 (175.0)	4,750 (187.0)	5,207 (205.0)	5,385 (212.0)
Overall length		mm (in.)	6,162 (242.6)	7,076 (278.6)	7,686 (302.6)	8,143 (320.6)	7,686 (302.6)
Overall width		mm (in.)	2,445 (96.3)	2,445 (96.3)	2,445 (96.3)	2,445 (96.3)	2,445 (96.3)
Overall height		mm (in.)	2,720 (107.1)	2,720 (107.1)	2,720 (107.1)	2,720 (107.1)	2,720 (107.1)
BBC		mm (in.)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)
Cab to axle		mm (in.)	2,149 (84.6)	2,733 (107.6)	3,038 (119.6)	3,495 (137.6)	3,673 (144.6)
Rear overhang		mm (in.)	1,270 (50.0)	1,600 (63.0)	1,905 (75.0)	1,905 (75.0)	1,270 (50.0)
Frame height at	Front axle	mm (in.)	950 (37.4)	950 (37.4)	950 (37.4)	950 (37.4)	950 (37.4)
	Rear axle	mm (in.)	1,010 (39.8)	1,010 (39.8)	1,010 (39.8)	1,010 (39.8)	1,010 (39.8)
Road clearance (at diff. case)		mm (in.)	285 (11.2)	285 (11.2)	285 (11.2)	285 (11.2)	285 (11.2)
Tread	Front	mm (in.)	1,980 (78.0)	1,980 (78.0)	1,980 (78.0)	1,980 (78.0)	1,980 (78.0)
	Rear	mm (in.)	1,830 (72.0)	1,830 (72.0)	1,830 (72.0)	1,830 (72.0)	1,830 (72.0)
Turning radius Tire		mm (in.)	6,440 (253.5)	7,290 (287.0)	7,740 (304.7)	8,410 (331.1)	8,670 (341.3)
Turning radius Swept		mm (in.)	6,970 (274.4)	7,820 (307.9)	8,270 (325.6)	8,940 (352.0)	9,200 (362.2)
<b>CHASSIS WEIGHTS</b> (on std. spec., without spare tire & std. tool set)							
<b>MANUAL T/M</b>							
Total weight	MT	kg (lb.)	—	—	—	—	—
Front axle	MT	kg (lb.)	—	—	—	—	—
Rear axle	MT	kg (lb.)	—	—	—	—	—
Unsprung weight	Front	kg (lb.)	—	—	—	—	—
	Rear	kg (lb.)	—	—	—	—	—
<b>AUTO T/M</b>							
Total weight	ATM	kg (lb.)	4,435 (9,775)	4,405 (9,710)	4,435 (9,775)	4,485 (9,890)	4,465 (9,845)
Front axle	ATM	kg (lb.)	2,740 (6,040)	2,795 (6,160)	2,820 (6,215)	2,860 (6,310)	2,895 (6,385)
Rear axle	ATM	kg (lb.)	1,695 (3,735)	1,610 (3,550)	1,615 (3,560)	1,625 (3,580)	1,570 (3,460)
Unsprung weight	Front	kg (lb.)	555 (1,225)	555 (1,225)	555 (1,225)	555 (1,225)	555 (1,225)
	Rear	kg (lb.)	1,020 (2,250)	1,020 (2,250)	1,020 (2,250)	1,020 (2,250)	1,020 (2,250)
Center of gravity height from the ground		mm (in.)	790 (31.1)	790 (31.1)	790 (31.1)	790 (31.1)	790 (31.1)



Model			NE8JPSA	NE8JRSA	NE8JTSA	NE8JVSA
<b>CAPACITY</b>						
GVWR	Manual T/M	kg (lb.)	—	—	—	—
	Auto T/M	kg (lb.)	10,430 (23,000)	10,430 (23,000)	10,430 (23,000)	10,430 (23,000)
GAWR	Front	kg (lb.)	3,630 (8,000)	3,630 (8,000)	3,630 (8,000)	3,630 (8,000)
	Rear	kg (lb.)	7,940 (17,500)	7,940 (17,500)	7,940 (17,500)	7,940 (17,500)
<b>DIMENSIONS</b> (On standard specifications)						
Wheelbase		mm (in.)	5,512 (217.0)	5,969 (235.0)	6,426 (253.0)	6,883 (271.0)
Overall length		mm (in.)	9,007 (354.6)	9,464 (372.6)	9,921 (390.6)	9,921 (390.6)
Overall width		mm (in.)	2,445 (96.3)	2,445 (96.3)	2,445 (96.3)	2,445 (96.3)
Overall height		mm (in.)	2,720 (107.1)	2,720 (107.1)	2,720 (107.1)	2,720 (107.1)
BBC		mm (in.)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)
Cab to axle		mm (in.)	3,800 (149.6)	4,257 (167.6)	4,714 (185.6)	5,171 (203.6)
Rear overhang		mm (in.)	2,464 (97.0)	2,464 (97.0)	2,464 (97.0)	2,007 (79.0)
Frame height at	Front axle	mm (in.)	950 (37.4)	950 (37.4)	950 (37.4)	950 (37.4)
	Rear axle	mm (in.)	1,010 (39.8)	1,010 (39.8)	1,010 (39.8)	1,010 (39.8)
Road clearance (at diff. case)		mm (in.)	285 (11.2)	285 (11.2)	285 (11.2)	285 (11.2)
Tread	Front	mm (in.)	1,980 (78.0)	1,980 (78.0)	1,980 (78.0)	1,980 (78.0)
	Rear	mm (in.)	1,830 (72.0)	1,830 (72.0)	1,830 (72.0)	1,830 (72.0)
Turning radius Tire		mm (in.)	8,860 (348.8)	9,530 (375.2)	10,200 (401.6)	10,870 (428.0)
Turning radius Swept		mm (in.)	9,390 (369.7)	10,060 (396.1)	10,730 (422.4)	11,400 (448.8)
<b>CHASSIS WEIGHTS</b> (on std. spec., without spare tire & std. tool set)						
<b>MANUAL T/M</b>						
Total weight	MT	kg (lb.)	—	—	—	—
Front axle	MT	kg (lb.)	—	—	—	—
Rear axle	MT	kg (lb.)	—	—	—	—
Unsprung weight	Front	kg (lb.)	—	—	—	—
	Rear	kg (lb.)	—	—	—	—
<b>AUTO T/M</b>						
Total weight	ATM	kg (lb.)	4,535 (10,000)	4,555 (10,040)	4,570 (10,075)	4,595 (10,130)
Front axle	ATM	kg (lb.)	2,865 (6,320)	2,890 (6,370)	2,935 (6,470)	2,935 (6,470)
Rear axle	ATM	kg (lb.)	1,670 (3,680)	1,665 (3,670)	1,635 (3,605)	1,660 (3,660)
Unsprung weight	Front	kg (lb.)	555 (1,225)	555 (1,225)	555 (1,225)	555 (1,225)
	Rear	kg (lb.)	1,020 (2,250)	1,020 (2,250)	1,020 (2,250)	1,020 (2,250)
Center of gravity height from the ground		mm (in.)	790 (31.1)	790 (31.1)	790 (31.1)	790 (31.1)

**NE8J****LOW PROFILE****Fr. Axl : MFS8 Fr. Spg : 8,000 lbs****Rr. Axl : RS17 Rr. Spg : 19,000 lbs**

Model			NE8JGSA	NE8JJSA	NE8JLSA	NE8JMSA	NE8JNSA
<b>CAPACITY</b>							
GVWR	Manual T/M	kg (lb.)	11,570 (25,500)	11,570 (25,500)	11,570 (25,500)	11,570 (25,500)	11,570 (25,500)
	Auto T/M	kg (lb.)	11,570 (25,500)	11,570 (25,500)	11,570 (25,500)	11,570 (25,500)	11,570 (25,500)
GAWR	Front	kg (lb.)	3,630 (8,000)	3,630 (8,000)	3,630 (8,000)	3,630 (8,000)	3,630 (8,000)
	Rear	kg (lb.)	7,940 (17,500)	7,940 (17,500)	7,940 (17,500)	7,940 (17,500)	7,940 (17,500)
<b>DIMENSIONS</b> (On standard specifications)							
Wheelbase		mm (in.)	3,861 (152.0)	4,445 (175.0)	4,750 (187.0)	5,207 (205.0)	5,385 (212.0)
Overall length		mm (in.)	6,162 (242.6)	7,076 (278.6)	7,686 (302.6)	8,143 (320.6)	7,686 (302.6)
Overall width		mm (in.)	2,430 (95.7)	2,430 (95.7)	2,430 (95.7)	2,430 (95.7)	2,430 (95.7)
Overall height		mm (in.)	2,615 (103.0)	2,615 (103.0)	2,615 (103.0)	2,615 (103.0)	2,615 (103.0)
BBC		mm (in.)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)
Cab to axle		mm (in.)	2,149 (84.6)	2,733 (107.6)	3,038 (119.6)	3,495 (137.6)	3,673 (144.6)
Rear overhang		mm (in.)	1,270 (50.0)	1,600 (63.0)	1,905 (75.0)	1,905 (75.0)	1,270 (50.0)
Frame height at	Front axle	mm (in.)	840 (33.1)	840 (33.1)	840 (33.1)	840 (33.1)	840 (33.1)
	Rear axle	mm (in.)	900 (35.4)	900 (35.4)	900 (35.4)	900 (35.4)	900 (35.4)
Road clearance (at diff. case)		mm (in.)	180 (7.1)	180 (7.1)	180 (7.1)	180 (7.1)	180 (7.1)
Tread	Front	mm (in.)	2,020 (79.5)	2,020 (79.5)	2,020 (79.5)	2,020 (79.5)	2,020 (79.5)
	Rear	mm (in.)	1,840 (72.4)	1,840 (72.4)	1,840 (72.4)	1,840 (72.4)	1,840 (72.4)
Turning radius Tire		mm (in.)	6,460 (254.3)	7,320 (288.2)	7,760 (305.5)	8,430 (331.9)	8,690 (342.1)
Turning radius Swept		mm (in.)	6,970 (274.4)	7,830 (308.3)	8,270 (325.6)	8,940 (352.0)	9,200 (362.2)
<b>CHASSIS WEIGHTS</b> (on std. spec., without spare tire & std. tool set)							
<b>MANUAL T/M</b>							
Total weight	MT	kg (lb.)	4,305 (9,493)	4,280 (9,438)	4,305 (9,493)	4,355 (9,603)	4,335 (9,558)
Front axle	MT	kg (lb.)	2,725 (6,008)	2,790 (6,153)	2,805 (6,188)	2,845 (6,273)	2,885 (6,363)
Rear axle	MT	kg (lb.)	1,580 (3,485)	1,490 (3,285)	1,500 (3,305)	1,510 (3,330)	1,450 (3,195)
Unsprung weight	Front	kg (lb.)	505 (1,115)	505 (1,115)	505 (1,115)	505 (1,115)	505 (1,115)
	Rear	kg (lb.)	900 (1,985)	900 (1,985)	900 (1,985)	900 (1,985)	900 (1,985)
<b>AUTO T/M</b>							
Total weight	ATM	kg (lb.)	4,265 (9,405)	4,240 (9,345)	4,270 (9,415)	4,315 (9,515)	4,295 (9,470)
Front axle	ATM	kg (lb.)	2,690 (5,935)	2,750 (6,060)	2,770 (6,110)	2,810 (6,195)	2,845 (6,275)
Rear axle	ATM	kg (lb.)	1,575 (3,470)	1,490 (3,285)	1,500 (3,305)	1,505 (3,320)	1,450 (3,195)
Unsprung weight	Front	kg (lb.)	505 (1,115)	505 (1,115)	505 (1,115)	505 (1,115)	505 (1,115)
	Rear	kg (lb.)	900 (1,985)	900 (1,985)	900 (1,985)	900 (1,985)	900 (1,985)
Center of gravity height from the ground		mm (in.)	690 (27.2)	690 (27.2)	690 (27.2)	690 (27.2)	690 (27.2)

Model			NE8JPSA	NE8JRSA	NE8JTSA	NE8JVSA
<b>CAPACITY</b>						
GVWR	Manual T/M	kg (lb.)	11,570 (25,500)	11,570 (25,500)	11,570 (25,500)	11,570 (25,500)
	Auto T/M	kg (lb.)	11,570 (25,500)	11,570 (25,500)	11,570 (25,500)	11,570 (25,500)
GAWR	Front	kg (lb.)	3,630 (8,000)	3,630 (8,000)	3,630 (8,000)	3,630 (8,000)
	Rear	kg (lb.)	7,940 (17,500)	7,940 (17,500)	7,940 (17,500)	7,940 (17,500)
<b>DIMENSIONS</b> (On standard specifications)						
Wheelbase		mm (in.)	5,512 (217.0)	5,969 (235.0)	6,426 (253.0)	6,883 (271.0)
Overall length		mm (in.)	9,007 (354.6)	9,464 (372.6)	9,921 (390.6)	9,921 (390.6)
Overall width		mm (in.)	2,430 (95.7)	2,430 (95.7)	2,430 (95.7)	2,430 (95.7)
Overall height		mm (in.)	2,615 (103.0)	2,615 (103.0)	2,615 (103.0)	2,615 (103.0)
BBC		mm (in.)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)
Cab to axle		mm (in.)	3,800 (149.6)	4,257 (167.6)	4,714 (185.6)	5,171 (203.6)
Rear overhang		mm (in.)	2,464 (97.0)	2,464 (97.0)	2,464 (97.0)	2,007 (79.0)
Frame height at	Front axle	mm (in.)	840 (33.1)	840 (33.1)	840 (33.1)	840 (33.1)
	Rear axle	mm (in.)	900 (35.4)	900 (35.4)	900 (35.4)	900 (35.4)
Road clearance (at diff. case)		mm (in.)	180 (7.1)	180 (7.1)	180 (7.1)	180 (7.1)
Tread	Front	mm (in.)	2,020 (79.5)	2,020 (79.5)	2,020 (79.5)	2,020 (79.5)
	Rear	mm (in.)	1,840 (72.4)	1,840 (72.4)	1,840 (72.4)	1,840 (72.4)
Turning radius Tire		mm (in.)	8,880 (349.6)	9,550 (376.0)	10,220 (402.4)	10,900 (429.1)
Turning radius Swept		mm (in.)	9,390 (369.7)	10,060 (396.1)	10,730 (422.4)	11,410 (449.2)
<b>CHASSIS WEIGHTS</b> (on std. spec., without spare tire & std. tool set)						
<b>MANUAL T/M</b>						
Total weight	MT	kg (lb.)	4,405 (9,713)	4,425 (9,753)	4,440 (9,788)	4,465 (9,843)
Front axle	MT	kg (lb.)	2,855 (6,298)	2,880 (6,348)	2,920 (6,438)	2,925 (6,448)
Rear axle	MT	kg (lb.)	1,550 (3,415)	1,545 (3,405)	1,520 (3,350)	1,540 (3,395)
Unsprung weight	Front	kg (lb.)	505 (1,115)	505 (1,115)	505 (1,115)	505 (1,115)
	Rear	kg (lb.)	900 (1,985)	900 (1,985)	900 (1,985)	900 (1,985)
<b>AUTO T/M</b>						
Total weight	ATM	kg (lb.)	4,365 (9,625)	4,385 (9,665)	4,400 (9,700)	4,430 (9,765)
Front axle	ATM	kg (lb.)	2,815 (6,210)	2,840 (6,260)	2,885 (6,360)	2,890 (6,370)
Rear axle	ATM	kg (lb.)	1,550 (3,415)	1,545 (3,405)	1,515 (3,340)	1,540 (3,395)
Unsprung weight	Front	kg (lb.)	505 (1,115)	505 (1,115)	505 (1,115)	505 (1,115)
	Rear	kg (lb.)	900 (1,985)	900 (1,985)	900 (1,985)	900 (1,985)
Center of gravity height from the ground		mm (in.)	690 (27.2)	690 (27.2)	690 (27.2)	690 (27.2)

## NE8J (Rr AIR SUS.)

Fr. Axl : MFS10 Fr. Spg : 12,000 lbs

Rr. Axl : RS19 Rr. Spg : 19,000 lbs

Model			NE8JGSG	NE8JJSG	NE8JLSG	NE8JMSG	NE8JNSG
<b>CAPACITY</b>							
GVWR	Manual T/M	kg (lb.)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)
	Auto T/M	kg (lb.)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)
GAWR	Front	kg (lb.)	4,540 (10,000)	4,540 (10,000)	4,540 (10,000)	4,540 (10,000)	4,540 (10,000)
	Rear	kg (lb.)	8,620 (19,000)	8,620 (19,000)	8,620 (19,000)	8,620 (19,000)	8,620 (19,000)
<b>DIMENSIONS</b> (On standard specifications)							
Wheelbase		mm (in.)	3,861 (152.0)	4,445 (175.0)	4,750 (187.0)	5,207 (205.0)	5,385 (212.0)
Overall length		mm (in.)	6,162 (242.6)	7,076 (278.6)	7,686 (302.6)	8,143 (320.6)	7,686 (302.6)
Overall width		mm (in.)	2,445 (96.3)	2,445 (96.3)	2,445 (96.3)	2,445 (96.3)	2,445 (96.3)
Overall height		mm (in.)	2,710 (106.7)	2,710 (106.7)	2,710 (106.7)	2,710 (106.7)	2,710 (106.7)
BBC		mm (in.)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)
Cab to axle		mm (in.)	2,149 (84.6)	2,733 (107.6)	3,038 (119.6)	3,495 (137.6)	3,673 (144.6)
Rear overhang		mm (in.)	1,270 (50.0)	1,600 (63.0)	1,905 (75.0)	1,905 (75.0)	1,270 (50.0)
Frame height at	Front axle	mm (in.)	940 (37.0)	940 (37.0)	940 (37.0)	940 (37.0)	940 (37.0)
	Rear axle	mm (in.)	990 (39.0)	990 (39.0)	990 (39.0)	990 (39.0)	990 (39.0)
Road clearance (at diff. case)		mm (in.)	285 (11.2)	285 (11.2)	285 (11.2)	285 (11.2)	285 (11.2)
Tread	Front	mm (in.)	2,005 (78.9)	2,005 (78.9)	2,005 (78.9)	2,005 (78.9)	2,005 (78.9)
	Rear	mm (in.)	1,830 (72.0)	1,830 (72.0)	1,830 (72.0)	1,830 (72.0)	1,830 (72.0)
Turning radius Tire		mm (in.)	6,390 (251.6)	7,240 (285.0)	7,680 (302.4)	8,340 (328.3)	8,600 (338.6)
Turning radius Swept		mm (in.)	6,920 (272.4)	7,770 (305.9)	8,210 (323.2)	8,870 (349.2)	9,130 (359.4)
<b>CHASSIS WEIGHTS</b> (on std. spec., without spare tire & std. tool set)							
<b>MANUAL T/M</b>							
Total weight	MT	kg (lb.)	4,515 (9,953)	4,480 (9,878)	4,510 (9,943)	4,555 (10,043)	4,535 (9,998)
Front axle	MT	kg (lb.)	2,830 (6,238)	2,890 (6,373)	2,910 (6,418)	2,945 (6,493)	2,985 (6,583)
Rear axle	MT	kg (lb.)	1,685 (3,715)	1,590 (3,505)	1,600 (3,525)	1,610 (3,550)	1,550 (3,415)
Unsprung weight	Front	kg (lb.)	610 (1,345)	610 (1,345)	610 (1,345)	610 (1,345)	610 (1,345)
	Rear	kg (lb.)	1,005 (2,215)	1,005 (2,215)	1,005 (2,215)	1,005 (2,215)	1,005 (2,215)
<b>AUTO T/M</b>							
Total weight	ATM	kg (lb.)	4,475 (9,865)	4,440 (9,790)	4,470 (9,855)	4,520 (9,965)	4,500 (9,920)
Front axle	ATM	kg (lb.)	2,795 (6,160)	2,850 (6,285)	2,870 (6,330)	2,915 (6,425)	2,950 (6,505)
Rear axle	ATM	kg (lb.)	1,680 (3,705)	1,590 (3,505)	1,600 (3,525)	1,605 (3,540)	1,550 (3,415)
Unsprung weight	Front	kg (lb.)	610 (1,345)	610 (1,345)	610 (1,345)	610 (1,345)	610 (1,345)
	Rear	kg (lb.)	1,005 (2,215)	1,005 (2,215)	1,005 (2,215)	1,005 (2,215)	1,005 (2,215)
Center of gravity height from the ground		mm (in.)	780 (30.7)	780 (30.7)	780 (30.7)	780 (30.7)	780 (30.7)

Model			NE8JPSG	NE8JRSG	NE8JTSG	NE8JVSG
<b>CAPACITY</b>						
GVWR	Manual T/M	kg (lb.)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)
	Auto T/M	kg (lb.)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)
GAWR	Front	kg (lb.)	4,540 (10,000)	4,540 (10,000)	4,540 (10,000)	4,540 (10,000)
	Rear	kg (lb.)	8,620 (19,000)	8,620 (19,000)	8,620 (19,000)	8,620 (19,000)
<b>DIMENSIONS</b> (On standard specifications)						
Wheelbase		mm (in.)	5,512 (217.0)	5,969 (235.0)	6,426 (253.0)	6,883 (271.0)
Overall length		mm (in.)	9,007 (354.6)	9,464 (372.6)	9,921 (390.6)	9,921 (390.6)
Overall width		mm (in.)	2,445 (96.3)	2,445 (96.3)	2,445 (96.3)	2,445 (96.3)
Overall height		mm (in.)	2,710 (106.7)	2,710 (106.7)	2,710 (106.7)	2,710 (106.7)
BBC		mm (in.)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)
Cab to axle		mm (in.)	3,800 (149.6)	4,257 (167.6)	4,714 (185.6)	5,171 (203.6)
Rear overhang		mm (in.)	2,464 (97.0)	2,464 (97.0)	2,464 (97.0)	2,007 (79.0)
Frame height at	Front axle	mm (in.)	940 (37.0)	940 (37.0)	940 (37.0)	940 (37.0)
	Rear axle	mm (in.)	990 (39.0)	990 (39.0)	990 (39.0)	990 (39.0)
Road clearance (at diff. case)		mm (in.)	285 (11.2)	285 (11.2)	285 (11.2)	285 (11.2)
Tread	Front	mm (in.)	2,005 (78.9)	2,005 (78.9)	2,005 (78.9)	2,005 (78.9)
	Rear	mm (in.)	1,830 (72.0)	1,830 (72.0)	1,830 (72.0)	1,830 (72.0)
Turning radius Tire		mm (in.)	8,790 (346.1)	9,450 (372.0)	10,120 (398.4)	10,780 (424.4)
Turning radius Swept		mm (in.)	9,320 (366.9)	9,980 (392.9)	10,650 (419.3)	11,310 (445.3)
<b>CHASSIS WEIGHTS</b> (on std. spec., without spare tire & std. tool set)						
<b>MANUAL T/M</b>						
Total weight	MT	kg (lb.)	4,605 (10,153)	4,625 (10,198)	4,640 (10,228)	4,670 (10,293)
Front axle	MT	kg (lb.)	2,955 (6,513)	2,980 (6,573)	3,020 (6,658)	3,025 (6,668)
Rear axle	MT	kg (lb.)	1,650 (3,640)	1,645 (3,625)	1,620 (3,570)	1,645 (3,625)
Unsprung weight	Front	kg (lb.)	610 (1,345)	610 (1,345)	610 (1,345)	610 (1,345)
	Rear	kg (lb.)	1,005 (2,215)	1,005 (2,215)	1,005 (2,215)	1,005 (2,215)
<b>AUTO T/M</b>						
Total weight	ATM	kg (lb.)	4,570 (10,075)	4,585 (10,110)	4,600 (10,140)	4,630 (10,205)
Front axle	ATM	kg (lb.)	2,920 (6,435)	2,940 (6,485)	2,985 (6,580)	2,990 (6,590)
Rear axle	ATM	kg (lb.)	1,650 (3,640)	1,645 (3,625)	1,615 (3,560)	1,640 (3,615)
Unsprung weight	Front	kg (lb.)	610 (1,345)	610 (1,345)	610 (1,345)	610 (1,345)
	Rear	kg (lb.)	1,005 (2,215)	1,005 (2,215)	1,005 (2,215)	1,005 (2,215)
Center of gravity height from the ground		mm (in.)	780 (30.7)	780 (30.7)	780 (30.7)	780 (30.7)

## NE8J (Rr AIR SUS.)

Fr. Axl : MFS8 Fr. Spg : 8,000 lbs

Rr. Axl : RS19 Rr. Spg : 19,000 lbs

Model			NE8JGSG	NE8JJSG	NE8JLSG	NE8JMSG	NE8JNSG
<b>CAPACITY</b>							
GVWR	Manual T/M	kg (lb.)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)
	Auto T/M	kg (lb.)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)
GAWR	Front	kg (lb.)	3,630 (8,000)	3,630 (8,000)	3,630 (8,000)	3,630 (8,000)	3,630 (8,000)
	Rear	kg (lb.)	8,620 (19,000)	8,620 (19,000)	8,620 (19,000)	8,620 (19,000)	8,620 (19,000)
<b>DIMENSIONS</b> (On standard specifications)							
Wheelbase		mm (in.)	3,861 (152.0)	4,445 (175.0)	4,750 (187.0)	5,207 (205.0)	5,385 (212.0)
Overall length		mm (in.)	6,162 (242.6)	7,076 (278.6)	7,686 (302.6)	8,143 (320.6)	7,686 (302.6)
Overall width		mm (in.)	2,445 (96.3)	2,445 (96.3)	2,445 (96.3)	2,445 (96.3)	2,445 (96.3)
Overall height		mm (in.)	2,715 (106.9)	2,715 (106.9)	2,715 (106.9)	2,715 (106.9)	2,715 (106.9)
BBC		mm (in.)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)
Cab to axle		mm (in.)	2,149 (84.6)	2,733 (107.6)	3,038 (119.6)	3,495 (137.6)	3,673 (144.6)
Rear overhang		mm (in.)	1,270 (50.0)	1,600 (63.0)	1,905 (75.0)	1,905 (75.0)	1,270 (50.0)
Frame height at	Front axle	mm (in.)	950 (37.4)	950 (37.4)	950 (37.4)	950 (37.4)	950 (37.4)
	Rear axle	mm (in.)	990 (39.0)	990 (39.0)	990 (39.0)	990 (39.0)	990 (39.0)
Road clearance (at diff. case)		mm (in.)	285 (11.2)	285 (11.2)	285 (11.2)	285 (11.2)	285 (11.2)
Tread	Front	mm (in.)	1,980 (78.0)	1,980 (78.0)	1,980 (78.0)	1,980 (78.0)	1,980 (78.0)
	Rear	mm (in.)	1,830 (72.0)	1,830 (72.0)	1,830 (72.0)	1,830 (72.0)	1,830 (72.0)
Turning radius Tire		mm (in.)	6,440 (253.5)	7,290 (287.0)	7,740 (304.7)	8,410 (331.1)	8,670 (341.3)
Turning radius Swept		mm (in.)	6,970 (274.4)	7,820 (307.9)	8,270 (325.6)	8,940 (352.0)	9,200 (362.2)
<b>CHASSIS WEIGHTS</b> (on std. spec., without spare tire & std. tool set)							
<b>MANUAL T/M</b>							
Total weight	MT	kg (lb.)	4,455 (9,823)	4,420 (9,743)	4,450 (9,808)	4,500 (9,923)	4,480 (9,878)
Front axle	MT	kg (lb.)	2,770 (6,108)	2,830 (6,238)	2,850 (6,283)	2,890 (6,373)	2,930 (6,463)
Rear axle	MT	kg (lb.)	1,685 (3,715)	1,590 (3,505)	1,600 (3,525)	1,610 (3,550)	1,550 (3,415)
Unsprung weight	Front	kg (lb.)	555 (1,225)	555 (1,225)	555 (1,225)	555 (1,225)	555 (1,225)
	Rear	kg (lb.)	1,005 (2,215)	1,005 (2,215)	1,005 (2,215)	1,005 (2,215)	1,005 (2,215)
<b>AUTO T/M</b>							
Total weight	ATM	kg (lb.)	4,420 (9,745)	4,385 (9,665)	4,415 (9,735)	4,460 (9,830)	4,440 (9,790)
Front axle	ATM	kg (lb.)	2,740 (6,040)	2,795 (6,160)	2,815 (6,210)	2,855 (6,290)	2,890 (6,375)
Rear axle	ATM	kg (lb.)	1,680 (3,705)	1,590 (3,505)	1,600 (3,525)	1,605 (3,540)	1,550 (3,415)
Unsprung weight	Front	kg (lb.)	555 (1,225)	555 (1,225)	555 (1,225)	555 (1,225)	555 (1,225)
	Rear	kg (lb.)	1,005 (2,215)	1,005 (2,215)	1,005 (2,215)	1,005 (2,215)	1,005 (2,215)
Center of gravity height from the ground		mm (in.)	785 (30.9)	785 (30.9)	785 (30.9)	785 (30.9)	785 (30.9)

Model			NE8JPSG	NE8JRSG	NE8JTSG	NE8JVSG
<b>CAPACITY</b>						
GVWR	Manual T/M	kg (lb.)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)
	Auto T/M	kg (lb.)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)
GAWR	Front	kg (lb.)	3,630 (8,000)	3,630 (8,000)	3,630 (8,000)	3,630 (8,000)
	Rear	kg (lb.)	8,620 (19,000)	8,620 (19,000)	8,620 (19,000)	8,620 (19,000)
<b>DIMENSIONS</b> (On standard specifications)						
Wheelbase		mm (in.)	5,512 (217.0)	5,969 (235.0)	6,426 (253.0)	6,883 (271.0)
Overall length		mm (in.)	9,007 (354.6)	9,464 (372.6)	9,921 (390.6)	9,921 (390.6)
Overall width		mm (in.)	2,445 (96.3)	2,445 (96.3)	2,445 (96.3)	2,445 (96.3)
Overall height		mm (in.)	2,715 (106.9)	2,715 (106.9)	2,715 (106.9)	2,715 (106.9)
BBC		mm (in.)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)
Cab to axle		mm (in.)	3,800 (149.6)	4,257 (167.6)	4,714 (185.6)	5,171 (203.6)
Rear overhang		mm (in.)	2,464 (97.0)	2,464 (97.0)	2,464 (97.0)	2,007 (79.0)
Frame height at	Front axle	mm (in.)	950 (37.4)	950 (37.4)	950 (37.4)	950 (37.4)
	Rear axle	mm (in.)	990 (39.0)	990 (39.0)	990 (39.0)	990 (39.0)
Road clearance (at diff. case)		mm (in.)	285 (11.2)	285 (11.2)	285 (11.2)	285 (11.2)
Tread	Front	mm (in.)	1,980 (78.0)	1,980 (78.0)	1,980 (78.0)	1,980 (78.0)
	Rear	mm (in.)	1,830 (72.0)	1,830 (72.0)	1,830 (72.0)	1,830 (72.0)
Turning radius Tire		mm (in.)	8,860 (348.8)	9,530 (375.2)	10,200 (401.6)	10,870 (428.0)
Turning radius Swept		mm (in.)	9,390 (369.7)	10,060 (396.1)	10,730 (422.4)	11,400 (448.8)
<b>CHASSIS WEIGHTS</b> (on std. spec., without spare tire & std. tool set)						
<b>MANUAL T/M</b>						
Total weight	MT	kg (lb.)	4,550 (10,033)	4,570 (10,073)	4,585 (10,108)	4,610 (10,163)
Front axle	MT	kg (lb.)	2,900 (6,393)	2,925 (6,448)	2,965 (6,538)	2,965 (6,538)
Rear axle	MT	kg (lb.)	1,650 (3,640)	1,645 (3,625)	1,620 (3,570)	1,645 (3,625)
Unsprung weight	Front	kg (lb.)	555 (1,225)	555 (1,225)	555 (1,225)	555 (1,225)
	Rear	kg (lb.)	1,005 (2,215)	1,005 (2,215)	1,005 (2,215)	1,005 (2,215)
<b>AUTO T/M</b>						
Total weight	ATM	kg (lb.)	4,510 (9,945)	4,530 (9,985)	4,545 (10,020)	4,575 (10,085)
Front axle	ATM	kg (lb.)	2,860 (6,305)	2,885 (6,360)	2,930 (6,460)	2,935 (6,470)
Rear axle	ATM	kg (lb.)	1,650 (3,640)	1,645 (3,625)	1,615 (3,560)	1,640 (3,615)
Unsprung weight	Front	kg (lb.)	555 (1,225)	555 (1,225)	555 (1,225)	555 (1,225)
	Rear	kg (lb.)	1,005 (2,215)	1,005 (2,215)	1,005 (2,215)	1,005 (2,215)
Center of gravity height from the ground		mm (in.)	785 (30.9)	785 (30.9)	785 (30.9)	785 (30.9)



**NE8J (Rr AIR SUS.)****Fr. Axl : MFS8 Fr. Spg : 8,000 lbs****Rr. Axl : RS17 Rr. Spg : 19,000 lbs**

Model			NE8JGSG	NE8JJSG	NE8JLSG	NE8JMSG	NE8JNSG
<b>CAPACITY</b>							
GVWR	Manual T/M	kg (lb.)	—	—	—	—	—
	Auto T/M	kg (lb.)	10,430 (23,000)	10,430 (23,000)	10,430 (23,000)	10,430 (23,000)	10,430 (23,000)
GAWR	Front	kg (lb.)	3,630 (8,000)	3,630 (8,000)	3,630 (8,000)	3,630 (8,000)	3,630 (8,000)
	Rear	kg (lb.)	7,940 (17,500)	7,940 (17,500)	7,940 (17,500)	7,940 (17,500)	7,940 (17,500)
<b>DIMENSIONS</b> (On standard specifications)							
Wheelbase		mm (in.)	3,861 (152.0)	4,445 (175.0)	4,750 (187.0)	5,207 (205.0)	5,385 (212.0)
Overall length		mm (in.)	6,162 (242.6)	7,076 (278.6)	7,686 (302.6)	8,143 (320.6)	7,686 (302.6)
Overall width		mm (in.)	2,445 (96.3)	2,445 (96.3)	2,445 (96.3)	2,445 (96.3)	2,445 (96.3)
Overall height		mm (in.)	2,715 (106.9)	2,715 (106.9)	2,715 (106.9)	2,715 (106.9)	2,715 (106.9)
BBC		mm (in.)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)
Cab to axle		mm (in.)	2,149 (84.6)	2,733 (107.6)	3,038 (119.6)	3,495 (137.6)	3,673 (144.6)
Rear overhang		mm (in.)	1,270 (50.0)	1,600 (63.0)	1,905 (75.0)	1,905 (75.0)	1,270 (50.0)
Frame height at	Front axle	mm (in.)	950 (37.4)	950 (37.4)	950 (37.4)	950 (37.4)	950 (37.4)
	Rear axle	mm (in.)	990 (39.0)	990 (39.0)	990 (39.0)	990 (39.0)	990 (39.0)
Road clearance (at diff. case)		mm (in.)	285 (11.2)	285 (11.2)	285 (11.2)	285 (11.2)	285 (11.2)
Tread	Front	mm (in.)	1,980 (78.0)	1,980 (78.0)	1,980 (78.0)	1,980 (78.0)	1,980 (78.0)
	Rear	mm (in.)	1,830 (72.0)	1,830 (72.0)	1,830 (72.0)	1,830 (72.0)	1,830 (72.0)
Turning radius Tire		mm (in.)	6,440 (253.5)	7,290 (287.0)	7,740 (304.7)	8,410 (331.1)	8,670 (341.3)
Turning radius Swept		mm (in.)	6,970 (274.4)	7,820 (307.9)	8,270 (325.6)	8,940 (352.0)	9,200 (362.2)
<b>CHASSIS WEIGHTS</b> (on std. spec., without spare tire & std. tool set)							
<b>MANUAL T/M</b>							
Total weight	MT	kg (lb.)	—	—	—	—	—
Front axle	MT	kg (lb.)	—	—	—	—	—
Rear axle	MT	kg (lb.)	—	—	—	—	—
Unsprung weight	Front	kg (lb.)	—	—	—	—	—
	Rear	kg (lb.)	—	—	—	—	—
<b>AUTO T/M</b>							
Total weight	ATM	kg (lb.)	4,420 (9,745)	4,385 (9,665)	4,415 (9,735)	4,460 (9,830)	4,440 (9,790)
Front axle	ATM	kg (lb.)	2,740 (6,040)	2,795 (6,160)	2,815 (6,210)	2,855 (6,290)	2,890 (6,375)
Rear axle	ATM	kg (lb.)	1,680 (3,705)	1,590 (3,505)	1,600 (3,525)	1,605 (3,540)	1,550 (3,415)
Unsprung weight	Front	kg (lb.)	555 (1,225)	555 (1,225)	555 (1,225)	555 (1,225)	555 (1,225)
	Rear	kg (lb.)	1,005 (2,215)	1,005 (2,215)	1,005 (2,215)	1,005 (2,215)	1,005 (2,215)
Center of gravity height from the ground		mm (in.)	785 (30.9)	785 (30.9)	785 (30.9)	785 (30.9)	785 (30.9)



Model			NE8JPSG	NE8JRSG	NE8JTSG	NE8JVSG
<b>CAPACITY</b>						
GVWR	Manual T/M	kg (lb.)	—	—	—	—
	Auto T/M	kg (lb.)	10,430 (23,000)	10,430 (23,000)	10,430 (23,000)	10,430 (23,000)
GAWR	Front	kg (lb.)	3,630 (8,000)	3,630 (8,000)	3,630 (8,000)	3,630 (8,000)
	Rear	kg (lb.)	7,940 (17,500)	7,940 (17,500)	7,940 (17,500)	7,940 (17,500)
<b>DIMENSIONS</b> (On standard specifications)						
Wheelbase		mm (in.)	5,512 (217.0)	5,969 (235.0)	6,426 (253.0)	6,883 (271.0)
Overall length		mm (in.)	9,007 (354.6)	9,464 (372.6)	9,921 (390.6)	9,921 (390.6)
Overall width		mm (in.)	2,445 (96.3)	2,445 (96.3)	2,445 (96.3)	2,445 (96.3)
Overall height		mm (in.)	2,715 (106.9)	2,715 (106.9)	2,715 (106.9)	2,715 (106.9)
BBC		mm (in.)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)
Cab to axle		mm (in.)	3,800 (149.6)	4,257 (167.6)	4,714 (185.6)	5,171 (203.6)
Rear overhang		mm (in.)	2,464 (97.0)	2,464 (97.0)	2,464 (97.0)	2,007 (79.0)
Frame height at	Front axle	mm (in.)	950 (37.4)	950 (37.4)	950 (37.4)	950 (37.4)
	Rear axle	mm (in.)	990 (39.0)	990 (39.0)	990 (39.0)	990 (39.0)
Road clearance (at diff. case)		mm (in.)	285 (11.2)	285 (11.2)	285 (11.2)	285 (11.2)
Tread	Front	mm (in.)	1,980 (78.0)	1,980 (78.0)	1,980 (78.0)	1,980 (78.0)
	Rear	mm (in.)	1,830 (72.0)	1,830 (72.0)	1,830 (72.0)	1,830 (72.0)
Turning radius Tire		mm (in.)	8,860 (348.8)	9,530 (375.2)	10,200 (401.6)	10,870 (428.0)
Turning radius Swept		mm (in.)	9,390 (369.7)	10,060 (396.1)	10,730 (422.4)	11,400 (448.8)
<b>CHASSIS WEIGHTS</b> (on std. spec., without spare tire & std. tool set)						
<b>MANUAL T/M</b>						
Total weight	MT	kg (lb.)	—	—	—	—
Front axle	MT	kg (lb.)	—	—	—	—
Rear axle	MT	kg (lb.)	—	—	—	—
Unsprung weight	Front	kg (lb.)	—	—	—	—
	Rear	kg (lb.)	—	—	—	—
<b>AUTO T/M</b>						
Total weight	ATM	kg (lb.)	4,510 (9,945)	4,530 (9,985)	4,545 (10,020)	4,575 (10,085)
Front axle	ATM	kg (lb.)	2,860 (6,305)	2,885 (6,360)	2,930 (6,460)	2,935 (6,470)
Rear axle	ATM	kg (lb.)	1,650 (3,640)	1,645 (3,625)	1,615 (3,560)	1,640 (3,615)
Unsprung weight	Front	kg (lb.)	555 (1,225)	555 (1,225)	555 (1,225)	555 (1,225)
	Rear	kg (lb.)	1,005 (2,215)	1,005 (2,215)	1,005 (2,215)	1,005 (2,215)
Center of gravity height from the ground		mm (in.)	785 (30.9)	785 (30.9)	785 (30.9)	785 (30.9)

**NE8J (Rr AIR SUS.)****LOW PROFILE****Fr. Axl : MFS8 Fr. Spg : 8,000 lbs****Rr. Axl : RS17 Rr. Spg : 19,000 lbs**

Model			NE8JGSG	NE8JJSG	NE8JLSG	NE8JMSG	NE8JNSG
<b>CAPACITY</b>							
GVWR	Manual T/M	kg (lb.)	11,570 (25,500)	11,570 (25,500)	11,570 (25,500)	11,570 (25,500)	11,570 (25,500)
	Auto T/M	kg (lb.)	11,570 (25,500)	11,570 (25,500)	11,570 (25,500)	11,570 (25,500)	11,570 (25,500)
GAWR	Front	kg (lb.)	3,630 (8,000)	3,630 (8,000)	3,630 (8,000)	3,630 (8,000)	3,630 (8,000)
	Rear	kg (lb.)	7,940 (17,500)	7,940 (17,500)	7,940 (17,500)	7,940 (17,500)	7,940 (17,500)
<b>DIMENSIONS</b> (On standard specifications)							
Wheelbase		mm (in.)	3,861 (152.0)	4,445 (175.0)	4,750 (187.0)	5,207 (205.0)	5,385 (212.0)
Overall length		mm (in.)	6,162 (242.6)	7,076 (278.6)	7,686 (302.6)	8,143 (320.6)	7,686 (302.6)
Overall width		mm (in.)	2,430 (95.7)	2,430 (95.7)	2,430 (95.7)	2,430 (95.7)	2,430 (95.7)
Overall height		mm (in.)	2,610 (102.8)	2,610 (102.8)	2,610 (102.8)	2,610 (102.8)	2,610 (102.8)
BBC		mm (in.)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)
Cab to axle		mm (in.)	2,149 (84.6)	2,733 (107.6)	3,038 (119.6)	3,495 (137.6)	3,673 (144.6)
Rear overhang		mm (in.)	1,270 (50.0)	1,600 (63.0)	1,905 (75.0)	1,905 (75.0)	1,270 (50.0)
Frame height at	Front axle	mm (in.)	840 (33.1)	840 (33.1)	840 (33.1)	840 (33.1)	840 (33.1)
	Rear axle	mm (in.)	885 (34.8)	885 (34.8)	885 (34.8)	885 (34.8)	885 (34.8)
Road clearance (at diff. case)		mm (in.)	180 (7.1)	180 (7.1)	180 (7.1)	180 (7.1)	180 (7.1)
Tread	Front	mm (in.)	2,020 (79.5)	2,020 (79.5)	2,020 (79.5)	2,020 (79.5)	2,020 (79.5)
	Rear	mm (in.)	1,840 (72.4)	1,840 (72.4)	1,840 (72.4)	1,840 (72.4)	1,840 (72.4)
Turning radius Tire		mm (in.)	6,460 (254.3)	7,320 (288.2)	7,760 (305.5)	8,430 (331.9)	8,690 (342.1)
Turning radius Swept		mm (in.)	6,970 (274.4)	7,830 (308.3)	8,270 (325.6)	8,940 (352.0)	9,200 (362.2)
<b>CHASSIS WEIGHTS</b> (on std. spec., without spare tire & std. tool set)							
<b>MANUAL T/M</b>							
Total weight	MT	kg (lb.)	4,290 (9,458)	4,255 (9,378)	4,285 (9,448)	4,330 (9,548)	4,310 (9,503)
Front axle	MT	kg (lb.)	2,725 (6,008)	2,780 (6,128)	2,805 (6,183)	2,840 (6,263)	2,875 (6,338)
Rear axle	MT	kg (lb.)	1,565 (3,450)	1,475 (3,250)	1,480 (3,265)	1,490 (3,285)	1,435 (3,165)
Unsprung weight	Front	kg (lb.)	505 (1,115)	505 (1,115)	505 (1,115)	505 (1,115)	505 (1,115)
	Rear	kg (lb.)	885 (1,950)	885 (1,950)	885 (1,950)	885 (1,950)	885 (1,950)
<b>AUTO T/M</b>							
Total weight	ATM	kg (lb.)	4,250 (9,370)	4,215 (9,290)	4,245 (9,360)	4,295 (9,470)	4,275 (9,425)
Front axle	ATM	kg (lb.)	2,685 (5,920)	2,745 (6,050)	2,765 (6,095)	2,805 (6,185)	2,845 (6,270)
Rear axle	ATM	kg (lb.)	1,565 (3,450)	1,470 (3,240)	1,480 (3,265)	1,490 (3,285)	1,430 (3,155)
Unsprung weight	Front	kg (lb.)	505 (1,115)	505 (1,115)	505 (1,115)	505 (1,115)	505 (1,115)
	Rear	kg (lb.)	885 (1,950)	885 (1,950)	885 (1,950)	885 (1,950)	885 (1,950)
Center of gravity height from the ground		mm (in.)	685 (27.0)	685 (27.0)	685 (27.0)	685 (27.0)	685 (27.0)

Model			NE8JPSG	NE8JRSG	NE8JTSG	NE8JVSG
<b>CAPACITY</b>						
GVWR	Manual T/M	kg (lb.)	11,570 (25,500)	11,570 (25,500)	11,570 (25,500)	11,570 (25,500)
	Auto T/M	kg (lb.)	11,570 (25,500)	11,570 (25,500)	11,570 (25,500)	11,570 (25,500)
GAWR	Front	kg (lb.)	3,630 (8,000)	3,630 (8,000)	3,630 (8,000)	3,630 (8,000)
	Rear	kg (lb.)	7,940 (17,500)	7,940 (17,500)	7,940 (17,500)	7,940 (17,500)
<b>DIMENSIONS</b> (On standard specifications)						
Wheelbase		mm (in.)	5,512 (217.0)	5,969 (235.0)	6,426 (253.0)	6,883 (271.0)
Overall length		mm (in.)	9,007 (354.6)	9,464 (372.6)	9,921 (390.6)	9,921 (390.6)
Overall width		mm (in.)	2,430 (95.7)	2,430 (95.7)	2,430 (95.7)	2,430 (95.7)
Overall height		mm (in.)	2,610 (102.8)	2,610 (102.8)	2,610 (102.8)	2,610 (102.8)
BBC		mm (in.)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)
Cab to axle		mm (in.)	3,800 (149.6)	4,257 (167.6)	4,714 (185.6)	5,171 (203.6)
Rear overhang		mm (in.)	2,464 (97.0)	2,464 (97.0)	2,464 (97.0)	2,007 (79.0)
Frame height at	Front axle	mm (in.)	840 (33.1)	840 (33.1)	840 (33.1)	840 (33.1)
	Rear axle	mm (in.)	885 (34.8)	885 (34.8)	885 (34.8)	885 (34.8)
Road clearance (at diff. case)		mm (in.)	180 (7.1)	180 (7.1)	180 (7.1)	180 (7.1)
Tread	Front	mm (in.)	2,020 (79.5)	2,020 (79.5)	2,020 (79.5)	2,020 (79.5)
	Rear	mm (in.)	1,840 (72.4)	1,840 (72.4)	1,840 (72.4)	1,840 (72.4)
Turning radius Tire		mm (in.)	8,880 (349.6)	9,550 (376.0)	10,220 (402.4)	10,900 (429.1)
Turning radius Swept		mm (in.)	9,390 (369.7)	10,060 (396.1)	10,730 (422.4)	11,410 (449.2)
<b>CHASSIS WEIGHTS</b> (on std. spec., without spare tire & std. tool set)						
<b>MANUAL T/M</b>						
Total weight	MT	kg (lb.)	4,380 (9,658)	4,400 (9,698)	4,415 (9,733)	4,445 (9,798)
Front axle	MT	kg (lb.)	2,845 (6,273)	2,875 (6,338)	2,915 (6,428)	2,920 (6,438)
Rear axle	MT	kg (lb.)	1,535 (3,385)	1,525 (3,360)	1,500 (3,305)	1,525 (3,360)
Unsprung weight	Front	kg (lb.)	505 (1,115)	505 (1,115)	505 (1,115)	505 (1,115)
	Rear	kg (lb.)	885 (1,950)	885 (1,950)	885 (1,950)	885 (1,950)
<b>AUTO T/M</b>						
Total weight	ATM	kg (lb.)	4,345 (9,580)	4,365 (9,625)	4,375 (9,645)	4,405 (9,710)
Front axle	ATM	kg (lb.)	2,815 (6,205)	2,840 (6,265)	2,875 (6,340)	2,880 (6,350)
Rear axle	ATM	kg (lb.)	1,530 (3,375)	1,525 (3,360)	1,500 (3,305)	1,525 (3,360)
Unsprung weight	Front	kg (lb.)	505 (1,115)	505 (1,115)	505 (1,115)	505 (1,115)
	Rear	kg (lb.)	885 (1,950)	885 (1,950)	885 (1,950)	885 (1,950)
Center of gravity height from the ground		mm (in.)	685 (27.0)	685 (27.0)	685 (27.0)	685 (27.0)

## NJ8J

## J08E-VC

Fr. Axl : MFS10 Fr. Spg : 12,000 lbs

Rr. Axl : RS19 Rr. Spg : 19,000 lbs

Model			NJ8JGSA	NJ8JJSA	NJ8JLSA	NJ8JMSA	NJ8JNSA
<b>CAPACITY</b>							
GVWR	Manual T/M	kg (lb.)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)	—
	Auto T/M	kg (lb.)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)
GAWR	Front	kg (lb.)	4,540 (10,000)	4,540 (10,000)	4,540 (10,000)	4,540 (10,000)	4,540 (10,000)
	Rear	kg (lb.)	8,620 (19,000)	8,620 (19,000)	8,620 (19,000)	8,620 (19,000)	8,620 (19,000)
<b>DIMENSIONS</b> (On standard specifications)							
Wheelbase		mm (in.)	3,861 (152.0)	4,445 (175.0)	4,750 (187.0)	5,207 (205.0)	5,385 (212.0)
Overall length		mm (in.)	6,162 (242.6)	7,076 (278.6)	7,686 (302.6)	8,143 (320.6)	7,686 (302.6)
Overall width		mm (in.)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)
Overall height		mm (in.)	2,715 (106.9)	2,715 (106.9)	2,715 (106.9)	2,715 (106.9)	2,715 (106.9)
BBC		mm (in.)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)
Cab to axle		mm (in.)	2,149 (84.6)	2,733 (107.6)	3,038 (119.6)	3,495 (137.6)	3,673 (144.6)
Rear overhang		mm (in.)	1,270 (50.0)	1,600 (63.0)	1,905 (75.0)	1,905 (75.0)	1,270 (50.0)
Frame height at	Front axle	mm (in.)	940 (37.0)	940 (37.0)	940 (37.0)	940 (37.0)	940 (37.0)
	Rear axle	mm (in.)	1,010 (39.8)	1,010 (39.8)	1,010 (39.8)	1,010 (39.8)	1,010 (39.8)
Road clearance (at diff. case)		mm (in.)	285 (11.2)	285 (11.2)	285 (11.2)	285 (11.2)	285 (11.2)
Tread	Front	mm (in.)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)
	Rear	mm (in.)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)
Turning radius Tire		mm (in.)	6,400 (252.0)	7,240 (285.0)	7,690 (302.8)	8,350 (328.7)	8,610 (339.0)
Turning radius Swept		mm (in.)	6,920 (272.4)	7,760 (305.5)	8,210 (323.2)	8,870 (349.2)	9,130 (359.4)
<b>CHASSIS WEIGHTS</b> (on std. spec., without spare tire & std. tool set)							
<b>MANUAL T/M</b>							
Total weight	MT	kg (lb.)	4,690 (10,338)	4,665 (10,283)	4,695 (10,348)	4,740 (10,448)	—
Front axle	MT	kg (lb.)	2,875 (6,338)	2,940 (6,478)	2,960 (6,523)	3,000 (6,613)	—
Rear axle	MT	kg (lb.)	1,815 (4,000)	1,725 (3,805)	1,735 (3,825)	1,740 (3,835)	—
Unsprung weight	Front	kg (lb.)	645 (1,420)	645 (1,420)	645 (1,420)	645 (1,420)	—
	Rear	kg (lb.)	1,120 (2,470)	1,120 (2,470)	1,120 (2,470)	1,120 (2,470)	—
<b>AUTO T/M</b>							
Total weight	ATM	kg (lb.)	4,650 (10,250)	4,625 (10,195)	4,655 (10,260)	4,705 (10,375)	4,685 (10,330)
Front axle	ATM	kg (lb.)	2,835 (6,250)	2,900 (6,390)	2,920 (6,435)	2,965 (6,540)	3,005 (6,625)
Rear axle	ATM	kg (lb.)	1,815 (4,000)	1,725 (3,805)	1,735 (3,825)	1,740 (3,835)	1,680 (3,705)
Unsprung weight	Front	kg (lb.)	645 (1,420)	645 (1,420)	645 (1,420)	645 (1,420)	645 (1,420)
	Rear	kg (lb.)	1,120 (2,470)	1,120 (2,470)	1,120 (2,470)	1,120 (2,470)	1,120 (2,470)
Center of gravity height from the ground		mm (in.)	790 (31.1)	790 (31.1)	790 (31.1)	790 (31.1)	790 (31.1)

Model			NJ8JPSA	NJ8JRSA	NJ8JTSA	NJ8JVSA
<b>CAPACITY</b>						
GVWR	Manual T/M	kg (lb.)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)
	Auto T/M	kg (lb.)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)
GAWR	Front	kg (lb.)	4,540 (10,000)	4,540 (10,000)	4,540 (10,000)	4,540 (10,000)
	Rear	kg (lb.)	8,620 (19,000)	8,620 (19,000)	8,620 (19,000)	8,620 (19,000)
<b>DIMENSIONS</b> (On standard specifications)						
Wheelbase		mm (in.)	5,512 (217.0)	5,969 (235.0)	6,426 (253.0)	6,883 (271.0)
Overall length		mm (in.)	9,007 (354.6)	9,464 (372.6)	9,921 (390.6)	9,921 (390.6)
Overall width		mm (in.)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)
Overall height		mm (in.)	2,715 (106.9)	2,715 (106.9)	2,715 (106.9)	2,715 (106.9)
BBC		mm (in.)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)
Cab to axle		mm (in.)	3,800 (149.6)	4,257 (167.6)	4,714 (185.6)	5,171 (203.6)
Rear overhang		mm (in.)	2,464 (97.0)	2,464 (97.0)	2,464 (97.0)	2,007 (79.0)
Frame height at	Front axle	mm (in.)	940 (37.0)	940 (37.0)	940 (37.0)	940 (37.0)
	Rear axle	mm (in.)	1,010 (39.8)	1,010 (39.8)	1,010 (39.8)	1,010 (39.8)
Road clearance (at diff. case)		mm (in.)	285 (11.2)	285 (11.2)	285 (11.2)	285 (11.2)
Tread	Front	mm (in.)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)
	Rear	mm (in.)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)
Turning radius Tire		mm (in.)	8,790 (346.1)	9,460 (372.4)	10,120 (398.4)	10,790 (424.8)
Turning radius Swept		mm (in.)	9,310 (366.5)	9,980 (392.9)	10,640 (418.9)	11,310 (445.3)
<b>CHASSIS WEIGHTS</b> (on std. spec., without spare tire & std. tool set)						
<b>MANUAL T/M</b>						
Total weight	MT	kg (lb.)	4,790 (10,558)	4,810 (10,603)	4,825 (10,638)	4,855 (10,703)
Front axle	MT	kg (lb.)	3,005 (6,623)	3,035 (6,688)	3,075 (6,778)	3,080 (6,788)
Rear axle	MT	kg (lb.)	1,785 (3,935)	1,775 (3,915)	1,750 (3,860)	1,775 (3,915)
Unsprung weight	Front	kg (lb.)	645 (1,420)	645 (1,420)	645 (1,420)	645 (1,420)
	Rear	kg (lb.)	1,120 (2,470)	1,120 (2,470)	1,120 (2,470)	1,120 (2,470)
<b>AUTO T/M</b>						
Total weight	ATM	kg (lb.)	4,755 (10,485)	4,770 (10,515)	4,785 (10,550)	4,815 (10,615)
Front axle	ATM	kg (lb.)	2,970 (6,550)	2,995 (6,600)	3,040 (6,705)	3,045 (6,715)
Rear axle	ATM	kg (lb.)	1,785 (3,935)	1,775 (3,915)	1,745 (3,845)	1,770 (3,900)
Unsprung weight	Front	kg (lb.)	645 (1,420)	645 (1,420)	645 (1,420)	645 (1,420)
	Rear	kg (lb.)	1,120 (2,470)	1,120 (2,470)	1,120 (2,470)	1,120 (2,470)
Center of gravity height from the ground		mm (in.)	790 (31.1)	790 (31.1)	790 (31.1)	790 (31.1)

## NJ8J

## J08E-VB

Fr. Axl : MFS10 Fr. Spg : 12,000 lbs

Rr. Axl : RS19 Rr. Spg : 19,000 lbs

Model			NJ8JGSA	NJ8JJSA	NJ8JLSA	NJ8JMSA	NJ8JNSA
<b>CAPACITY</b>							
GVWR	Manual T/M	kg (lb.)	—	—	—	—	—
	Auto T/M	kg (lb.)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)
GAWR	Front	kg (lb.)	4,540 (10,000)	4,540 (10,000)	4,540 (10,000)	4,540 (10,000)	4,540 (10,000)
	Rear	kg (lb.)	8,620 (19,000)	8,620 (19,000)	8,620 (19,000)	8,620 (19,000)	8,620 (19,000)
<b>DIMENSIONS</b> (On standard specifications)							
Wheelbase		mm (in.)	3,861 (152.0)	4,445 (175.0)	4,750 (187.0)	5,207 (205.0)	5,385 (212.0)
Overall length		mm (in.)	6,162 (242.6)	7,076 (278.6)	7,686 (302.6)	8,143 (320.6)	7,686 (302.6)
Overall width		mm (in.)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)
Overall height		mm (in.)	2,715 (106.9)	2,715 (106.9)	2,715 (106.9)	2,715 (106.9)	2,715 (106.9)
BBC		mm (in.)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)
Cab to axle		mm (in.)	2,149 (84.6)	2,733 (107.6)	3,038 (119.6)	3,495 (137.6)	3,673 (144.6)
Rear overhang		mm (in.)	1,270 (50.0)	1,600 (63.0)	1,905 (75.0)	1,905 (75.0)	1,270 (50.0)
Frame height at	Front axle	mm (in.)	940 (37.0)	940 (37.0)	940 (37.0)	940 (37.0)	940 (37.0)
	Rear axle	mm (in.)	1,010 (39.8)	1,010 (39.8)	1,010 (39.8)	1,010 (39.8)	1,010 (39.8)
Road clearance (at diff. case)		mm (in.)	285 (11.2)	285 (11.2)	285 (11.2)	285 (11.2)	285 (11.2)
Tread	Front	mm (in.)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)
	Rear	mm (in.)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)
Turning radius Tire		mm (in.)	6,400 (252.0)	7,240 (285.0)	7,690 (302.8)	8,350 (328.7)	8,610 (339.0)
Turning radius Swept		mm (in.)	6,920 (272.4)	7,760 (305.5)	8,210 (323.2)	8,870 (349.2)	9,130 (359.4)
<b>CHASSIS WEIGHTS</b> (on std. spec., without spare tire & std. tool set)							
<b>MANUAL T/M</b>							
Total weight	MT	kg (lb.)	—	—	—	—	—
Front axle	MT	kg (lb.)	—	—	—	—	—
Rear axle	MT	kg (lb.)	—	—	—	—	—
Unsprung weight	Front	kg (lb.)	—	—	—	—	—
	Rear	kg (lb.)	—	—	—	—	—
<b>AUTO T/M</b>							
Total weight	ATM	kg (lb.)	4,670 (10,295)	4,645 (10,240)	4,675 (10,305)	4,730 (10,430)	4,710 (10,385)
Front axle	ATM	kg (lb.)	2,845 (6,270)	2,905 (6,405)	2,925 (6,445)	2,970 (6,550)	3,005 (6,625)
Rear axle	ATM	kg (lb.)	1,825 (4,025)	1,740 (3,835)	1,750 (3,860)	1,760 (3,880)	1,705 (3,760)
Unsprung weight	Front	kg (lb.)	645 (1,420)	645 (1,420)	645 (1,420)	645 (1,420)	645 (1,420)
	Rear	kg (lb.)	1,120 (2,470)	1,120 (2,470)	1,120 (2,470)	1,120 (2,470)	1,120 (2,470)
Center of gravity height from the ground		mm (in.)	790 (31.1)	790 (31.1)	790 (31.1)	790 (31.1)	790 (31.1)

Model			NJ8JPSA	NJ8JRSA	NJ8JTSA	NJ8JVSA
<b>CAPACITY</b>						
GVWR	Manual T/M	kg (lb.)	—	—	—	—
	Auto T/M	kg (lb.)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)
GAWR	Front	kg (lb.)	4,540 (10,000)	4,540 (10,000)	4,540 (10,000)	4,540 (10,000)
	Rear	kg (lb.)	8,620 (19,000)	8,620 (19,000)	8,620 (19,000)	8,620 (19,000)
<b>DIMENSIONS</b> (On standard specifications)						
Wheelbase		mm (in.)	5,512 (217.0)	5,969 (235.0)	6,426 (253.0)	6,883 (271.0)
Overall length		mm (in.)	9,007 (354.6)	9,464 (372.6)	9,921 (390.6)	9,921 (390.6)
Overall width		mm (in.)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)
Overall height		mm (in.)	2,715 (106.9)	2,715 (106.9)	2,715 (106.9)	2,715 (106.9)
BBC		mm (in.)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)
Cab to axle		mm (in.)	3,800 (149.6)	4,257 (167.6)	4,714 (185.6)	5,171 (203.6)
Rear overhang		mm (in.)	2,464 (97.0)	2,464 (97.0)	2,464 (97.0)	2,007 (79.0)
Frame height at	Front axle	mm (in.)	940 (37.0)	940 (37.0)	940 (37.0)	940 (37.0)
	Rear axle	mm (in.)	1,010 (39.8)	1,010 (39.8)	1,010 (39.8)	1,010 (39.8)
Road clearance (at diff. case)		mm (in.)	285 (11.2)	285 (11.2)	285 (11.2)	285 (11.2)
Tread	Front	mm (in.)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)
	Rear	mm (in.)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)
Turning radius Tire		mm (in.)	8,790 (346.1)	9,460 (372.4)	10,120 (398.4)	10,790 (424.8)
Turning radius Swept		mm (in.)	9,310 (366.5)	9,980 (392.9)	10,640 (418.9)	11,310 (445.3)
<b>CHASSIS WEIGHTS</b> (on std. spec., without spare tire & std. tool set)						
<b>MANUAL T/M</b>						
Total weight	MT	kg (lb.)	—	—	—	—
Front axle	MT	kg (lb.)	—	—	—	—
Rear axle	MT	kg (lb.)	—	—	—	—
Unsprung weight	Front	kg (lb.)	—	—	—	—
	Rear	kg (lb.)	—	—	—	—
<b>AUTO T/M</b>						
Total weight	ATM	kg (lb.)	4,780 (10,540)	4,800 (10,580)	4,820 (10,625)	4,855 (10,705)
Front axle	ATM	kg (lb.)	2,975 (6,560)	2,995 (6,600)	3,055 (6,735)	3,060 (6,750)
Rear axle	ATM	kg (lb.)	1,805 (3,980)	1,805 (3,980)	1,765 (3,890)	1,795 (3,955)
Unsprung weight	Front	kg (lb.)	645 (1,420)	645 (1,420)	645 (1,420)	645 (1,420)
	Rear	kg (lb.)	1,120 (2,470)	1,120 (2,470)	1,120 (2,470)	1,120 (2,470)
Center of gravity height from the ground		mm (in.)	790 (31.1)	790 (31.1)	790 (31.1)	790 (31.1)



**NJ8J****J08E-VC****Fr. Axl : MFS10 Fr. Spg : 8,000 lbs****Rr. Axl : RS19 Rr. Spg : 19,000 lbs**

Model			NJ8JGSA	NJ8JJSA	NJ8JLSA	NJ8JMSA	NJ8JNSA
<b>CAPACITY</b>							
GVWR	Manual T/M	kg (lb.)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)	—
	Auto T/M	kg (lb.)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)
GAWR	Front	kg (lb.)	3,630 (8,000)	3,630 (8,000)	3,630 (8,000)	3,630 (8,000)	3,630 (8,000)
	Rear	kg (lb.)	8,620 (19,000)	8,620 (19,000)	8,620 (19,000)	8,620 (19,000)	8,620 (19,000)
<b>DIMENSIONS</b> (On standard specifications)							
Wheelbase		mm (in.)	3,861 (152.0)	4,445 (175.0)	4,750 (187.0)	5,207 (205.0)	5,385 (212.0)
Overall length		mm (in.)	6,162 (242.6)	7,076 (278.6)	7,686 (302.6)	8,143 (320.6)	7,686 (302.6)
Overall width		mm (in.)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)
Overall height		mm (in.)	2,725 (107.3)	2,725 (107.3)	2,725 (107.3)	2,725 (107.3)	2,725 (107.3)
BBC		mm (in.)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)
Cab to axle		mm (in.)	2,149 (84.6)	2,733 (107.6)	3,038 (119.6)	3,495 (137.6)	3,673 (144.6)
Rear overhang		mm (in.)	1,270 (50.0)	1,600 (63.0)	1,905 (75.0)	1,905 (75.0)	1,270 (50.0)
Frame height at	Front axle	mm (in.)	955 (37.6)	955 (37.6)	955 (37.6)	955 (37.6)	955 (37.6)
	Rear axle	mm (in.)	1,010 (39.8)	1,010 (39.8)	1,010 (39.8)	1,010 (39.8)	1,010 (39.8)
Road clearance (at diff. case)		mm (in.)	285 (11.2)	285 (11.2)	285 (11.2)	285 (11.2)	285 (11.2)
Tread	Front	mm (in.)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)
	Rear	mm (in.)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)
Turning radius Tire		mm (in.)	6,400 (252.0)	7,240 (285.0)	7,690 (302.8)	8,350 (328.7)	8,610 (339.0)
Turning radius Swept		mm (in.)	6,920 (272.4)	7,760 (305.5)	8,210 (323.2)	8,870 (349.2)	9,130 (359.4)
<b>CHASSIS WEIGHTS</b> (on std. spec., without spare tire & std. tool set)							
<b>MANUAL T/M</b>							
Total weight	MT	kg (lb.)	4,655 (10,263)	4,630 (10,208)	4,660 (10,273)	4,710 (10,383)	—
Front axle	MT	kg (lb.)	2,840 (6,263)	2,905 (6,403)	2,925 (6,448)	2,970 (6,548)	—
Rear axle	MT	kg (lb.)	1,815 (4,000)	1,725 (3,805)	1,735 (3,825)	1,740 (3,835)	—
Unsprung weight	Front	kg (lb.)	615 (1,355)	615 (1,355)	615 (1,355)	615 (1,355)	—
	Rear	kg (lb.)	1,120 (2,470)	1,120 (2,470)	1,120 (2,470)	1,120 (2,470)	—
<b>AUTO T/M</b>							
Total weight	ATM	kg (lb.)	4,620 (10,185)	4,595 (10,130)	4,620 (10,185)	4,670 (10,295)	4,650 (10,250)
Front axle	ATM	kg (lb.)	2,805 (6,185)	2,870 (6,325)	2,885 (6,360)	2,930 (6,460)	2,970 (6,545)
Rear axle	ATM	kg (lb.)	1,815 (4,000)	1,725 (3,805)	1,735 (3,825)	1,740 (3,835)	1,680 (3,705)
Unsprung weight	Front	kg (lb.)	615 (1,355)	615 (1,355)	615 (1,355)	615 (1,355)	615 (1,355)
	Rear	kg (lb.)	1,120 (2,470)	1,120 (2,470)	1,120 (2,470)	1,120 (2,470)	1,120 (2,470)
Center of gravity height from the ground		mm (in.)	790 (31.1)	790 (31.1)	790 (31.1)	790 (31.1)	790 (31.1)



Model			NJ8JPSA	NJ8JRSA	NJ8JTSA	NJ8JVSA
<b>CAPACITY</b>						
GVWR	Manual T/M	kg (lb.)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)
	Auto T/M	kg (lb.)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)
GAWR	Front	kg (lb.)	3,630 (8,000)	3,630 (8,000)	3,630 (8,000)	3,630 (8,000)
	Rear	kg (lb.)	8,620 (19,000)	8,620 (19,000)	8,620 (19,000)	8,620 (19,000)
<b>DIMENSIONS</b> (On standard specifications)						
Wheelbase		mm (in.)	5,512 (217.0)	5,969 (235.0)	6,426 (253.0)	6,883 (271.0)
Overall length		mm (in.)	9,007 (354.6)	9,464 (372.6)	9,921 (390.6)	9,921 (390.6)
Overall width		mm (in.)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)
Overall height		mm (in.)	2,725 (107.3)	2,725 (107.3)	2,725 (107.3)	2,725 (107.3)
BBC		mm (in.)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)
Cab to axle		mm (in.)	3,800 (149.6)	4,257 (167.6)	4,714 (185.6)	5,171 (203.6)
Rear overhang		mm (in.)	2,464 (97.0)	2,464 (97.0)	2,464 (97.0)	2,007 (79.0)
Frame height at	Front axle	mm (in.)	955 (37.6)	955 (37.6)	955 (37.6)	955 (37.6)
	Rear axle	mm (in.)	1,010 (39.8)	1,010 (39.8)	1,010 (39.8)	1,010 (39.8)
Road clearance (at diff. case)		mm (in.)	285 (11.2)	285 (11.2)	285 (11.2)	285 (11.2)
Tread	Front	mm (in.)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)
	Rear	mm (in.)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)
Turning radius Tire		mm (in.)	8,790 (346.1)	9,460 (372.4)	10,120 (398.4)	10,790 (424.8)
Turning radius Swept		mm (in.)	9,310 (366.5)	9,980 (392.9)	10,640 (418.9)	11,310 (445.3)
<b>CHASSIS WEIGHTS</b> (on std. spec., without spare tire & std. tool set)						
<b>MANUAL T/M</b>						
Total weight	MT	kg (lb.)	4,760 (10,493)	4,780 (10,538)	4,795 (10,573)	4,820 (10,628)
Front axle	MT	kg (lb.)	2,975 (6,558)	3,005 (6,623)	3,045 (6,713)	3,045 (6,713)
Rear axle	MT	kg (lb.)	1,785 (3,935)	1,775 (3,915)	1,750 (3,860)	1,775 (3,915)
Unsprung weight	Front	kg (lb.)	615 (1,355)	615 (1,355)	615 (1,355)	615 (1,355)
	Rear	kg (lb.)	1,120 (2,470)	1,120 (2,470)	1,120 (2,470)	1,120 (2,470)
<b>AUTO T/M</b>						
Total weight	ATM	kg (lb.)	4,720 (10,405)	4,740 (10,450)	4,755 (10,485)	4,785 (10,550)
Front axle	ATM	kg (lb.)	2,935 (6,470)	2,965 (6,535)	3,010 (6,640)	3,015 (6,650)
Rear axle	ATM	kg (lb.)	1,785 (3,935)	1,775 (3,915)	1,745 (3,845)	1,770 (3,900)
Unsprung weight	Front	kg (lb.)	615 (1,355)	615 (1,355)	615 (1,355)	615 (1,355)
	Rear	kg (lb.)	1,120 (2,470)	1,120 (2,470)	1,120 (2,470)	1,120 (2,470)
Center of gravity height from the ground		mm (in.)	790 (31.1)	790 (31.1)	790 (31.1)	790 (31.1)

## NJ8J

## J08E-VB

Fr. Axl : MFS10 Fr. Spg : 8,000 lbs

Rr. Axl : RS19 Rr. Spg : 19,000 lbs

Model			NJ8JGSA	NJ8JJSA	NJ8JLSA	NJ8JMSA	NJ8JNSA
<b>CAPACITY</b>							
GVWR	Manual T/M	kg (lb.)	—	—	—	—	—
	Auto T/M	kg (lb.)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)
GAWR	Front	kg (lb.)	3,630 (8,000)	3,630 (8,000)	3,630 (8,000)	3,630 (8,000)	3,630 (8,000)
	Rear	kg (lb.)	8,620 (19,000)	8,620 (19,000)	8,620 (19,000)	8,620 (19,000)	8,620 (19,000)
<b>DIMENSIONS</b> (On standard specifications)							
Wheelbase		mm (in.)	3,861 (152.0)	4,445 (175.0)	4,750 (187.0)	5,207 (205.0)	5,385 (212.0)
Overall length		mm (in.)	6,162 (242.6)	7,076 (278.6)	7,686 (302.6)	8,143 (320.6)	7,686 (302.6)
Overall width		mm (in.)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)
Overall height		mm (in.)	2,725 (107.3)	2,725 (107.3)	2,725 (107.3)	2,725 (107.3)	2,725 (107.3)
BBC		mm (in.)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)
Cab to axle		mm (in.)	2,149 (84.6)	2,733 (107.6)	3,038 (119.6)	3,495 (137.6)	3,673 (144.6)
Rear overhang		mm (in.)	1,270 (50.0)	1,600 (63.0)	1,905 (75.0)	1,905 (75.0)	1,270 (50.0)
Frame height at	Front axle	mm (in.)	955 (37.6)	955 (37.6)	955 (37.6)	955 (37.6)	955 (37.6)
	Rear axle	mm (in.)	1,010 (39.8)	1,010 (39.8)	1,010 (39.8)	1,010 (39.8)	1,010 (39.8)
Road clearance (at diff. case)		mm (in.)	285 (11.2)	285 (11.2)	285 (11.2)	285 (11.2)	285 (11.2)
Tread	Front	mm (in.)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)
	Rear	mm (in.)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)
Turning radius Tire		mm (in.)	6,400 (252.0)	7,240 (285.0)	7,690 (302.8)	8,350 (328.7)	8,610 (339.0)
Turning radius Swept		mm (in.)	6,920 (272.4)	7,760 (305.5)	8,210 (323.2)	8,870 (349.2)	9,130 (359.4)
<b>CHASSIS WEIGHTS</b> (on std. spec., without spare tire & std. tool set)							
<b>MANUAL T/M</b>							
Total weight	MT	kg (lb.)	—	—	—	—	—
Front axle	MT	kg (lb.)	—	—	—	—	—
Rear axle	MT	kg (lb.)	—	—	—	—	—
Unsprung weight	Front	kg (lb.)	—	—	—	—	—
	Rear	kg (lb.)	—	—	—	—	—
<b>AUTO T/M</b>							
Total weight	ATM	kg (lb.)	4,635 (10,220)	4,615 (10,175)	4,645 (10,240)	4,700 (10,360)	4,680 (10,315)
Front axle	ATM	kg (lb.)	2,810 (6,195)	2,875 (6,340)	2,895 (6,380)	2,940 (6,480)	2,975 (6,555)
Rear axle	ATM	kg (lb.)	1,825 (4,025)	1,740 (3,835)	1,750 (3,860)	1,760 (3,880)	1,705 (3,760)
Unsprung weight	Front	kg (lb.)	615 (1,355)	615 (1,355)	615 (1,355)	615 (1,355)	615 (1,355)
	Rear	kg (lb.)	1,120 (2,470)	1,120 (2,470)	1,120 (2,470)	1,120 (2,470)	1,120 (2,470)
Center of gravity height from the ground		mm (in.)	790 (31.1)	790 (31.1)	790 (31.1)	790 (31.1)	790 (31.1)

Model			NJ8JPSA	NJ8JRSA	NJ8JTSA	NJ8JVSA
<b>CAPACITY</b>						
GVWR	Manual T/M	kg (lb.)	—	—	—	—
	Auto T/M	kg (lb.)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)
GAWR	Front	kg (lb.)	3,630 (8,000)	3,630 (8,000)	3,630 (8,000)	3,630 (8,000)
	Rear	kg (lb.)	8,620 (19,000)	8,620 (19,000)	8,620 (19,000)	8,620 (19,000)
<b>DIMENSIONS</b> (On standard specifications)						
Wheelbase		mm (in.)	5,512 (217.0)	5,969 (235.0)	6,426 (253.0)	6,883 (271.0)
Overall length		mm (in.)	9,007 (354.6)	9,464 (372.6)	9,921 (390.6)	9,921 (390.6)
Overall width		mm (in.)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)
Overall height		mm (in.)	2,725 (107.3)	2,725 (107.3)	2,725 (107.3)	2,725 (107.3)
BBC		mm (in.)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)
Cab to axle		mm (in.)	3,800 (149.6)	4,257 (167.6)	4,714 (185.6)	5,171 (203.6)
Rear overhang		mm (in.)	2,464 (97.0)	2,464 (97.0)	2,464 (97.0)	2,007 (79.0)
Frame height at	Front axle	mm (in.)	955 (37.6)	955 (37.6)	955 (37.6)	955 (37.6)
	Rear axle	mm (in.)	1,010 (39.8)	1,010 (39.8)	1,010 (39.8)	1,010 (39.8)
Road clearance (at diff. case)		mm (in.)	285 (11.2)	285 (11.2)	285 (11.2)	285 (11.2)
Tread	Front	mm (in.)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)
	Rear	mm (in.)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)
Turning radius Tire		mm (in.)	8,790 (346.1)	9,460 (372.4)	10,120 (398.4)	10,790 (424.8)
Turning radius Swept		mm (in.)	9,310 (366.5)	9,980 (392.9)	10,640 (418.9)	11,310 (445.3)
<b>CHASSIS WEIGHTS</b> (on std. spec., without spare tire & std. tool set)						
<b>MANUAL T/M</b>						
Total weight	MT	kg (lb.)	—	—	—	—
Front axle	MT	kg (lb.)	—	—	—	—
Rear axle	MT	kg (lb.)	—	—	—	—
Unsprung weight	Front	kg (lb.)	—	—	—	—
	Rear	kg (lb.)	—	—	—	—
<b>AUTO T/M</b>						
Total weight	ATM	kg (lb.)	4,750 (10,470)	4,770 (10,515)	4,790 (10,560)	4,820 (10,625)
Front axle	ATM	kg (lb.)	2,945 (6,490)	2,965 (6,535)	3,025 (6,670)	3,025 (6,670)
Rear axle	ATM	kg (lb.)	1,805 (3,980)	1,805 (3,980)	1,765 (3,890)	1,795 (3,955)
Unsprung weight	Front	kg (lb.)	615 (1,355)	615 (1,355)	615 (1,355)	615 (1,355)
	Rear	kg (lb.)	1,120 (2,470)	1,120 (2,470)	1,120 (2,470)	1,120 (2,470)
Center of gravity height from the ground		mm (in.)	790 (31.1)	790 (31.1)	790 (31.1)	790 (31.1)

**NJ8J****LOW PROFILE / J08E-VC****Fr. Axl : MFS10 Fr. Spg : 8,000 lbs****Rr. Axl : RS17 Rr. Spg : 19,000 lbs**

Model			NJ8JGSA	NJ8JJSA	NJ8JLSA	NJ8JMSA	NJ8JNSA
<b>CAPACITY</b>							
GVWR	Manual T/M	kg (lb.)	—	—	—	—	—
	Auto T/M	kg (lb.)	11,570 (25,500)	11,570 (25,500)	11,570 (25,500)	11,570 (25,500)	11,570 (25,500)
GAWR	Front	kg (lb.)	3,630 (8,000)	3,630 (8,000)	3,630 (8,000)	3,630 (8,000)	3,630 (8,000)
	Rear	kg (lb.)	7,940 (17,500)	7,940 (17,500)	7,940 (17,500)	7,940 (17,500)	7,940 (17,500)
<b>DIMENSIONS</b> (On standard specifications)							
Wheelbase		mm (in.)	3,861 (152.0)	4,445 (175.0)	4,750 (187.0)	5,207 (205.0)	5,385 (212.0)
Overall length		mm (in.)	6,162 (242.6)	7,076 (278.6)	7,686 (302.6)	8,143 (320.6)	7,686 (302.6)
Overall width		mm (in.)	2,430 (95.7)	2,430 (95.7)	2,430 (95.7)	2,430 (95.7)	2,430 (95.7)
Overall height		mm (in.)	2,615 (103.0)	2,615 (103.0)	2,615 (103.0)	2,615 (103.0)	2,615 (103.0)
BBC		mm (in.)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)
Cab to axle		mm (in.)	2,149 (84.6)	2,733 (107.6)	3,038 (119.6)	3,495 (137.6)	3,673 (144.6)
Rear overhang		mm (in.)	1,270 (50.0)	1,600 (63.0)	1,905 (75.0)	1,905 (75.0)	1,270 (50.0)
Frame height at	Front axle	mm (in.)	845 (33.3)	845 (33.3)	845 (33.3)	845 (33.3)	845 (33.3)
	Rear axle	mm (in.)	900 (35.4)	900 (35.4)	900 (35.4)	900 (35.4)	900 (35.4)
Road clearance (at diff. case)		mm (in.)	180 (7.1)	180 (7.1)	180 (7.1)	180 (7.1)	180 (7.1)
Tread	Front	mm (in.)	2,030 (79.9)	2,030 (79.9)	2,030 (79.9)	2,030 (79.9)	2,030 (79.9)
	Rear	mm (in.)	1,840 (72.4)	1,840 (72.4)	1,840 (72.4)	1,840 (72.4)	1,840 (72.4)
Turning radius Tire		mm (in.)	6,410 (252.4)	7,250 (285.4)	7,690 (302.8)	8,360 (329.1)	8,620 (339.4)
Turning radius Swept		mm (in.)	6,925 (272.6)	7,765 (305.7)	8,205 (323.0)	8,875 (349.4)	9,135 (359.6)
<b>CHASSIS WEIGHTS</b> (on std. spec., without spare tire & std. tool set)							
<b>MANUAL T/M</b>							
Total weight	MT	kg (lb.)	—	—	—	—	—
Front axle	MT	kg (lb.)	—	—	—	—	—
Rear axle	MT	kg (lb.)	—	—	—	—	—
Unsprung weight	Front	kg (lb.)	—	—	—	—	—
	Rear	kg (lb.)	—	—	—	—	—
<b>AUTO T/M</b>							
Total weight	ATM	kg (lb.)	4,470 (9,855)	4,445 (9,800)	4,470 (9,855)	4,520 (9,965)	4,500 (9,920)
Front axle	ATM	kg (lb.)	2,765 (6,095)	2,830 (6,240)	2,845 (6,275)	2,890 (6,370)	2,925 (6,450)
Rear axle	ATM	kg (lb.)	1,705 (3,760)	1,615 (3,560)	1,625 (3,580)	1,630 (3,595)	1,575 (3,470)
Unsprung weight	Front	kg (lb.)	570 (1,255)	570 (1,255)	570 (1,255)	570 (1,255)	570 (1,255)
	Rear	kg (lb.)	1,010 (2,225)	1,010 (2,225)	1,010 (2,225)	1,010 (2,225)	1,010 (2,225)
Center of gravity height from the ground		mm (in.)	690 (27.2)	690 (27.2)	690 (27.2)	690 (27.2)	690 (27.2)

Model			NJ8JPSA	NJ8JRSA	NJ8JTSA	NJ8JVSA
<b>CAPACITY</b>						
GVWR	Manual T/M	kg (lb.)	—	—	—	—
	Auto T/M	kg (lb.)	11,570 (25,500)	11,570 (25,500)	11,570 (25,500)	11,570 (25,500)
GAWR	Front	kg (lb.)	3,630 (8,000)	3,630 (8,000)	3,630 (8,000)	3,630 (8,000)
	Rear	kg (lb.)	7,940 (17,500)	7,940 (17,500)	7,940 (17,500)	7,940 (17,500)
<b>DIMENSIONS</b> (On standard specifications)						
Wheelbase		mm (in.)	5,512 (217.0)	5,969 (235.0)	6,426 (253.0)	6,883 (271.0)
Overall length		mm (in.)	9,007 (354.6)	9,464 (372.6)	9,921 (390.6)	9,921 (390.6)
Overall width		mm (in.)	2,430 (95.7)	2,430 (95.7)	2,430 (95.7)	2,430 (95.7)
Overall height		mm (in.)	2,615 (103.0)	2,615 (103.0)	2,615 (103.0)	2,615 (103.0)
BBC		mm (in.)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)
Cab to axle		mm (in.)	3,800 (149.6)	4,257 (167.6)	4,714 (185.6)	5,171 (203.6)
Rear overhang		mm (in.)	2,464 (97.0)	2,464 (97.0)	2,464 (97.0)	2,007 (79.0)
Frame height at	Front axle	mm (in.)	845 (33.3)	845 (33.3)	845 (33.3)	845 (33.3)
	Rear axle	mm (in.)	900 (35.4)	900 (35.4)	900 (35.4)	900 (35.4)
Road clearance (at diff. case)		mm (in.)	180 (7.1)	180 (7.1)	180 (7.1)	180 (7.1)
Tread	Front	mm (in.)	2,030 (79.9)	2,030 (79.9)	2,030 (79.9)	2,030 (79.9)
	Rear	mm (in.)	1,840 (72.4)	1,840 (72.4)	1,840 (72.4)	1,840 (72.4)
Turning radius Tire		mm (in.)	8,800 (346.5)	9,470 (372.8)	10,130 (398.8)	10,800 (425.2)
Turning radius Swept		mm (in.)	9,315 (366.7)	9,985 (393.1)	10,645 (419.1)	11,315 (445.5)
<b>CHASSIS WEIGHTS</b> (on std. spec., without spare tire & std. tool set)						
<b>MANUAL T/M</b>						
Total weight	MT	kg (lb.)	—	—	—	—
Front axle	MT	kg (lb.)	—	—	—	—
Rear axle	MT	kg (lb.)	—	—	—	—
Unsprung weight	Front	kg (lb.)	—	—	—	—
	Rear	kg (lb.)	—	—	—	—
<b>AUTO T/M</b>						
Total weight	ATM	kg (lb.)	4,570 (10,075)	4,590 (10,120)	4,605 (10,150)	4,635 (10,220)
Front axle	ATM	kg (lb.)	2,895 (6,380)	2,920 (6,440)	2,965 (6,535)	2,970 (6,550)
Rear axle	ATM	kg (lb.)	1,675 (3,695)	1,670 (3,680)	1,640 (3,615)	1,665 (3,670)
Unsprung weight	Front	kg (lb.)	570 (1,255)	570 (1,255)	570 (1,255)	570 (1,255)
	Rear	kg (lb.)	1,010 (2,225)	1,010 (2,225)	1,010 (2,225)	1,010 (2,225)
Center of gravity height from the ground		mm (in.)	690 (27.2)	690 (27.2)	690 (27.2)	690 (27.2)

**NJ8J****LOW PROFILE / J08E-VB****Fr. Axl : MFS10 Fr. Spg : 8,000 lbs****Rr. Axl : RS17 Rr. Spg : 19,000 lbs**

Model			NJ8JGSA	NJ8JJSA	NJ8JLSA	NJ8JMSA	NJ8JNSA
<b>CAPACITY</b>							
GVWR	Manual T/M	kg (lb.)	—	—	—	—	—
	Auto T/M	kg (lb.)	11,570 (25,500)	11,570 (25,500)	11,570 (25,500)	11,570 (25,500)	11,570 (25,500)
GAWR	Front	kg (lb.)	3,630 (8,000)	3,630 (8,000)	3,630 (8,000)	3,630 (8,000)	3,630 (8,000)
	Rear	kg (lb.)	7,940 (17,500)	7,940 (17,500)	7,940 (17,500)	7,940 (17,500)	7,940 (17,500)
<b>DIMENSIONS</b> (On standard specifications)							
Wheelbase		mm (in.)	3,861 (152.0)	4,445 (175.0)	4,750 (187.0)	5,207 (205.0)	5,385 (212.0)
Overall length		mm (in.)	6,162 (242.6)	7,076 (278.6)	7,686 (302.6)	8,143 (320.6)	7,686 (302.6)
Overall width		mm (in.)	2,430 (95.7)	2,430 (95.7)	2,430 (95.7)	2,430 (95.7)	2,430 (95.7)
Overall height		mm (in.)	2,615 (103.0)	2,615 (103.0)	2,615 (103.0)	2,615 (103.0)	2,615 (103.0)
BBC		mm (in.)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)
Cab to axle		mm (in.)	2,149 (84.6)	2,733 (107.6)	3,038 (119.6)	3,495 (137.6)	3,673 (144.6)
Rear overhang		mm (in.)	1,270 (50.0)	1,600 (63.0)	1,905 (75.0)	1,905 (75.0)	1,270 (50.0)
Frame height at	Front axle	mm (in.)	845 (33.3)	845 (33.3)	845 (33.3)	845 (33.3)	845 (33.3)
	Rear axle	mm (in.)	900 (35.4)	900 (35.4)	900 (35.4)	900 (35.4)	900 (35.4)
Road clearance (at diff. case)		mm (in.)	180 (7.1)	180 (7.1)	180 (7.1)	180 (7.1)	180 (7.1)
Tread	Front	mm (in.)	2,030 (79.9)	2,030 (79.9)	2,030 (79.9)	2,030 (79.9)	2,030 (79.9)
	Rear	mm (in.)	1,840 (72.4)	1,840 (72.4)	1,840 (72.4)	1,840 (72.4)	1,840 (72.4)
Turning radius Tire		mm (in.)	6,410 (252.4)	7,250 (285.4)	7,690 (302.8)	8,360 (329.1)	8,620 (339.4)
Turning radius Swept		mm (in.)	6,925 (272.6)	7,765 (305.7)	8,205 (323.0)	8,875 (349.4)	9,135 (359.6)
<b>CHASSIS WEIGHTS</b> (on std. spec., without spare tire & std. tool set)							
<b>MANUAL T/M</b>							
Total weight	MT	kg (lb.)	—	—	—	—	—
Front axle	MT	kg (lb.)	—	—	—	—	—
Rear axle	MT	kg (lb.)	—	—	—	—	—
Unsprung weight	Front	kg (lb.)	—	—	—	—	—
	Rear	kg (lb.)	—	—	—	—	—
<b>AUTO T/M</b>							
Total weight	ATM	kg (lb.)	4,485 (9,890)	4,465 (9,845)	4,495 (9,910)	4,550 (10,030)	4,530 (9,985)
Front axle	ATM	kg (lb.)	2,765 (6,100)	2,835 (6,250)	2,855 (6,295)	2,895 (6,380)	2,935 (6,470)
Rear axle	ATM	kg (lb.)	1,720 (3,790)	1,630 (3,595)	1,640 (3,615)	1,655 (3,650)	1,595 (3,515)
Unsprung weight	Front	kg (lb.)	570 (1,255)	570 (1,255)	570 (1,255)	570 (1,255)	570 (1,255)
	Rear	kg (lb.)	1,010 (2,225)	1,010 (2,225)	1,010 (2,225)	1,010 (2,225)	1,010 (2,225)
Center of gravity height from the ground		mm (in.)	690 (27.2)	690 (27.2)	690 (27.2)	690 (27.2)	690 (27.2)

Model			NJ8JPSA	NJ8JRSA	NJ8JTSA	NJ8JVSA
<b>CAPACITY</b>						
GVWR	Manual T/M	kg (lb.)	—	—	—	—
	Auto T/M	kg (lb.)	11,570 (25,500)	11,570 (25,500)	11,570 (25,500)	11,570 (25,500)
GAWR	Front	kg (lb.)	3,630 (8,000)	3,630 (8,000)	3,630 (8,000)	3,630 (8,000)
	Rear	kg (lb.)	7,940 (17,500)	7,940 (17,500)	7,940 (17,500)	7,940 (17,500)
<b>DIMENSIONS</b> (On standard specifications)						
Wheelbase		mm (in.)	5,512 (217.0)	5,969 (235.0)	6,426 (253.0)	6,883 (271.0)
Overall length		mm (in.)	9,007 (354.6)	9,464 (372.6)	9,921 (390.6)	9,921 (390.6)
Overall width		mm (in.)	2,430 (95.7)	2,430 (95.7)	2,430 (95.7)	2,430 (95.7)
Overall height		mm (in.)	2,615 (103.0)	2,615 (103.0)	2,615 (103.0)	2,615 (103.0)
BBC		mm (in.)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)
Cab to axle		mm (in.)	3,800 (149.6)	4,257 (167.6)	4,714 (185.6)	5,171 (203.6)
Rear overhang		mm (in.)	2,464 (97.0)	2,464 (97.0)	2,464 (97.0)	2,007 (79.0)
Frame height at	Front axle	mm (in.)	845 (33.3)	845 (33.3)	845 (33.3)	845 (33.3)
	Rear axle	mm (in.)	900 (35.4)	900 (35.4)	900 (35.4)	900 (35.4)
Road clearance (at diff. case)		mm (in.)	180 (7.1)	180 (7.1)	180 (7.1)	180 (7.1)
Tread	Front	mm (in.)	2,030 (79.9)	2,030 (79.9)	2,030 (79.9)	2,030 (79.9)
	Rear	mm (in.)	1,840 (72.4)	1,840 (72.4)	1,840 (72.4)	1,840 (72.4)
Turning radius Tire		mm (in.)	8,800 (346.5)	9,470 (372.8)	10,130 (398.8)	10,800 (425.2)
Turning radius Swept		mm (in.)	9,315 (366.7)	9,985 (393.1)	10,645 (419.1)	11,315 (445.5)
<b>CHASSIS WEIGHTS</b> (on std. spec., without spare tire & std. tool set)						
<b>MANUAL T/M</b>						
Total weight	MT	kg (lb.)	—	—	—	—
Front axle	MT	kg (lb.)	—	—	—	—
Rear axle	MT	kg (lb.)	—	—	—	—
Unsprung weight	Front	kg (lb.)	—	—	—	—
	Rear	kg (lb.)	—	—	—	—
<b>AUTO T/M</b>						
Total weight	ATM	kg (lb.)	4,600 (10,140)	4,620 (10,185)	4,640 (10,230)	4,670 (10,295)
Front axle	ATM	kg (lb.)	2,900 (6,390)	2,925 (6,450)	2,980 (6,570)	2,985 (6,580)
Rear axle	ATM	kg (lb.)	1,700 (3,750)	1,695 (3,735)	1,660 (3,660)	1,685 (3,715)
Unsprung weight	Front	kg (lb.)	570 (1,255)	570 (1,255)	570 (1,255)	570 (1,255)
	Rear	kg (lb.)	1,010 (2,225)	1,010 (2,225)	1,010 (2,225)	1,010 (2,225)
Center of gravity height from the ground		mm (in.)	690 (27.2)	690 (27.2)	690 (27.2)	690 (27.2)

**NJ8J (Rr AIR SUS.)****J08E-VC****Fr. Axl : MFS10 Fr. Spg : 12,000 lbs****Rr. Axl : RS19 Rr. Spg : 19,000 lbs**

Model			NJ8JGSG	NJ8JJSJG	NJ8JLSJG	NJ8JMSJG	NJ8JNSJG
<b>CAPACITY</b>							
GVWR	Manual T/M	kg (lb.)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)
	Auto T/M	kg (lb.)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)
GAWR	Front	kg (lb.)	4,540 (10,000)	4,540 (10,000)	4,540 (10,000)	4,540 (10,000)	4,540 (10,000)
	Rear	kg (lb.)	8,620 (19,000)	8,620 (19,000)	8,620 (19,000)	8,620 (19,000)	8,620 (19,000)
<b>DIMENSIONS</b> (On standard specifications)							
Wheelbase		mm (in.)	3,861 (152.0)	4,445 (175.0)	4,750 (187.0)	5,207 (205.0)	5,385 (212.0)
Overall length		mm (in.)	6,162 (242.6)	7,076 (278.6)	7,686 (302.6)	8,143 (320.6)	7,686 (302.6)
Overall width		mm (in.)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)
Overall height		mm (in.)	2,710 (106.7)	2,710 (106.7)	2,710 (106.7)	2,710 (106.7)	2,710 (106.7)
BBC		mm (in.)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)
Cab to axle		mm (in.)	2,149 (84.6)	2,733 (107.6)	3,038 (119.6)	3,495 (137.6)	3,673 (144.6)
Rear overhang		mm (in.)	1,270 (50.0)	1,600 (63.0)	1,905 (75.0)	1,905 (75.0)	1,270 (50.0)
Frame height at	Front axle	mm (in.)	940 (37.0)	940 (37.0)	940 (37.0)	940 (37.0)	940 (37.0)
	Rear axle	mm (in.)	990 (39.0)	990 (39.0)	990 (39.0)	990 (39.0)	990 (39.0)
Road clearance (at diff. case)		mm (in.)	285 (11.2)	285 (11.2)	285 (11.2)	285 (11.2)	285 (11.2)
Tread	Front	mm (in.)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)
	Rear	mm (in.)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)
Turning radius Tire		mm (in.)	6,400 (252.0)	7,240 (285.0)	7,690 (302.8)	8,350 (328.7)	8,610 (339.0)
Turning radius Swept		mm (in.)	6,920 (272.4)	7,760 (305.5)	8,210 (323.2)	8,870 (349.2)	9,130 (359.4)
<b>CHASSIS WEIGHTS</b> (on std. spec., without spare tire & std. tool set)							
<b>MANUAL T/M</b>							
Total weight	MT	kg (lb.)	4,675 (10,308)	4,640 (10,228)	4,670 (10,293)	4,720 (10,408)	4,700 (10,363)
Front axle	MT	kg (lb.)	2,875 (6,338)	2,930 (6,458)	2,955 (6,513)	2,995 (6,603)	3,035 (6,693)
Rear axle	MT	kg (lb.)	1,800 (3,970)	1,710 (3,770)	1,715 (3,780)	1,725 (3,805)	1,665 (3,670)
Unsprung weight	Front	kg (lb.)	645 (1,420)	645 (1,420)	645 (1,420)	645 (1,420)	645 (1,420)
	Rear	kg (lb.)	1,105 (2,435)	1,105 (2,435)	1,105 (2,435)	1,105 (2,435)	1,105 (2,435)
<b>AUTO T/M</b>							
Total weight	ATM	kg (lb.)	4,635 (10,220)	4,605 (10,150)	4,630 (10,205)	4,680 (10,315)	4,660 (10,275)
Front axle	ATM	kg (lb.)	2,835 (6,250)	2,900 (6,390)	2,915 (6,425)	2,960 (6,525)	2,995 (6,605)
Rear axle	ATM	kg (lb.)	1,800 (3,970)	1,705 (3,760)	1,715 (3,780)	1,720 (3,790)	1,665 (3,670)
Unsprung weight	Front	kg (lb.)	645 (1,420)	645 (1,420)	645 (1,420)	645 (1,420)	645 (1,420)
	Rear	kg (lb.)	1,105 (2,435)	1,105 (2,435)	1,105 (2,435)	1,105 (2,435)	1,105 (2,435)
Center of gravity height from the ground		mm (in.)	785 (30.9)	785 (30.9)	785 (30.9)	785 (30.9)	785 (30.9)



Model			NJ8JPSG	NJ8JRSG	NJ8JTSG	NJ8JVSG
<b>CAPACITY</b>						
GVWR	Manual T/M	kg (lb.)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)
	Auto T/M	kg (lb.)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)
GAWR	Front	kg (lb.)	4,540 (10,000)	4,540 (10,000)	4,540 (10,000)	4,540 (10,000)
	Rear	kg (lb.)	8,620 (19,000)	8,620 (19,000)	8,620 (19,000)	8,620 (19,000)
<b>DIMENSIONS</b> (On standard specifications)						
Wheelbase		mm (in.)	5,512 (217.0)	5,969 (235.0)	6,426 (253.0)	6,883 (271.0)
Overall length		mm (in.)	9,007 (354.6)	9,464 (372.6)	9,921 (390.6)	9,921 (390.6)
Overall width		mm (in.)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)
Overall height		mm (in.)	2,710 (106.7)	2,710 (106.7)	2,710 (106.7)	2,710 (106.7)
BBC		mm (in.)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)
Cab to axle		mm (in.)	3,800 (149.6)	4,257 (167.6)	4,714 (185.6)	5,171 (203.6)
Rear overhang		mm (in.)	2,464 (97.0)	2,464 (97.0)	2,464 (97.0)	2,007 (79.0)
Frame height at	Front axle	mm (in.)	940 (37.0)	940 (37.0)	940 (37.0)	940 (37.0)
	Rear axle	mm (in.)	990 (39.0)	990 (39.0)	990 (39.0)	990 (39.0)
Road clearance (at diff. case)		mm (in.)	285 (11.2)	285 (11.2)	285 (11.2)	285 (11.2)
Tread	Front	mm (in.)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)
	Rear	mm (in.)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)
Turning radius Tire		mm (in.)	8,790 (346.1)	9,460 (372.4)	10,120 (398.4)	10,790 (424.8)
Turning radius Swept		mm (in.)	9,310 (366.5)	9,980 (392.9)	10,640 (418.9)	11,310 (445.3)
<b>CHASSIS WEIGHTS</b> (on std. spec., without spare tire & std. tool set)						
<b>MANUAL T/M</b>						
Total weight	MT	kg (lb.)	4,770 (10,518)	4,785 (10,548)	4,800 (10,583)	4,830 (10,648)
Front axle	MT	kg (lb.)	3,005 (6,628)	3,025 (6,668)	3,070 (6,768)	3,075 (6,778)
Rear axle	MT	kg (lb.)	1,765 (3,890)	1,760 (3,880)	1,730 (3,815)	1,755 (3,870)
Unsprung weight	Front	kg (lb.)	645 (1,420)	645 (1,420)	645 (1,420)	645 (1,420)
	Rear	kg (lb.)	1,105 (2,435)	1,105 (2,435)	1,105 (2,435)	1,105 (2,435)
<b>AUTO T/M</b>						
Total weight	ATM	kg (lb.)	4,730 (10,430)	4,750 (10,470)	4,765 (10,505)	4,790 (10,560)
Front axle	ATM	kg (lb.)	2,965 (6,540)	2,990 (6,590)	3,035 (6,690)	3,035 (6,690)
Rear axle	ATM	kg (lb.)	1,765 (3,890)	1,760 (3,880)	1,730 (3,815)	1,755 (3,870)
Unsprung weight	Front	kg (lb.)	645 (1,420)	645 (1,420)	645 (1,420)	645 (1,420)
	Rear	kg (lb.)	1,105 (2,435)	1,105 (2,435)	1,105 (2,435)	1,105 (2,435)
Center of gravity height from the ground		mm (in.)	785 (30.9)	785 (30.9)	785 (30.9)	785 (30.9)

**NJ8J (Rr AIR SUS.)****J08E-VB****Fr. Axl : MFS10 Fr. Spg : 12,000 lbs****Rr. Axl : RS19 Rr. Spg : 19,000 lbs**

Model			NJ8JGSG	NJ8JJSJG	NJ8JLSJG	NJ8JMSJG	NJ8JNSJG
<b>CAPACITY</b>							
GVWR	Manual T/M	kg (lb.)	—	—	—	—	—
	Auto T/M	kg (lb.)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)
GAWR	Front	kg (lb.)	4,540 (10,000)	4,540 (10,000)	4,540 (10,000)	4,540 (10,000)	4,540 (10,000)
	Rear	kg (lb.)	8,620 (19,000)	8,620 (19,000)	8,620 (19,000)	8,620 (19,000)	8,620 (19,000)
<b>DIMENSIONS</b> (On standard specifications)							
Wheelbase		mm (in.)	3,861 (152.0)	4,445 (175.0)	4,750 (187.0)	5,207 (205.0)	5,385 (212.0)
Overall length		mm (in.)	6,162 (242.6)	7,076 (278.6)	7,686 (302.6)	8,143 (320.6)	7,686 (302.6)
Overall width		mm (in.)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)
Overall height		mm (in.)	2,710 (106.7)	2,710 (106.7)	2,710 (106.7)	2,710 (106.7)	2,710 (106.7)
BBC		mm (in.)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)
Cab to axle		mm (in.)	2,149 (84.6)	2,733 (107.6)	3,038 (119.6)	3,495 (137.6)	3,673 (144.6)
Rear overhang		mm (in.)	1,270 (50.0)	1,600 (63.0)	1,905 (75.0)	1,905 (75.0)	1,270 (50.0)
Frame height at	Front axle	mm (in.)	940 (37.0)	940 (37.0)	940 (37.0)	940 (37.0)	940 (37.0)
	Rear axle	mm (in.)	990 (39.0)	990 (39.0)	990 (39.0)	990 (39.0)	990 (39.0)
Road clearance (at diff. case)		mm (in.)	285 (11.2)	285 (11.2)	285 (11.2)	285 (11.2)	285 (11.2)
Tread	Front	mm (in.)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)
	Rear	mm (in.)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)
Turning radius Tire		mm (in.)	6,400 (252.0)	7,240 (285.0)	7,690 (302.8)	8,350 (328.7)	8,610 (339.0)
Turning radius Swept		mm (in.)	6,920 (272.4)	7,760 (305.5)	8,210 (323.2)	8,870 (349.2)	9,130 (359.4)
<b>CHASSIS WEIGHTS</b> (on std. spec., without spare tire & std. tool set)							
<b>MANUAL T/M</b>							
Total weight	MT	kg (lb.)	—	—	—	—	—
Front axle	MT	kg (lb.)	—	—	—	—	—
Rear axle	MT	kg (lb.)	—	—	—	—	—
Unsprung weight	Front	kg (lb.)	—	—	—	—	—
	Rear	kg (lb.)	—	—	—	—	—
<b>AUTO T/M</b>							
Total weight	ATM	kg (lb.)	4,655 (10,260)	4,620 (10,185)	4,655 (10,260)	4,705 (10,375)	4,690 (10,340)
Front axle	ATM	kg (lb.)	2,840 (6,260)	2,900 (6,395)	2,925 (6,445)	2,960 (6,530)	3,005 (6,625)
Rear axle	ATM	kg (lb.)	1,815 (4,000)	1,720 (3,790)	1,730 (3,815)	1,745 (3,845)	1,685 (3,715)
Unsprung weight	Front	kg (lb.)	645 (1,420)	645 (1,420)	645 (1,420)	645 (1,420)	645 (1,420)
	Rear	kg (lb.)	1,105 (2,435)	1,105 (2,435)	1,105 (2,435)	1,105 (2,435)	1,105 (2,435)
Center of gravity height from the ground		mm (in.)	785 (30.9)	785 (30.9)	785 (30.9)	785 (30.9)	785 (30.9)

Model			NJ8JPSG	NJ8JRSG	NJ8JTSG	NJ8JVSG
<b>CAPACITY</b>						
GVWR	Manual T/M	kg (lb.)	—	—	—	—
	Auto T/M	kg (lb.)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)
GAWR	Front	kg (lb.)	4,540 (10,000)	4,540 (10,000)	4,540 (10,000)	4,540 (10,000)
	Rear	kg (lb.)	8,620 (19,000)	8,620 (19,000)	8,620 (19,000)	8,620 (19,000)
<b>DIMENSIONS</b> (On standard specifications)						
Wheelbase		mm (in.)	5,512 (217.0)	5,969 (235.0)	6,426 (253.0)	6,883 (271.0)
Overall length		mm (in.)	9,007 (354.6)	9,464 (372.6)	9,921 (390.6)	9,921 (390.6)
Overall width		mm (in.)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)
Overall height		mm (in.)	2,710 (106.7)	2,710 (106.7)	2,710 (106.7)	2,710 (106.7)
BBC		mm (in.)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)
Cab to axle		mm (in.)	3,800 (149.6)	4,257 (167.6)	4,714 (185.6)	5,171 (203.6)
Rear overhang		mm (in.)	2,464 (97.0)	2,464 (97.0)	2,464 (97.0)	2,007 (79.0)
Frame height at	Front axle	mm (in.)	940 (37.0)	940 (37.0)	940 (37.0)	940 (37.0)
	Rear axle	mm (in.)	990 (39.0)	990 (39.0)	990 (39.0)	990 (39.0)
Road clearance (at diff. case)		mm (in.)	285 (11.2)	285 (11.2)	285 (11.2)	285 (11.2)
Tread	Front	mm (in.)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)
	Rear	mm (in.)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)
Turning radius Tire		mm (in.)	8,790 (346.1)	9,460 (372.4)	10,120 (398.4)	10,790 (424.8)
Turning radius Swept		mm (in.)	9,310 (366.5)	9,980 (392.9)	10,640 (418.9)	11,310 (445.3)
<b>CHASSIS WEIGHTS</b> (on std. spec., without spare tire & std. tool set)						
<b>MANUAL T/M</b>						
Total weight	MT	kg (lb.)	—	—	—	—
Front axle	MT	kg (lb.)	—	—	—	—
Rear axle	MT	kg (lb.)	—	—	—	—
Unsprung weight	Front	kg (lb.)	—	—	—	—
	Rear	kg (lb.)	—	—	—	—
<b>AUTO T/M</b>						
Total weight	ATM	kg (lb.)	4,760 (10,495)	4,780 (10,540)	4,795 (10,570)	4,830 (10,650)
Front axle	ATM	kg (lb.)	2,970 (6,550)	2,995 (6,605)	3,045 (6,710)	3,055 (6,735)
Rear axle	ATM	kg (lb.)	1,790 (3,945)	1,785 (3,935)	1,750 (3,860)	1,775 (3,915)
Unsprung weight	Front	kg (lb.)	645 (1,420)	645 (1,420)	645 (1,420)	645 (1,420)
	Rear	kg (lb.)	1,105 (2,435)	1,105 (2,435)	1,105 (2,435)	1,105 (2,435)
Center of gravity height from the ground		mm (in.)	785 (30.9)	785 (30.9)	785 (30.9)	785 (30.9)

**NJ8J (Rr AIR SUS.)****J08E-VC****Fr. Axl : MFS10 Fr. Spg : 8,000 lbs****Rr. Axl : RS19 Rr. Spg : 19,000 lbs**

Model			NJ8JGSG	NJ8JJSJG	NJ8JLSJG	NJ8JMSJG	NJ8JNSJG
<b>CAPACITY</b>							
GVWR	Manual T/M	kg (lb.)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)
	Auto T/M	kg (lb.)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)
GAWR	Front	kg (lb.)	3,630 (8,000)	3,630 (8,000)	3,630 (8,000)	3,630 (8,000)	3,630 (8,000)
	Rear	kg (lb.)	8,620 (19,000)	8,620 (19,000)	8,620 (19,000)	8,620 (19,000)	8,620 (19,000)
<b>DIMENSIONS</b> (On standard specifications)							
Wheelbase		mm (in.)	3,861 (152.0)	4,445 (175.0)	4,750 (187.0)	5,207 (205.0)	5,385 (212.0)
Overall length		mm (in.)	6,162 (242.6)	7,076 (278.6)	7,686 (302.6)	8,143 (320.6)	7,686 (302.6)
Overall width		mm (in.)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)
Overall height		mm (in.)	2,720 (107.1)	2,720 (107.1)	2,720 (107.1)	2,720 (107.1)	2,720 (107.1)
BBC		mm (in.)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)
Cab to axle		mm (in.)	2,149 (84.6)	2,733 (107.6)	3,038 (119.6)	3,495 (137.6)	3,673 (144.6)
Rear overhang		mm (in.)	1,270 (50.0)	1,600 (63.0)	1,905 (75.0)	1,905 (75.0)	1,270 (50.0)
Frame height at	Front axle	mm (in.)	955 (37.6)	955 (37.6)	955 (37.6)	955 (37.6)	955 (37.6)
	Rear axle	mm (in.)	990 (39.0)	990 (39.0)	990 (39.0)	990 (39.0)	990 (39.0)
Road clearance (at diff. case)		mm (in.)	285 (11.2)	285 (11.2)	285 (11.2)	285 (11.2)	285 (11.2)
Tread	Front	mm (in.)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)
	Rear	mm (in.)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)
Turning radius Tire		mm (in.)	6,400 (252.0)	7,240 (285.0)	7,690 (302.8)	8,350 (328.7)	8,610 (339.0)
Turning radius Swept		mm (in.)	6,920 (272.4)	7,760 (305.5)	8,210 (323.2)	8,870 (349.2)	9,130 (359.4)
<b>CHASSIS WEIGHTS</b> (on std. spec., without spare tire & std. tool set)							
<b>MANUAL T/M</b>							
Total weight	MT	kg (lb.)	4,645 (10,238)	4,610 (10,163)	4,640 (10,228)	4,685 (10,328)	4,665 (10,283)
Front axle	MT	kg (lb.)	2,845 (6,268)	2,900 (6,393)	2,925 (6,448)	2,960 (6,523)	3,000 (6,613)
Rear axle	MT	kg (lb.)	1,800 (3,970)	1,710 (3,770)	1,715 (3,780)	1,725 (3,805)	1,665 (3,670)
Unsprung weight	Front	kg (lb.)	615 (1,355)	615 (1,355)	615 (1,355)	615 (1,355)	615 (1,355)
	Rear	kg (lb.)	1,105 (2,435)	1,105 (2,435)	1,105 (2,435)	1,105 (2,435)	1,105 (2,435)
<b>AUTO T/M</b>							
Total weight	ATM	kg (lb.)	4,605 (10,150)	4,570 (10,075)	4,600 (10,140)	4,650 (10,250)	4,630 (10,205)
Front axle	ATM	kg (lb.)	2,805 (6,180)	2,865 (6,315)	2,885 (6,360)	2,930 (6,460)	2,965 (6,535)
Rear axle	ATM	kg (lb.)	1,800 (3,970)	1,705 (3,760)	1,715 (3,780)	1,720 (3,790)	1,665 (3,670)
Unsprung weight	Front	kg (lb.)	615 (1,355)	615 (1,355)	615 (1,355)	615 (1,355)	615 (1,355)
	Rear	kg (lb.)	1,105 (2,435)	1,105 (2,435)	1,105 (2,435)	1,105 (2,435)	1,105 (2,435)
Center of gravity height from the ground		mm (in.)	785 (30.9)	785 (30.9)	785 (30.9)	785 (30.9)	785 (30.9)

Model			NJ8JPSG	NJ8JRSG	NJ8JTSG	NJ8JVSG
<b>CAPACITY</b>						
GVWR	Manual T/M	kg (lb.)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)
	Auto T/M	kg (lb.)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)
GAWR	Front	kg (lb.)	3,630 (8,000)	3,630 (8,000)	3,630 (8,000)	3,630 (8,000)
	Rear	kg (lb.)	8,620 (19,000)	8,620 (19,000)	8,620 (19,000)	8,620 (19,000)
<b>DIMENSIONS</b> (On standard specifications)						
Wheelbase		mm (in.)	5,512 (217.0)	5,969 (235.0)	6,426 (253.0)	6,883 (271.0)
Overall length		mm (in.)	9,007 (354.6)	9,464 (372.6)	9,921 (390.6)	9,921 (390.6)
Overall width		mm (in.)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)
Overall height		mm (in.)	2,720 (107.1)	2,720 (107.1)	2,720 (107.1)	2,720 (107.1)
BBC		mm (in.)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)
Cab to axle		mm (in.)	3,800 (149.6)	4,257 (167.6)	4,714 (185.6)	5,171 (203.6)
Rear overhang		mm (in.)	2,464 (97.0)	2,464 (97.0)	2,464 (97.0)	2,007 (79.0)
Frame height at	Front axle	mm (in.)	955 (37.6)	955 (37.6)	955 (37.6)	955 (37.6)
	Rear axle	mm (in.)	990 (39.0)	990 (39.0)	990 (39.0)	990 (39.0)
Road clearance (at diff. case)		mm (in.)	285 (11.2)	285 (11.2)	285 (11.2)	285 (11.2)
Tread	Front	mm (in.)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)
	Rear	mm (in.)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)
Turning radius Tire		mm (in.)	8,790 (346.1)	9,460 (372.4)	10,120 (398.4)	10,790 (424.8)
Turning radius Swept		mm (in.)	9,310 (366.5)	9,980 (392.9)	10,640 (418.9)	11,310 (445.3)
<b>CHASSIS WEIGHTS</b> (on std. spec., without spare tire & std. tool set)						
<b>MANUAL T/M</b>						
Total weight	MT	kg (lb.)	4,735 (10,438)	4,755 (10,483)	4,770 (10,518)	4,800 (10,583)
Front axle	MT	kg (lb.)	2,970 (6,548)	2,995 (6,603)	3,040 (6,703)	3,045 (6,713)
Rear axle	MT	kg (lb.)	1,765 (3,890)	1,760 (3,880)	1,730 (3,815)	1,755 (3,870)
Unsprung weight	Front	kg (lb.)	615 (1,355)	615 (1,355)	615 (1,355)	615 (1,355)
	Rear	kg (lb.)	1,105 (2,435)	1,105 (2,435)	1,105 (2,435)	1,105 (2,435)
<b>AUTO T/M</b>						
Total weight	ATM	kg (lb.)	4,700 (10,360)	4,715 (10,395)	4,730 (10,430)	4,760 (10,495)
Front axle	ATM	kg (lb.)	2,935 (6,470)	2,955 (6,515)	3,000 (6,615)	3,005 (6,625)
Rear axle	ATM	kg (lb.)	1,765 (3,890)	1,760 (3,880)	1,730 (3,815)	1,755 (3,870)
Unsprung weight	Front	kg (lb.)	615 (1,355)	615 (1,355)	615 (1,355)	615 (1,355)
	Rear	kg (lb.)	1,105 (2,435)	1,105 (2,435)	1,105 (2,435)	1,105 (2,435)
Center of gravity height from the ground		mm (in.)	785 (30.9)	785 (30.9)	785 (30.9)	785 (30.9)

**NJ8J (Rr AIR SUS.)****J08E-VB****Fr. Axl : MFS10 Fr. Spg : 8,000 lbs****Rr. Axl : RS19 Rr. Spg : 19,000 lbs**

Model			NJ8JGSG	NJ8JJSJG	NJ8JLSG	NJ8JMSG	NJ8JNSG
<b>CAPACITY</b>							
GVWR	Manual T/M	kg (lb.)	—	—	—	—	—
	Auto T/M	kg (lb.)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)
GAWR	Front	kg (lb.)	3,630 (8,000)	3,630 (8,000)	3,630 (8,000)	3,630 (8,000)	3,630 (8,000)
	Rear	kg (lb.)	8,620 (19,000)	8,620 (19,000)	8,620 (19,000)	8,620 (19,000)	8,620 (19,000)
<b>DIMENSIONS</b> (On standard specifications)							
Wheelbase		mm (in.)	3,861 (152.0)	4,445 (175.0)	4,750 (187.0)	5,207 (205.0)	5,385 (212.0)
Overall length		mm (in.)	6,162 (242.6)	7,076 (278.6)	7,686 (302.6)	8,143 (320.6)	7,686 (302.6)
Overall width		mm (in.)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)
Overall height		mm (in.)	2,720 (107.1)	2,720 (107.1)	2,720 (107.1)	2,720 (107.1)	2,720 (107.1)
BBC		mm (in.)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)
Cab to axle		mm (in.)	2,149 (84.6)	2,733 (107.6)	3,038 (119.6)	3,495 (137.6)	3,673 (144.6)
Rear overhang		mm (in.)	1,270 (50.0)	1,600 (63.0)	1,905 (75.0)	1,905 (75.0)	1,270 (50.0)
Frame height at	Front axle	mm (in.)	955 (37.6)	955 (37.6)	955 (37.6)	955 (37.6)	955 (37.6)
	Rear axle	mm (in.)	990 (39.0)	990 (39.0)	990 (39.0)	990 (39.0)	990 (39.0)
Road clearance (at diff. case)		mm (in.)	285 (11.2)	285 (11.2)	285 (11.2)	285 (11.2)	285 (11.2)
Tread	Front	mm (in.)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)
	Rear	mm (in.)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)
Turning radius Tire		mm (in.)	6,400 (252.0)	7,240 (285.0)	7,690 (302.8)	8,350 (328.7)	8,610 (339.0)
Turning radius Swept		mm (in.)	6,920 (272.4)	7,760 (305.5)	8,210 (323.2)	8,870 (349.2)	9,130 (359.4)
<b>CHASSIS WEIGHTS</b> (on std. spec., without spare tire & std. tool set)							
<b>MANUAL T/M</b>							
Total weight	MT	kg (lb.)	—	—	—	—	—
Front axle	MT	kg (lb.)	—	—	—	—	—
Rear axle	MT	kg (lb.)	—	—	—	—	—
Unsprung weight	Front	kg (lb.)	—	—	—	—	—
	Rear	kg (lb.)	—	—	—	—	—
<b>AUTO T/M</b>							
Total weight	ATM	kg (lb.)	4,625 (10,195)	4,590 (10,120)	4,620 (10,185)	4,675 (10,305)	4,655 (10,260)
Front axle	ATM	kg (lb.)	2,810 (6,195)	2,870 (6,330)	2,890 (6,370)	2,930 (6,460)	2,970 (6,545)
Rear axle	ATM	kg (lb.)	1,815 (4,000)	1,720 (3,790)	1,730 (3,815)	1,745 (3,845)	1,685 (3,715)
Unsprung weight	Front	kg (lb.)	615 (1,355)	615 (1,355)	615 (1,355)	615 (1,355)	615 (1,355)
	Rear	kg (lb.)	1,105 (2,435)	1,105 (2,435)	1,105 (2,435)	1,105 (2,435)	1,105 (2,435)
Center of gravity height from the ground		mm (in.)	785 (30.9)	785 (30.9)	785 (30.9)	785 (30.9)	785 (30.9)

Model			NJ8JPSG	NJ8JRSG	NJ8JTSG	NJ8JVSG
<b>CAPACITY</b>						
GVWR	Manual T/M	kg (lb.)	—	—	—	—
	Auto T/M	kg (lb.)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)
GAWR	Front	kg (lb.)	3,630 (8,000)	3,630 (8,000)	3,630 (8,000)	3,630 (8,000)
	Rear	kg (lb.)	8,620 (19,000)	8,620 (19,000)	8,620 (19,000)	8,620 (19,000)
<b>DIMENSIONS</b> (On standard specifications)						
Wheelbase		mm (in.)	5,512 (217.0)	5,969 (235.0)	6,426 (253.0)	6,883 (271.0)
Overall length		mm (in.)	9,007 (354.6)	9,464 (372.6)	9,921 (390.6)	9,921 (390.6)
Overall width		mm (in.)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)
Overall height		mm (in.)	2,720 (107.1)	2,720 (107.1)	2,720 (107.1)	2,720 (107.1)
BBC		mm (in.)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)
Cab to axle		mm (in.)	3,800 (149.6)	4,257 (167.6)	4,714 (185.6)	5,171 (203.6)
Rear overhang		mm (in.)	2,464 (97.0)	2,464 (97.0)	2,464 (97.0)	2,007 (79.0)
Frame height at	Front axle	mm (in.)	955 (37.6)	955 (37.6)	955 (37.6)	955 (37.6)
	Rear axle	mm (in.)	990 (39.0)	990 (39.0)	990 (39.0)	990 (39.0)
Road clearance (at diff. case)		mm (in.)	285 (11.2)	285 (11.2)	285 (11.2)	285 (11.2)
Tread	Front	mm (in.)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)
	Rear	mm (in.)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)
Turning radius Tire		mm (in.)	8,790 (346.1)	9,460 (372.4)	10,120 (398.4)	10,790 (424.8)
Turning radius Swept		mm (in.)	9,310 (366.5)	9,980 (392.9)	10,640 (418.9)	11,310 (445.3)
<b>CHASSIS WEIGHTS</b> (on std. spec., without spare tire & std. tool set)						
<b>MANUAL T/M</b>						
Total weight	MT	kg (lb.)	—	—	—	—
Front axle	MT	kg (lb.)	—	—	—	—
Rear axle	MT	kg (lb.)	—	—	—	—
Unsprung weight	Front	kg (lb.)	—	—	—	—
	Rear	kg (lb.)	—	—	—	—
<b>AUTO T/M</b>						
Total weight	ATM	kg (lb.)	4,725 (10,415)	4,745 (10,460)	4,765 (10,505)	4,800 (10,580)
Front axle	ATM	kg (lb.)	2,935 (6,470)	2,960 (6,525)	3,015 (6,645)	3,025 (6,665)
Rear axle	ATM	kg (lb.)	1,790 (3,945)	1,785 (3,935)	1,750 (3,860)	1,775 (3,915)
Unsprung weight	Front	kg (lb.)	615 (1,355)	615 (1,355)	615 (1,355)	615 (1,355)
	Rear	kg (lb.)	1,105 (2,435)	1,105 (2,435)	1,105 (2,435)	1,105 (2,435)
Center of gravity height from the ground		mm (in.)	785 (30.9)	785 (30.9)	785 (30.9)	785 (30.9)



**NJ8J (Rr AIR SUS.)****LOW PROFILE / J08E-VC****Fr. Axl : MFS10 Fr. Spg : 8,000 lbs****Rr. Axl : RS17 Rr. Spg : 19,000 lbs**

Model			NJ8JGSG	NJ8JJSG	NJ8JLSG	NJ8JMSG	NJ8JNSG
<b>CAPACITY</b>							
GVWR	Manual T/M	kg (lb.)	11,570 (25,500)	11,570 (25,500)	11,570 (25,500)	11,570 (25,500)	11,570 (25,500)
	Auto T/M	kg (lb.)	11,570 (25,500)	11,570 (25,500)	11,570 (25,500)	11,570 (25,500)	11,570 (25,500)
GAWR	Front	kg (lb.)	3,630 (8,000)	3,630 (8,000)	3,630 (8,000)	3,630 (8,000)	3,630 (8,000)
	Rear	kg (lb.)	7,940 (17,500)	7,940 (17,500)	7,940 (17,500)	7,940 (17,500)	7,940 (17,500)
<b>DIMENSIONS</b> (On standard specifications)							
Wheelbase		mm (in.)	3,861 (152.0)	4,445 (175.0)	4,750 (187.0)	5,207 (205.0)	5,385 (212.0)
Overall length		mm (in.)	6,162 (242.6)	7,076 (278.6)	7,686 (302.6)	8,143 (320.6)	7,686 (302.6)
Overall width		mm (in.)	2,430 (95.7)	2,430 (95.7)	2,430 (95.7)	2,430 (95.7)	2,430 (95.7)
Overall height		mm (in.)	2,610 (102.8)	2,610 (102.8)	2,610 (102.8)	2,610 (102.8)	2,610 (102.8)
BBC		mm (in.)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)
Cab to axle		mm (in.)	2,149 (84.6)	2,733 (107.6)	3,038 (119.6)	3,495 (137.6)	3,673 (144.6)
Rear overhang		mm (in.)	1,270 (50.0)	1,600 (63.0)	1,905 (75.0)	1,905 (75.0)	1,270 (50.0)
Frame height at	Front axle	mm (in.)	845 (33.3)	845 (33.3)	845 (33.3)	845 (33.3)	845 (33.3)
	Rear axle	mm (in.)	885 (34.8)	885 (34.8)	885 (34.8)	885 (34.8)	885 (34.8)
Road clearance (at diff. case)		mm (in.)	180 (7.1)	180 (7.1)	180 (7.1)	180 (7.1)	180 (7.1)
Tread	Front	mm (in.)	2,030 (79.9)	2,030 (79.9)	2,030 (79.9)	2,030 (79.9)	2,030 (79.9)
	Rear	mm (in.)	1,840 (72.4)	1,840 (72.4)	1,840 (72.4)	1,840 (72.4)	1,840 (72.4)
Turning radius Tire		mm (in.)	6,410 (252.4)	7,250 (285.4)	7,690 (302.8)	8,360 (329.1)	8,620 (339.4)
Turning radius Swept		mm (in.)	6,925 (272.6)	7,765 (305.7)	8,205 (323.0)	8,875 (349.4)	9,135 (359.6)
<b>CHASSIS WEIGHTS</b> (on std. spec., without spare tire & std. tool set)							
<b>MANUAL T/M</b>							
Total weight	MT	kg (lb.)	4,495 (9,908)	4,460 (9,833)	4,490 (9,898)	4,535 (9,998)	4,515 (9,953)
Front axle	MT	kg (lb.)	2,800 (6,173)	2,860 (6,308)	2,880 (6,348)	2,920 (6,438)	2,955 (6,513)
Rear axle	MT	kg (lb.)	1,695 (3,735)	1,600 (3,525)	1,610 (3,550)	1,615 (3,560)	1,560 (3,440)
Unsprung weight	Front	kg (lb.)	570 (1,255)	570 (1,255)	570 (1,255)	570 (1,255)	570 (1,255)
	Rear	kg (lb.)	1,000 (2,205)	1,000 (2,205)	1,000 (2,205)	1,000 (2,205)	1,000 (2,205)
<b>AUTO T/M</b>							
Total weight	ATM	kg (lb.)	4,455 (9,820)	4,420 (9,745)	4,450 (9,810)	4,500 (9,920)	4,480 (9,875)
Front axle	ATM	kg (lb.)	2,760 (6,085)	2,820 (6,220)	2,845 (6,270)	2,885 (6,360)	2,925 (6,445)
Rear axle	ATM	kg (lb.)	1,695 (3,735)	1,600 (3,525)	1,605 (3,540)	1,615 (3,560)	1,555 (3,430)
Unsprung weight	Front	kg (lb.)	570 (1,255)	570 (1,255)	570 (1,255)	570 (1,255)	570 (1,255)
	Rear	kg (lb.)	1,000 (2,205)	1,000 (2,205)	1,000 (2,205)	1,000 (2,205)	1,000 (2,205)
Center of gravity height from the ground		mm (in.)	685 (27.0)	685 (27.0)	685 (27.0)	685 (27.0)	685 (27.0)



Model			NJ8JPSG	NJ8JRSG	NJ8JTSG	NJ8JVSG
<b>CAPACITY</b>						
GVWR	Manual T/M	kg (lb.)	11,570 (25,500)	11,570 (25,500)	11,570 (25,500)	11,570 (25,500)
	Auto T/M	kg (lb.)	11,570 (25,500)	11,570 (25,500)	11,570 (25,500)	11,570 (25,500)
GAWR	Front	kg (lb.)	3,630 (8,000)	3,630 (8,000)	3,630 (8,000)	3,630 (8,000)
	Rear	kg (lb.)	7,940 (17,500)	7,940 (17,500)	7,940 (17,500)	7,940 (17,500)
<b>DIMENSIONS</b> (On standard specifications)						
Wheelbase		mm (in.)	5,512 (217.0)	5,969 (235.0)	6,426 (253.0)	6,883 (271.0)
Overall length		mm (in.)	9,007 (354.6)	9,464 (372.6)	9,921 (390.6)	9,921 (390.6)
Overall width		mm (in.)	2,430 (95.7)	2,430 (95.7)	2,430 (95.7)	2,430 (95.7)
Overall height		mm (in.)	2,610 (102.8)	2,610 (102.8)	2,610 (102.8)	2,610 (102.8)
BBC		mm (in.)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)
Cab to axle		mm (in.)	3,800 (149.6)	4,257 (167.6)	4,714 (185.6)	5,171 (203.6)
Rear overhang		mm (in.)	2,464 (97.0)	2,464 (97.0)	2,464 (97.0)	2,007 (79.0)
Frame height at	Front axle	mm (in.)	845 (33.3)	845 (33.3)	845 (33.3)	845 (33.3)
	Rear axle	mm (in.)	885 (34.8)	885 (34.8)	885 (34.8)	885 (34.8)
Road clearance (at diff. case)		mm (in.)	180 (7.1)	180 (7.1)	180 (7.1)	180 (7.1)
Tread	Front	mm (in.)	2,030 (79.9)	2,030 (79.9)	2,030 (79.9)	2,030 (79.9)
	Rear	mm (in.)	1,840 (72.4)	1,840 (72.4)	1,840 (72.4)	1,840 (72.4)
Turning radius Tire		mm (in.)	8,800 (346.5)	9,470 (372.8)	10,130 (398.8)	10,800 (425.2)
Turning radius Swept		mm (in.)	9,315 (366.7)	9,985 (393.1)	10,645 (419.1)	11,315 (445.5)
<b>CHASSIS WEIGHTS</b> (on std. spec., without spare tire & std. tool set)						
<b>MANUAL T/M</b>						
Total weight	MT	kg (lb.)	4,585 (10,108)	4,605 (10,153)	4,620 (10,183)	4,650 (10,253)
Front axle	MT	kg (lb.)	2,925 (6,448)	2,955 (6,513)	3,000 (6,613)	3,005 (6,628)
Rear axle	MT	kg (lb.)	1,660 (3,660)	1,650 (3,640)	1,620 (3,570)	1,645 (3,625)
Unsprung weight	Front	kg (lb.)	570 (1,255)	570 (1,255)	570 (1,255)	570 (1,255)
	Rear	kg (lb.)	1,000 (2,205)	1,000 (2,205)	1,000 (2,205)	1,000 (2,205)
<b>AUTO T/M</b>						
Total weight	ATM	kg (lb.)	4,550 (10,030)	4,565 (10,065)	4,580 (10,095)	4,610 (10,165)
Front axle	ATM	kg (lb.)	2,895 (6,380)	2,915 (6,425)	2,960 (6,525)	2,965 (6,540)
Rear axle	ATM	kg (lb.)	1,655 (3,650)	1,650 (3,640)	1,620 (3,570)	1,645 (3,625)
Unsprung weight	Front	kg (lb.)	570 (1,255)	570 (1,255)	570 (1,255)	570 (1,255)
	Rear	kg (lb.)	1,000 (2,205)	1,000 (2,205)	1,000 (2,205)	1,000 (2,205)
Center of gravity height from the ground		mm (in.)	685 (27.0)	685 (27.0)	685 (27.0)	685 (27.0)

**NJ8J (Rr AIR SUS.)****LOW PROFILE / J08E-VB****Fr. Axl : MFS10 Fr. Spg : 8,000 lbs****Rr. Axl : RS17 Rr. Spg : 19,000 lbs**

Model			NJ8JGSG	NJ8JJSJG	NJ8JLSJG	NJ8JMSJG	NJ8JNSJG
<b>CAPACITY</b>							
GVWR	Manual T/M	kg (lb.)	—	—	—	—	—
	Auto T/M	kg (lb.)	11,570 (25,500)	11,570 (25,500)	11,570 (25,500)	11,570 (25,500)	11,570 (25,500)
GAWR	Front	kg (lb.)	3,630 (8,000)	3,630 (8,000)	3,630 (8,000)	3,630 (8,000)	3,630 (8,000)
	Rear	kg (lb.)	7,940 (17,500)	7,940 (17,500)	7,940 (17,500)	7,940 (17,500)	7,940 (17,500)
<b>DIMENSIONS</b> (On standard specifications)							
Wheelbase		mm (in.)	3,861 (152.0)	4,445 (175.0)	4,750 (187.0)	5,207 (205.0)	5,385 (212.0)
Overall length		mm (in.)	6,162 (242.6)	7,076 (278.6)	7,686 (302.6)	8,143 (320.6)	7,686 (302.6)
Overall width		mm (in.)	2,430 (95.7)	2,430 (95.7)	2,430 (95.7)	2,430 (95.7)	2,430 (95.7)
Overall height		mm (in.)	2,610 (102.8)	2,610 (102.8)	2,610 (102.8)	2,610 (102.8)	2,610 (102.8)
BBC		mm (in.)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)
Cab to axle		mm (in.)	2,149 (84.6)	2,733 (107.6)	3,038 (119.6)	3,495 (137.6)	3,673 (144.6)
Rear overhang		mm (in.)	1,270 (50.0)	1,600 (63.0)	1,905 (75.0)	1,905 (75.0)	1,270 (50.0)
Frame height at	Front axle	mm (in.)	845 (33.3)	845 (33.3)	845 (33.3)	845 (33.3)	845 (33.3)
	Rear axle	mm (in.)	885 (34.8)	885 (34.8)	885 (34.8)	885 (34.8)	885 (34.8)
Road clearance (at diff. case)		mm (in.)	180 (7.1)	180 (7.1)	180 (7.1)	180 (7.1)	180 (7.1)
Tread	Front	mm (in.)	2,030 (79.9)	2,030 (79.9)	2,030 (79.9)	2,030 (79.9)	2,030 (79.9)
	Rear	mm (in.)	1,840 (72.4)	1,840 (72.4)	1,840 (72.4)	1,840 (72.4)	1,840 (72.4)
Turning radius Tire		mm (in.)	6,410 (252.4)	7,250 (285.4)	7,690 (302.8)	8,360 (329.1)	8,620 (339.4)
Turning radius Swept		mm (in.)	6,925 (272.6)	7,765 (305.7)	8,205 (323.0)	8,875 (349.4)	9,135 (359.6)
<b>CHASSIS WEIGHTS</b> (on std. spec., without spare tire & std. tool set)							
<b>MANUAL T/M</b>							
Total weight	MT	kg (lb.)	—	—	—	—	—
Front axle	MT	kg (lb.)	—	—	—	—	—
Rear axle	MT	kg (lb.)	—	—	—	—	—
Unsprung weight	Front	kg (lb.)	—	—	—	—	—
	Rear	kg (lb.)	—	—	—	—	—
<b>AUTO T/M</b>							
Total weight	ATM	kg (lb.)	4,475 (9,865)	4,440 (9,790)	4,470 (9,855)	4,525 (9,975)	4,505 (9,930)
Front axle	ATM	kg (lb.)	2,770 (6,105)	2,825 (6,230)	2,845 (6,275)	2,890 (6,370)	2,925 (6,445)
Rear axle	ATM	kg (lb.)	1,705 (3,760)	1,615 (3,560)	1,625 (3,580)	1,635 (3,605)	1,580 (3,485)
Unsprung weight	Front	kg (lb.)	570 (1,255)	570 (1,255)	570 (1,255)	570 (1,255)	570 (1,255)
	Rear	kg (lb.)	1,000 (2,205)	1,000 (2,205)	1,000 (2,205)	1,000 (2,205)	1,000 (2,205)
Center of gravity height from the ground		mm (in.)	685 (27.0)	685 (27.0)	685 (27.0)	685 (27.0)	685 (27.0)

Model			NJ8JPSG	NJ8JRSG	NJ8JTSG	NJ8JVSG
<b>CAPACITY</b>						
GVWR	Manual T/M	kg (lb.)	—	—	—	—
	Auto T/M	kg (lb.)	11,570 (25,500)	11,570 (25,500)	11,570 (25,500)	11,570 (25,500)
GAWR	Front	kg (lb.)	3,630 (8,000)	3,630 (8,000)	3,630 (8,000)	3,630 (8,000)
	Rear	kg (lb.)	7,940 (17,500)	7,940 (17,500)	7,940 (17,500)	7,940 (17,500)
<b>DIMENSIONS</b> (On standard specifications)						
Wheelbase		mm (in.)	5,512 (217.0)	5,969 (235.0)	6,426 (253.0)	6,883 (271.0)
Overall length		mm (in.)	9,007 (354.6)	9,464 (372.6)	9,921 (390.6)	9,921 (390.6)
Overall width		mm (in.)	2,430 (95.7)	2,430 (95.7)	2,430 (95.7)	2,430 (95.7)
Overall height		mm (in.)	2,610 (102.8)	2,610 (102.8)	2,610 (102.8)	2,610 (102.8)
BBC		mm (in.)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)
Cab to axle		mm (in.)	3,800 (149.6)	4,257 (167.6)	4,714 (185.6)	5,171 (203.6)
Rear overhang		mm (in.)	2,464 (97.0)	2,464 (97.0)	2,464 (97.0)	2,007 (79.0)
Frame height at	Front axle	mm (in.)	845 (33.3)	845 (33.3)	845 (33.3)	845 (33.3)
	Rear axle	mm (in.)	885 (34.8)	885 (34.8)	885 (34.8)	885 (34.8)
Road clearance (at diff. case)		mm (in.)	180 (7.1)	180 (7.1)	180 (7.1)	180 (7.1)
Tread	Front	mm (in.)	2,030 (79.9)	2,030 (79.9)	2,030 (79.9)	2,030 (79.9)
	Rear	mm (in.)	1,840 (72.4)	1,840 (72.4)	1,840 (72.4)	1,840 (72.4)
Turning radius Tire		mm (in.)	8,800 (346.5)	9,470 (372.8)	10,130 (398.8)	10,800 (425.2)
Turning radius Swept		mm (in.)	9,315 (366.7)	9,985 (393.1)	10,645 (419.1)	11,315 (445.5)
<b>CHASSIS WEIGHTS</b> (on std. spec., without spare tire & std. tool set)						
<b>MANUAL T/M</b>						
Total weight	MT	kg (lb.)	—	—	—	—
Front axle	MT	kg (lb.)	—	—	—	—
Rear axle	MT	kg (lb.)	—	—	—	—
Unsprung weight	Front	kg (lb.)	—	—	—	—
	Rear	kg (lb.)	—	—	—	—
<b>AUTO T/M</b>						
Total weight	ATM	kg (lb.)	4,575 (10,085)	4,595 (10,130)	4,615 (10,175)	4,650 (10,250)
Front axle	ATM	kg (lb.)	2,895 (6,380)	2,920 (6,435)	2,975 (6,560)	2,980 (6,570)
Rear axle	ATM	kg (lb.)	1,680 (3,705)	1,675 (3,695)	1,640 (3,615)	1,670 (3,680)
Unsprung weight	Front	kg (lb.)	570 (1,255)	570 (1,255)	570 (1,255)	570 (1,255)
	Rear	kg (lb.)	1,000 (2,205)	1,000 (2,205)	1,000 (2,205)	1,000 (2,205)
Center of gravity height from the ground		mm (in.)	685 (27.0)	685 (27.0)	685 (27.0)	685 (27.0)

## NF8J

Fr. Axl : MFS12 Fr. Spg : 12,000 lbs

Rr. Axl : RS21 Rr. Spg : 21,000 lbs

Model			NF8JJSA	NF8JLSA	NF8JMSA	NF8JPSA
<b>CAPACITY</b>						
GVWR	Manual T/M	kg (lb.)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)
	Auto T/M	kg (lb.)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)
GAWR	Front	kg (lb.)	5,440 (12,000)	5,440 (12,000)	5,440 (12,000)	5,440 (12,000)
	Rear	kg (lb.)	9,530 (21,000)	9,530 (21,000)	9,530 (21,000)	9,530 (21,000)
<b>DIMENSIONS</b> (On standard specifications)						
Wheelbase		mm (in.)	4,445 (175.0)	4,750 (187.0)	5,207 (205.0)	5,512 (217.0)
Overall length		mm (in.)	7,076 (278.6)	7,686 (302.6)	8,143 (320.6)	9,007 (354.6)
Overall width		mm (in.)	2,485 (97.8)	2,485 (97.8)	2,485 (97.8)	2,485 (97.8)
Overall height		mm (in.)	2,720 (107.1)	2,720 (107.1)	2,720 (107.1)	2,720 (107.1)
BBC		mm (in.)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)
Cab to axle		mm (in.)	2,733 (107.6)	3,038 (119.6)	3,495 (137.6)	3,800 (149.6)
Rear overhang		mm (in.)	1,600 (63.0)	1,905 (75.0)	1,905 (75.0)	2,464 (97.0)
Frame height at	Front axle	mm (in.)	940 (37.0)	940 (37.0)	940 (37.0)	940 (37.0)
	Rear axle	mm (in.)	1,030 (40.6)	1,030 (40.6)	1,030 (40.6)	1,030 (40.6)
Road clearance (at diff. case)		mm (in.)	285 (11.2)	285 (11.2)	285 (11.2)	285 (11.2)
Tread	Front	mm (in.)	2,005 (78.9)	2,005 (78.9)	2,005 (78.9)	2,005 (78.9)
	Rear	mm (in.)	1,870 (73.6)	1,870 (73.6)	1,870 (73.6)	1,870 (73.6)
Turning radius Tire		mm (in.)	7,240 (285.0)	7,680 (302.4)	8,340 (328.3)	8,790 (346.1)
Turning radius Swept		mm (in.)	7,770 (305.9)	8,210 (323.2)	8,870 (349.2)	9,320 (366.9)
<b>CHASSIS WEIGHTS</b> (on std. spec., without spare tire & std. tool set)						
<b>MANUAL T/M</b>						
Total weight	MT	kg (lb.)	4,610 (10,165)	4,650 (10,250)	4,725 (10,415)	4,765 (10,505)
Front axle	MT	kg (lb.)	2,930 (6,460)	2,955 (6,515)	3,005 (6,625)	3,000 (6,615)
Rear axle	MT	kg (lb.)	1,680 (3,705)	1,695 (3,735)	1,720 (3,790)	1,765 (3,890)
Unsprung weight	Front	kg (lb.)	610 (1,345)	610 (1,345)	610 (1,345)	610 (1,345)
	Rear	kg (lb.)	1,035 (2,280)	1,035 (2,280)	1,035 (2,280)	1,035 (2,280)
<b>AUTO T/M</b>						
Total weight	ATM	kg (lb.)	4,570 (10,075)	4,605 (10,150)	4,685 (10,330)	4,725 (10,415)
Front axle	ATM	kg (lb.)	2,895 (6,380)	2,915 (6,425)	2,970 (6,550)	2,965 (6,535)
Rear axle	ATM	kg (lb.)	1,675 (3,695)	1,690 (3,725)	1,715 (3,780)	1,760 (3,880)
Unsprung weight	Front	kg (lb.)	610 (1,345)	610 (1,345)	610 (1,345)	610 (1,345)
	Rear	kg (lb.)	1,035 (2,280)	1,035 (2,280)	1,035 (2,280)	1,035 (2,280)
Center of gravity height from the ground		mm (in.)	800 (31.5)	800 (31.5)	800 (31.5)	800 (31.5)

Model			NF8JRSA	NF8JTSA	NF8JVSA
<b>CAPACITY</b>					
GVWR	Manual T/M	kg (lb.)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)
	Auto T/M	kg (lb.)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)
GAWR	Front	kg (lb.)	5,440 (12,000)	5,440 (12,000)	5,440 (12,000)
	Rear	kg (lb.)	9,530 (21,000)	9,530 (21,000)	9,530 (21,000)
<b>DIMENSIONS</b> (On standard specifications)					
Wheelbase		mm (in.)	5,969 (235.0)	6,426 (253.0)	6,883 (271.0)
Overall length		mm (in.)	9,464 (372.6)	9,921 (390.6)	9,921 (390.6)
Overall width		mm (in.)	2,485 (97.8)	2,485 (97.8)	2,485 (97.8)
Overall height		mm (in.)	2,720 (107.1)	2,720 (107.1)	2,720 (107.1)
BBC		mm (in.)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)
Cab to axle		mm (in.)	4,257 (167.6)	4,714 (185.6)	5,171 (203.6)
Rear overhang		mm (in.)	2,464 (97.0)	2,464 (97.0)	2,007 (79.0)
Frame height at	Front axle	mm (in.)	940 (37.0)	940 (37.0)	940 (37.0)
	Rear axle	mm (in.)	1,030 (40.6)	1,030 (40.6)	1,030 (40.6)
Road clearance (at diff. case)		mm (in.)	285 (11.2)	285 (11.2)	285 (11.2)
Tread	Front	mm (in.)	2,005 (78.9)	2,005 (78.9)	2,005 (78.9)
	Rear	mm (in.)	1,870 (73.6)	1,870 (73.6)	1,870 (73.6)
Turning radius Tire		mm (in.)	9,450 (372.0)	10,120 (398.4)	10,780 (424.4)
Turning radius Swept		mm (in.)	9,980 (392.9)	10,650 (419.3)	11,310 (445.3)
<b>CHASSIS WEIGHTS</b> (on std. spec., without spare tire & std. tool set)					
<b>MANUAL T/M</b>					
Total weight	MT	kg (lb.)	4,790 (10,560)	4,810 (10,605)	4,845 (10,680)
Front axle	MT	kg (lb.)	3,025 (6,670)	3,080 (6,790)	3,085 (6,800)
Rear axle	MT	kg (lb.)	1,765 (3,890)	1,730 (3,815)	1,760 (3,880)
Unsprung weight	Front	kg (lb.)	610 (1,345)	610 (1,345)	610 (1,345)
	Rear	kg (lb.)	1,035 (2,280)	1,035 (2,280)	1,035 (2,280)
<b>AUTO T/M</b>					
Total weight	ATM	kg (lb.)	4,750 (10,470)	4,770 (10,515)	4,805 (10,595)
Front axle	ATM	kg (lb.)	2,990 (6,590)	3,045 (6,710)	3,050 (6,725)
Rear axle	ATM	kg (lb.)	1,760 (3,880)	1,725 (3,805)	1,755 (3,870)
Unsprung weight	Front	kg (lb.)	610 (1,345)	610 (1,345)	610 (1,345)
	Rear	kg (lb.)	1,035 (2,280)	1,035 (2,280)	1,035 (2,280)
Center of gravity height from the ground		mm (in.)	800 (31.5)	800 (31.5)	800 (31.5)

## NF8J (Rr AIR SUS.)

Fr. Axl : MFS12 Fr. Spg : 12,000 lbs

Rr. Axl : RS21 Rr. Spg : 21,000 lbs

Model			NF8JJSG	NF8JLSG	NF8JMSG	NF8JPSG
<b>CAPACITY</b>						
GVWR	Manual T/M	kg (lb.)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)
	Auto T/M	kg (lb.)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)
GAWR	Front	kg (lb.)	5,440 (12,000)	5,440 (12,000)	5,440 (12,000)	5,440 (12,000)
	Rear	kg (lb.)	9,530 (21,000)	9,530 (21,000)	9,530 (21,000)	9,530 (21,000)
<b>DIMENSIONS</b> (On standard specifications)						
Wheelbase		mm (in.)	4,445 (175.0)	4,750 (187.0)	5,207 (205.0)	5,512 (217.0)
Overall length		mm (in.)	7,076 (278.6)	7,686 (302.6)	8,143 (320.6)	9,007 (354.6)
Overall width		mm (in.)	2,485 (97.8)	2,485 (97.8)	2,485 (97.8)	2,485 (97.8)
Overall height		mm (in.)	2,705 (106.5)	2,705 (106.5)	2,705 (106.5)	2,705 (106.5)
BBC		mm (in.)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)
Cab to axle		mm (in.)	2,733 (107.6)	3,038 (119.6)	3,495 (137.6)	3,800 (149.6)
Rear overhang		mm (in.)	1,600 (63.0)	1,905 (75.0)	1,905 (75.0)	2,464 (97.0)
Frame height at	Front axle	mm (in.)	940 (37.0)	940 (37.0)	940 (37.0)	940 (37.0)
	Rear axle	mm (in.)	995 (39.2)	995 (39.2)	995 (39.2)	995 (39.2)
Road clearance (at diff. case)		mm (in.)	285 (11.2)	285 (11.2)	285 (11.2)	285 (11.2)
Tread	Front	mm (in.)	2,005 (78.9)	2,005 (78.9)	2,005 (78.9)	2,005 (78.9)
	Rear	mm (in.)	1,870 (73.6)	1,870 (73.6)	1,870 (73.6)	1,870 (73.6)
Turning radius Tire		mm (in.)	7,240 (285.0)	7,680 (302.4)	8,340 (328.3)	8,790 (346.1)
Turning radius Swept		mm (in.)	7,770 (305.9)	8,210 (323.2)	8,870 (349.2)	9,320 (366.9)
<b>CHASSIS WEIGHTS</b> (on std. spec., without spare tire & std. tool set)						
<b>MANUAL T/M</b>						
Total weight	MT	kg (lb.)	4,590 (10,120)	4,625 (10,195)	4,705 (10,375)	4,745 (10,460)
Front axle	MT	kg (lb.)	2,930 (6,460)	2,950 (6,500)	3,000 (6,615)	3,000 (6,615)
Rear axle	MT	kg (lb.)	1,660 (3,660)	1,675 (3,695)	1,705 (3,760)	1,745 (3,845)
Unsprung weight	Front	kg (lb.)	610 (1,345)	610 (1,345)	610 (1,345)	610 (1,345)
	Rear	kg (lb.)	1,025 (2,260)	1,025 (2,260)	1,025 (2,260)	1,025 (2,260)
<b>AUTO T/M</b>						
Total weight	ATM	kg (lb.)	4,550 (10,030)	4,585 (10,110)	4,660 (10,275)	4,700 (10,360)
Front axle	ATM	kg (lb.)	2,890 (6,370)	2,910 (6,415)	2,960 (6,525)	2,960 (6,525)
Rear axle	ATM	kg (lb.)	1,660 (3,660)	1,675 (3,695)	1,700 (3,750)	1,740 (3,835)
Unsprung weight	Front	kg (lb.)	610 (1,345)	610 (1,345)	610 (1,345)	610 (1,345)
	Rear	kg (lb.)	1,025 (2,260)	1,025 (2,260)	1,025 (2,260)	1,025 (2,260)
Center of gravity height from the ground		mm (in.)	780 (30.7)	780 (30.7)	780 (30.7)	780 (30.7)

Model			NF8JRSG	NF8JTSG	NF8JVSG
<b>CAPACITY</b>					
GVWR	Manual T/M	kg (lb.)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)
	Auto T/M	kg (lb.)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)
GAWR	Front	kg (lb.)	5,440 (12,000)	5,440 (12,000)	5,440 (12,000)
	Rear	kg (lb.)	9,530 (21,000)	9,530 (21,000)	9,530 (21,000)
<b>DIMENSIONS</b> (On standard specifications)					
Wheelbase		mm (in.)	5,969 (235.0)	6,426 (253.0)	6,883 (271.0)
Overall length		mm (in.)	9,464 (372.6)	9,921 (390.6)	9,921 (390.6)
Overall width		mm (in.)	2,485 (97.8)	2,485 (97.8)	2,485 (97.8)
Overall height		mm (in.)	2,705 (106.5)	2,705 (106.5)	2,705 (106.5)
BBC		mm (in.)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)
Cab to axle		mm (in.)	4,257 (167.6)	4,714 (185.6)	5,171 (203.6)
Rear overhang		mm (in.)	2,464 (97.0)	2,464 (97.0)	2,007 (79.0)
Frame height at	Front axle	mm (in.)	940 (37.0)	940 (37.0)	940 (37.0)
	Rear axle	mm (in.)	995 (39.2)	995 (39.2)	995 (39.2)
Road clearance (at diff. case)		mm (in.)	285 (11.2)	285 (11.2)	285 (11.2)
Tread	Front	mm (in.)	2,005 (78.9)	2,005 (78.9)	2,005 (78.9)
	Rear	mm (in.)	1,870 (73.6)	1,870 (73.6)	1,870 (73.6)
Turning radius Tire		mm (in.)	9,450 (372.0)	10,120 (398.4)	10,780 (424.4)
Turning radius Swept		mm (in.)	9,980 (392.9)	10,650 (419.3)	11,310 (445.3)
<b>CHASSIS WEIGHTS</b> (on std. spec., without spare tire & std. tool set)					
<b>MANUAL T/M</b>					
Total weight	MT	kg (lb.)	4,770 (10,515)	4,790 (10,560)	4,825 (10,635)
Front axle	MT	kg (lb.)	3,025 (6,670)	3,080 (6,790)	3,085 (6,800)
Rear axle	MT	kg (lb.)	1,745 (3,845)	1,710 (3,770)	1,740 (3,835)
Unsprung weight	Front	kg (lb.)	610 (1,345)	610 (1,345)	610 (1,345)
	Rear	kg (lb.)	1,025 (2,260)	1,025 (2,260)	1,025 (2,260)
<b>AUTO T/M</b>					
Total weight	ATM	kg (lb.)	4,725 (10,415)	4,750 (10,470)	4,780 (10,540)
Front axle	ATM	kg (lb.)	2,985 (6,580)	3,040 (6,700)	3,040 (6,705)
Rear axle	ATM	kg (lb.)	1,740 (3,835)	1,710 (3,770)	1,740 (3,835)
Unsprung weight	Front	kg (lb.)	610 (1,345)	610 (1,345)	610 (1,345)
	Rear	kg (lb.)	1,025 (2,260)	1,025 (2,260)	1,025 (2,260)
Center of gravity height from the ground		mm (in.)	780 (30.7)	780 (30.7)	780 (30.7)



## NV8J

Fr. Axl : MFS12 Fr. Spg : 12,000 lbs

Rr. Axl : RS21 Rr. Spg : 21,000 lbs

Model			NV8JGSA	NV8JJSA	NV8JLSA	NV8JMSA
<b>CAPACITY</b>						
GVWR	Manual T/M	kg (lb.)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)
	Auto T/M	kg (lb.)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)
GAWR	Front	kg (lb.)	5,440 (12,000)	5,440 (12,000)	5,440 (12,000)	5,440 (12,000)
	Rear	kg (lb.)	9,530 (21,000)	9,530 (21,000)	9,530 (21,000)	9,530 (21,000)
<b>DIMENSIONS</b> (On standard specifications)						
Wheelbase		mm (in.)	3,861 (152.0)	4,445 (175.0)	4,750 (187.0)	5,207 (205.0)
Overall length		mm (in.)	6,162 (242.6)	7,076 (278.6)	7,686 (302.6)	8,143 (320.6)
Overall width		mm (in.)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)
Overall height		mm (in.)	2,720 (107.1)	2,720 (107.1)	2,720 (107.1)	2,720 (107.1)
BBC		mm (in.)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)
Cab to axle		mm (in.)	2,149 (84.6)	2,733 (107.6)	3,038 (119.6)	3,495 (137.6)
Rear overhang		mm (in.)	1,270 (50.0)	1,600 (63.0)	1,905 (75.0)	1,905 (75.0)
Frame height at	Front axle	mm (in.)	940 (37.0)	940 (37.0)	940 (37.0)	940 (37.0)
	Rear axle	mm (in.)	1,030 (40.6)	1,030 (40.6)	1,030 (40.6)	1,030 (40.6)
Road clearance (at diff. case)		mm (in.)	285 (11.2)	285 (11.2)	285 (11.2)	285 (11.2)
Tread	Front	mm (in.)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)
	Rear	mm (in.)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)
Turning radius Tire		mm (in.)	6,400 (252.0)	7,240 (285.0)	7,690 (302.8)	8,350 (328.7)
Turning radius Swept		mm (in.)	6,920 (272.4)	7,760 (305.5)	8,210 (323.2)	8,870 (349.2)
<b>CHASSIS WEIGHTS</b> (on std. spec., without spare tire & std. tool set)						
<b>MANUAL T/M</b>						
Total weight	MT	kg (lb.)	4,930 (10,867)	4,975 (10,967)	5,015 (11,057)	5,090 (11,222)
Front axle	MT	kg (lb.)	2,954 (6,513)	3,066 (6,761)	3,098 (6,831)	3,158 (6,963)
Rear axle	MT	kg (lb.)	1,976 (4,354)	1,909 (4,206)	1,917 (4,226)	1,932 (4,259)
Unsprung weight	Front	kg (lb.)	645 (1,420)	645 (1,420)	645 (1,420)	645 (1,420)
	Rear	kg (lb.)	1,135 (2,500)	1,135 (2,500)	1,135 (2,500)	1,135 (2,500)
<b>AUTO T/M</b>						
Total weight	ATM	kg (lb.)	4,879 (10,754)	4,929 (10,864)	4,964 (10,944)	5,039 (11,109)
Front axle	ATM	kg (lb.)	2,907 (6,405)	3,024 (6,667)	3,054 (6,733)	3,112 (6,860)
Rear axle	ATM	kg (lb.)	1,972 (4,349)	1,905 (4,197)	1,910 (4,211)	1,927 (4,249)
Unsprung weight	Front	kg (lb.)	645 (1,420)	645 (1,420)	645 (1,420)	645 (1,420)
	Rear	kg (lb.)	1,135 (2,500)	1,135 (2,500)	1,135 (2,500)	1,135 (2,500)
Center of gravity height from the ground		mm (in.)	795 (31.3)	795 (31.3)	795 (31.3)	795 (31.3)



Model			NV8JPSA	NV8JRSA	NV8JTSA	NV8JVSA
<b>CAPACITY</b>						
GVWR	Manual T/M	kg (lb.)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)
	Auto T/M	kg (lb.)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)
GAWR	Front	kg (lb.)	5,440 (12,000)	5,440 (12,000)	5,440 (12,000)	5,440 (12,000)
	Rear	kg (lb.)	9,530 (21,000)	9,530 (21,000)	9,530 (21,000)	9,530 (21,000)
<b>DIMENSIONS</b> (On standard specifications)						
Wheelbase		mm (in.)	5,512 (217.0)	5,969 (235.0)	6,426 (253.0)	6,883 (271.0)
Overall length		mm (in.)	9,007 (354.6)	9,464 (372.6)	9,921 (390.6)	9,921 (390.6)
Overall width		mm (in.)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)
Overall height		mm (in.)	2,720 (107.1)	2,720 (107.1)	2,720 (107.1)	2,720 (107.1)
BBC		mm (in.)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)
Cab to axle		mm (in.)	3,800 (149.6)	4,257 (167.6)	4,714 (185.6)	5,171 (203.6)
Rear overhang		mm (in.)	2,464 (97.0)	2,464 (97.0)	2,464 (97.0)	2,007 (79.0)
Frame height at	Front axle	mm (in.)	940 (37.0)	940 (37.0)	940 (37.0)	940 (37.0)
	Rear axle	mm (in.)	1,030 (40.6)	1,030 (40.6)	1,030 (40.6)	1,030 (40.6)
Road clearance (at diff. case)		mm (in.)	285 (11.2)	285 (11.2)	285 (11.2)	285 (11.2)
Tread	Front	mm (in.)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)
	Rear	mm (in.)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)
Turning radius Tire		mm (in.)	8,790 (346.1)	9,460 (372.4)	10,120 (398.4)	10,790 (424.8)
Turning radius Swept		mm (in.)	9,310 (366.5)	9,980 (392.9)	10,640 (418.9)	11,310 (445.3)
<b>CHASSIS WEIGHTS</b> (on std. spec., without spare tire & std. tool set)						
<b>MANUAL T/M</b>						
Total weight	MT	kg (lb.)	5,130 (11,312)	5,155 (11,367)	5,180 (11,422)	5,210 (11,487)
Front axle	MT	kg (lb.)	3,163 (6,974)	3,195 (7,045)	3,261 (7,193)	3,266 (7,199)
Rear axle	MT	kg (lb.)	1,967 (4,338)	1,960 (4,322)	1,919 (4,229)	1,944 (4,288)
Unsprung weight	Front	kg (lb.)	645 (1,420)	645 (1,420)	645 (1,420)	645 (1,420)
	Rear	kg (lb.)	1,135 (2,500)	1,135 (2,500)	1,135 (2,500)	1,135 (2,500)
<b>AUTO T/M</b>						
Total weight	ATM	kg (lb.)	5,079 (11,199)	5,109 (11,264)	5,129 (11,309)	5,159 (11,374)
Front axle	ATM	kg (lb.)	3,116 (6,869)	3,156 (6,960)	3,215 (7,089)	3,219 (7,098)
Rear axle	ATM	kg (lb.)	1,963 (4,330)	1,953 (4,304)	1,914 (4,220)	1,940 (4,276)
Unsprung weight	Front	kg (lb.)	645 (1,420)	645 (1,420)	645 (1,420)	645 (1,420)
	Rear	kg (lb.)	1,135 (2,500)	1,135 (2,500)	1,135 (2,500)	1,135 (2,500)
Center of gravity height from the ground		mm (in.)	795 (31.3)	795 (31.3)	795 (31.3)	795 (31.3)

## NV8J

Fr. Axl : MFS10 Fr. Spg : 12,000 lbs

Rr. Axl : RS21 Rr. Spg : 19,000 lbs

Model			NV8JGSA	NV8JJSA	NV8JLSA	NV8JMSA
<b>CAPACITY</b>						
GVWR	Manual T/M	kg (lb.)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)
	Auto T/M	kg (lb.)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)
GAWR	Front	kg (lb.)	4,540 (10,000)	4,540 (10,000)	4,540 (10,000)	4,540 (10,000)
	Rear	kg (lb.)	8,620 (19,000)	8,620 (19,000)	8,620 (19,000)	8,620 (19,000)
<b>DIMENSIONS</b> (On standard specifications)						
Wheelbase		mm (in.)	3,861 (152.0)	4,445 (175.0)	4,750 (187.0)	5,207 (205.0)
Overall length		mm (in.)	6,162 (242.6)	7,076 (278.6)	7,686 (302.6)	8,143 (320.6)
Overall width		mm (in.)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)
Overall height		mm (in.)	2,715 (106.9)	2,715 (106.9)	2,715 (106.9)	2,715 (106.9)
BBC		mm (in.)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)
Cab to axle		mm (in.)	2,149 (84.6)	2,733 (107.6)	3,038 (119.6)	3,495 (137.6)
Rear overhang		mm (in.)	1,270 (50.0)	1,600 (63.0)	1,905 (75.0)	1,905 (75.0)
Frame height at	Front axle	mm (in.)	940 (37.0)	940 (37.0)	940 (37.0)	940 (37.0)
	Rear axle	mm (in.)	1,010 (39.8)	1,010 (39.8)	1,010 (39.8)	1,010 (39.8)
Road clearance (at diff. case)		mm (in.)	285 (11.2)	285 (11.2)	285 (11.2)	285 (11.2)
Tread	Front	mm (in.)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)
	Rear	mm (in.)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)
Turning radius Tire		mm (in.)	6,400 (252.0)	7,240 (285.0)	7,690 (302.8)	8,350 (328.7)
Turning radius Swept		mm (in.)	6,920 (272.4)	7,760 (305.5)	8,210 (323.2)	8,870 (349.2)
<b>CHASSIS WEIGHTS</b> (on std. spec., without spare tire & std. tool set)						
<b>MANUAL T/M</b>						
Total weight	MT	kg (lb.)	4,920 (10,847)	4,895 (10,792)	4,930 (10,867)	4,980 (10,977)
Front axle	MT	kg (lb.)	2,954 (6,513)	3,031 (6,681)	3,063 (6,751)	3,113 (6,863)
Rear axle	MT	kg (lb.)	1,966 (4,334)	1,864 (4,111)	1,867 (4,116)	1,867 (4,114)
Unsprung weight	Front	kg (lb.)	645 (1,420)	645 (1,420)	645 (1,420)	645 (1,420)
	Rear	kg (lb.)	1,125 (2,480)	1,125 (2,480)	1,125 (2,480)	1,125 (2,480)
<b>AUTO T/M</b>						
Total weight	ATM	kg (lb.)	4,869 (10,734)	4,849 (10,689)	4,879 (10,754)	4,929 (10,864)
Front axle	ATM	kg (lb.)	2,912 (6,420)	2,994 (6,602)	3,019 (6,653)	3,067 (6,760)
Rear axle	ATM	kg (lb.)	1,957 (4,314)	1,855 (4,087)	1,860 (4,101)	1,862 (4,104)
Unsprung weight	Front	kg (lb.)	645 (1,420)	645 (1,420)	645 (1,420)	645 (1,420)
	Rear	kg (lb.)	1,125 (2,480)	1,125 (2,480)	1,125 (2,480)	1,125 (2,480)
Center of gravity height from the ground		mm (in.)	785 (30.9)	785 (30.9)	785 (30.9)	785 (30.9)

Model			NV8JPSA	NV8JRSA	NV8JTSA	NV8JVSA
<b>CAPACITY</b>						
GVWR	Manual T/M	kg (lb.)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)
	Auto T/M	kg (lb.)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)
GAWR	Front	kg (lb.)	4,540 (10,000)	4,540 (10,000)	4,540 (10,000)	4,540 (10,000)
	Rear	kg (lb.)	8,620 (19,000)	8,620 (19,000)	8,620 (19,000)	8,620 (19,000)
<b>DIMENSIONS</b> (On standard specifications)						
Wheelbase		mm (in.)	5,512 (217.0)	5,969 (235.0)	6,426 (253.0)	6,883 (271.0)
Overall length		mm (in.)	9,007 (354.6)	9,464 (372.6)	9,921 (390.6)	9,921 (390.6)
Overall width		mm (in.)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)
Overall height		mm (in.)	2,715 (106.9)	2,715 (106.9)	2,715 (106.9)	2,715 (106.9)
BBC		mm (in.)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)
Cab to axle		mm (in.)	3,800 (149.6)	4,257 (167.6)	4,714 (185.6)	5,171 (203.6)
Rear overhang		mm (in.)	2,464 (97.0)	2,464 (97.0)	2,464 (97.0)	2,007 (79.0)
Frame height at	Front axle	mm (in.)	940 (37.0)	940 (37.0)	940 (37.0)	940 (37.0)
	Rear axle	mm (in.)	1,010 (39.8)	1,010 (39.8)	1,010 (39.8)	1,010 (39.8)
Road clearance (at diff. case)		mm (in.)	285 (11.2)	285 (11.2)	285 (11.2)	285 (11.2)
Tread	Front	mm (in.)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)
	Rear	mm (in.)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)
Turning radius Tire		mm (in.)	8,790 (346.1)	9,460 (372.4)	10,120 (398.4)	10,790 (424.8)
Turning radius Swept		mm (in.)	9,310 (366.5)	9,980 (392.9)	10,640 (418.9)	11,310 (445.3)
<b>CHASSIS WEIGHTS</b> (on std. spec., without spare tire & std. tool set)						
<b>MANUAL T/M</b>						
Total weight	MT	kg (lb.)	5,035 (11,102)	5,055 (11,142)	5,070 (11,177)	5,105 (11,252)
Front axle	MT	kg (lb.)	3,128 (6,899)	3,160 (6,965)	3,216 (7,088)	3,226 (7,109)
Rear axle	MT	kg (lb.)	1,907 (4,203)	1,895 (4,177)	1,854 (4,089)	1,879 (4,143)
Unsprung weight	Front	kg (lb.)	645 (1,420)	645 (1,420)	645 (1,420)	645 (1,420)
	Rear	kg (lb.)	1,125 (2,480)	1,125 (2,480)	1,125 (2,480)	1,125 (2,480)
<b>AUTO T/M</b>						
Total weight	ATM	kg (lb.)	4,984 (10,989)	5,004 (11,034)	5,019 (11,064)	5,054 (11,144)
Front axle	ATM	kg (lb.)	3,081 (6,794)	3,116 (6,870)	3,170 (6,989)	3,179 (7,013)
Rear axle	ATM	kg (lb.)	1,903 (4,195)	1,888 (4,164)	1,849 (4,075)	1,875 (4,131)
Unsprung weight	Front	kg (lb.)	645 (1,420)	645 (1,420)	645 (1,420)	645 (1,420)
	Rear	kg (lb.)	1,125 (2,480)	1,125 (2,480)	1,125 (2,480)	1,125 (2,480)
Center of gravity height from the ground		mm (in.)	785 (30.9)	785 (30.9)	785 (30.9)	785 (30.9)

## NV8J

Fr. Axl : MFS10 Fr. Spg : 12,000 lbs

Rr. Axl : RS21 Rr. Spg : 21,000 lbs

Model			NV8JGSA	NV8JJSA	NV8JLSA	NV8JMSA
<b>CAPACITY</b>						
GVWR	Manual T/M	kg (lb.)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)
	Auto T/M	kg (lb.)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)
GAWR	Front	kg (lb.)	4,540 (10,000)	4,540 (10,000)	4,540 (10,000)	4,540 (10,000)
	Rear	kg (lb.)	9,530 (21,000)	9,530 (21,000)	9,530 (21,000)	9,530 (21,000)
<b>DIMENSIONS</b> (On standard specifications)						
Wheelbase		mm (in.)	3,861 (152.0)	4,445 (175.0)	4,750 (187.0)	5,207 (205.0)
Overall length		mm (in.)	6,162 (242.6)	7,076 (278.6)	7,686 (302.6)	8,143 (320.6)
Overall width		mm (in.)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)
Overall height		mm (in.)	2,720 (107.1)	2,720 (107.1)	2,720 (107.1)	2,720 (107.1)
BBC		mm (in.)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)
Cab to axle		mm (in.)	2,149 (84.6)	2,733 (107.6)	3,038 (119.6)	3,495 (137.6)
Rear overhang		mm (in.)	1,270 (50.0)	1,600 (63.0)	1,905 (75.0)	1,905 (75.0)
Frame height at	Front axle	mm (in.)	940 (37.0)	940 (37.0)	940 (37.0)	940 (37.0)
	Rear axle	mm (in.)	1,030 (40.6)	1,030 (40.6)	1,030 (40.6)	1,030 (40.6)
Road clearance (at diff. case)		mm (in.)	285 (11.2)	285 (11.2)	285 (11.2)	285 (11.2)
Tread	Front	mm (in.)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)
	Rear	mm (in.)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)
Turning radius Tire		mm (in.)	6,400 (252.0)	7,240 (285.0)	7,690 (302.8)	8,350 (328.7)
Turning radius Swept		mm (in.)	6,920 (272.4)	7,760 (305.5)	8,210 (323.2)	8,870 (349.2)
<b>CHASSIS WEIGHTS</b> (on std. spec., without spare tire & std. tool set)						
<b>MANUAL T/M</b>						
Total weight	MT	kg (lb.)	4,930 (10,867)	4,975 (10,967)	5,015 (11,057)	5,090 (11,222)
Front axle	MT	kg (lb.)	2,954 (6,513)	3,066 (6,761)	3,098 (6,831)	3,158 (6,963)
Rear axle	MT	kg (lb.)	1,976 (4,354)	1,909 (4,206)	1,917 (4,226)	1,932 (4,259)
Unsprung weight	Front	kg (lb.)	645 (1,420)	645 (1,420)	645 (1,420)	645 (1,420)
	Rear	kg (lb.)	1,135 (2,500)	1,135 (2,500)	1,135 (2,500)	1,135 (2,500)
<b>AUTO T/M</b>						
Total weight	ATM	kg (lb.)	4,879 (10,754)	4,929 (10,864)	4,964 (10,944)	5,039 (11,109)
Front axle	ATM	kg (lb.)	2,907 (6,405)	3,024 (6,667)	3,054 (6,733)	3,112 (6,860)
Rear axle	ATM	kg (lb.)	1,972 (4,349)	1,905 (4,197)	1,910 (4,211)	1,927 (4,249)
Unsprung weight	Front	kg (lb.)	645 (1,420)	645 (1,420)	645 (1,420)	645 (1,420)
	Rear	kg (lb.)	1,135 (2,500)	1,135 (2,500)	1,135 (2,500)	1,135 (2,500)
Center of gravity height from the ground		mm (in.)	795 (31.3)	795 (31.3)	795 (31.3)	795 (31.3)

Model			NV8JPSA	NV8JRSA	NV8JTSA	NV8JVSA
<b>CAPACITY</b>						
GVWR	Manual T/M	kg (lb.)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)
	Auto T/M	kg (lb.)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)
GAWR	Front	kg (lb.)	4,540 (10,000)	4,540 (10,000)	4,540 (10,000)	4,540 (10,000)
	Rear	kg (lb.)	9,530 (21,000)	9,530 (21,000)	9,530 (21,000)	9,530 (21,000)
<b>DIMENSIONS</b> (On standard specifications)						
Wheelbase		mm (in.)	5,512 (217.0)	5,969 (235.0)	6,426 (253.0)	6,883 (271.0)
Overall length		mm (in.)	9,007 (354.6)	9,464 (372.6)	9,921 (390.6)	9,921 (390.6)
Overall width		mm (in.)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)
Overall height		mm (in.)	2,720 (107.1)	2,720 (107.1)	2,720 (107.1)	2,720 (107.1)
BBC		mm (in.)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)
Cab to axle		mm (in.)	3,800 (149.6)	4,257 (167.6)	4,714 (185.6)	5,171 (203.6)
Rear overhang		mm (in.)	2,464 (97.0)	2,464 (97.0)	2,464 (97.0)	2,007 (79.0)
Frame height at	Front axle	mm (in.)	940 (37.0)	940 (37.0)	940 (37.0)	940 (37.0)
	Rear axle	mm (in.)	1,030 (40.6)	1,030 (40.6)	1,030 (40.6)	1,030 (40.6)
Road clearance (at diff. case)		mm (in.)	285 (11.2)	285 (11.2)	285 (11.2)	285 (11.2)
Tread	Front	mm (in.)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)
	Rear	mm (in.)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)
Turning radius Tire		mm (in.)	8,790 (346.1)	9,460 (372.4)	10,120 (398.4)	10,790 (424.8)
Turning radius Swept		mm (in.)	9,310 (366.5)	9,980 (392.9)	10,640 (418.9)	11,310 (445.3)
<b>CHASSIS WEIGHTS</b> (on std. spec., without spare tire & std. tool set)						
<b>MANUAL T/M</b>						
Total weight	MT	kg (lb.)	5,130 (11,312)	5,155 (11,367)	5,180 (11,422)	5,210 (11,487)
Front axle	MT	kg (lb.)	3,163 (6,974)	3,195 (7,045)	3,261 (7,193)	3,266 (7,199)
Rear axle	MT	kg (lb.)	1,967 (4,338)	1,960 (4,322)	1,919 (4,229)	1,944 (4,288)
Unsprung weight	Front	kg (lb.)	645 (1,420)	645 (1,420)	645 (1,420)	645 (1,420)
	Rear	kg (lb.)	1,135 (2,500)	1,135 (2,500)	1,135 (2,500)	1,135 (2,500)
<b>AUTO T/M</b>						
Total weight	ATM	kg (lb.)	5,079 (11,199)	5,109 (11,264)	5,129 (11,309)	5,159 (11,374)
Front axle	ATM	kg (lb.)	3,116 (6,869)	3,156 (6,960)	3,215 (7,089)	3,219 (7,098)
Rear axle	ATM	kg (lb.)	1,963 (4,330)	1,953 (4,304)	1,914 (4,220)	1,940 (4,276)
Unsprung weight	Front	kg (lb.)	645 (1,420)	645 (1,420)	645 (1,420)	645 (1,420)
	Rear	kg (lb.)	1,135 (2,500)	1,135 (2,500)	1,135 (2,500)	1,135 (2,500)
Center of gravity height from the ground		mm (in.)	795 (31.3)	795 (31.3)	795 (31.3)	795 (31.3)

## NV8J

Fr. Axl : MFS12 Fr. Spg : 12,000 lbs

Rr. Axl : RS21 Rr. Spg : 19,000 lbs

Model			NV8JGSA	NV8JJSA	NV8JLSA	NV8JMSA
<b>CAPACITY</b>						
GVWR	Manual T/M	kg (lb.)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)
	Auto T/M	kg (lb.)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)
GAWR	Front	kg (lb.)	5,440 (12,000)	5,440 (12,000)	5,440 (12,000)	5,440 (12,000)
	Rear	kg (lb.)	8,620 (19,000)	8,620 (19,000)	8,620 (19,000)	8,620 (19,000)
<b>DIMENSIONS</b> (On standard specifications)						
Wheelbase		mm (in.)	3,861 (152.0)	4,445 (175.0)	4,750 (187.0)	5,207 (205.0)
Overall length		mm (in.)	6,162 (242.6)	7,076 (278.6)	7,686 (302.6)	8,143 (320.6)
Overall width		mm (in.)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)
Overall height		mm (in.)	2,715 (106.9)	2,715 (106.9)	2,715 (106.9)	2,715 (106.9)
BBC		mm (in.)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)
Cab to axle		mm (in.)	2,149 (84.6)	2,733 (107.6)	3,038 (119.6)	3,495 (137.6)
Rear overhang		mm (in.)	1,270 (50.0)	1,600 (63.0)	1,905 (75.0)	1,905 (75.0)
Frame height at	Front axle	mm (in.)	940 (37.0)	940 (37.0)	940 (37.0)	940 (37.0)
	Rear axle	mm (in.)	1,010 (39.8)	1,010 (39.8)	1,010 (39.8)	1,010 (39.8)
Road clearance (at diff. case)		mm (in.)	285 (11.2)	285 (11.2)	285 (11.2)	285 (11.2)
Tread	Front	mm (in.)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)
	Rear	mm (in.)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)
Turning radius Tire		mm (in.)	6,400 (252.0)	7,240 (285.0)	7,690 (302.8)	8,350 (328.7)
Turning radius Swept		mm (in.)	6,920 (272.4)	7,760 (305.5)	8,210 (323.2)	8,870 (349.2)
<b>CHASSIS WEIGHTS</b> (on std. spec., without spare tire & std. tool set)						
<b>MANUAL T/M</b>						
Total weight	MT	kg (lb.)	4,920 (10,847)	4,895 (10,792)	4,930 (10,867)	4,980 (10,977)
Front axle	MT	kg (lb.)	2,954 (6,513)	3,031 (6,681)	3,063 (6,751)	3,113 (6,863)
Rear axle	MT	kg (lb.)	1,966 (4,334)	1,864 (4,111)	1,867 (4,116)	1,867 (4,114)
Unsprung weight	Front	kg (lb.)	645 (1,420)	645 (1,420)	645 (1,420)	645 (1,420)
	Rear	kg (lb.)	1,125 (2,480)	1,125 (2,480)	1,125 (2,480)	1,125 (2,480)
<b>AUTO T/M</b>						
Total weight	ATM	kg (lb.)	4,869 (10,734)	4,849 (10,689)	4,879 (10,754)	4,929 (10,864)
Front axle	ATM	kg (lb.)	2,912 (6,420)	2,994 (6,602)	3,019 (6,653)	3,067 (6,760)
Rear axle	ATM	kg (lb.)	1,957 (4,314)	1,855 (4,087)	1,860 (4,101)	1,862 (4,104)
Unsprung weight	Front	kg (lb.)	645 (1,420)	645 (1,420)	645 (1,420)	645 (1,420)
	Rear	kg (lb.)	1,125 (2,480)	1,125 (2,480)	1,125 (2,480)	1,125 (2,480)
Center of gravity height from the ground		mm (in.)	785 (30.9)	785 (30.9)	785 (30.9)	785 (30.9)

Model			NV8JPSA	NV8JRSA	NV8JTSA	NV8JVSA
<b>CAPACITY</b>						
GVWR	Manual T/M	kg (lb.)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)
	Auto T/M	kg (lb.)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)
GAWR	Front	kg (lb.)	5,440 (12,000)	5,440 (12,000)	5,440 (12,000)	5,440 (12,000)
	Rear	kg (lb.)	8,620 (19,000)	8,620 (19,000)	8,620 (19,000)	8,620 (19,000)
<b>DIMENSIONS</b> (On standard specifications)						
Wheelbase		mm (in.)	5,512 (217.0)	5,969 (235.0)	6,426 (253.0)	6,883 (271.0)
Overall length		mm (in.)	9,007 (354.6)	9,464 (372.6)	9,921 (390.6)	9,921 (390.6)
Overall width		mm (in.)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)
Overall height		mm (in.)	2,715 (106.9)	2,715 (106.9)	2,715 (106.9)	2,715 (106.9)
BBC		mm (in.)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)
Cab to axle		mm (in.)	3,800 (149.6)	4,257 (167.6)	4,714 (185.6)	5,171 (203.6)
Rear overhang		mm (in.)	2,464 (97.0)	2,464 (97.0)	2,464 (97.0)	2,007 (79.0)
Frame height at	Front axle	mm (in.)	940 (37.0)	940 (37.0)	940 (37.0)	940 (37.0)
	Rear axle	mm (in.)	1,010 (39.8)	1,010 (39.8)	1,010 (39.8)	1,010 (39.8)
Road clearance (at diff. case)		mm (in.)	285 (11.2)	285 (11.2)	285 (11.2)	285 (11.2)
Tread	Front	mm (in.)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)
	Rear	mm (in.)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)
Turning radius Tire		mm (in.)	8,790 (346.1)	9,460 (372.4)	10,120 (398.4)	10,790 (424.8)
Turning radius Swept		mm (in.)	9,310 (366.5)	9,980 (392.9)	10,640 (418.9)	11,310 (445.3)
<b>CHASSIS WEIGHTS</b> (on std. spec., without spare tire & std. tool set)						
<b>MANUAL T/M</b>						
Total weight	MT	kg (lb.)	5,035 (11,102)	5,055 (11,142)	5,070 (11,177)	5,105 (11,252)
Front axle	MT	kg (lb.)	3,128 (6,899)	3,160 (6,965)	3,216 (7,088)	3,226 (7,109)
Rear axle	MT	kg (lb.)	1,907 (4,203)	1,895 (4,177)	1,854 (4,089)	1,879 (4,143)
Unsprung weight	Front	kg (lb.)	645 (1,420)	645 (1,420)	645 (1,420)	645 (1,420)
	Rear	kg (lb.)	1,125 (2,480)	1,125 (2,480)	1,125 (2,480)	1,125 (2,480)
<b>AUTO T/M</b>						
Total weight	ATM	kg (lb.)	4,984 (10,989)	5,004 (11,034)	5,019 (11,064)	5,054 (11,144)
Front axle	ATM	kg (lb.)	3,081 (6,794)	3,116 (6,870)	3,170 (6,989)	3,179 (7,013)
Rear axle	ATM	kg (lb.)	1,903 (4,195)	1,888 (4,164)	1,849 (4,075)	1,875 (4,131)
Unsprung weight	Front	kg (lb.)	645 (1,420)	645 (1,420)	645 (1,420)	645 (1,420)
	Rear	kg (lb.)	1,125 (2,480)	1,125 (2,480)	1,125 (2,480)	1,125 (2,480)
Center of gravity height from the ground		mm (in.)	785 (30.9)	785 (30.9)	785 (30.9)	785 (30.9)



## NV8J

Fr. Axl : MFS14 Fr. Spg : 14,000 lbs

Rr. Axl : RS21 Rr. Spg : 19,000 lbs

Model			NV8JGSA	NV8JJSA	NV8JLSA	NV8JMSA
<b>CAPACITY</b>						
GVWR	Manual T/M	kg (lb.)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)
	Auto T/M	kg (lb.)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)
GAWR	Front	kg (lb.)	5,980 (13,200)	5,980 (13,200)	5,980 (13,200)	5,980 (13,200)
	Rear	kg (lb.)	8,620 (19,000)	8,620 (19,000)	8,620 (19,000)	8,620 (19,000)
<b>DIMENSIONS</b> (On standard specifications)						
Wheelbase		mm (in.)	3,861 (152.0)	4,445 (175.0)	4,750 (187.0)	5,207 (205.0)
Overall length		mm (in.)	6,162 (242.6)	7,076 (278.6)	7,686 (302.6)	8,143 (320.6)
Overall width		mm (in.)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)
Overall height		mm (in.)	2,720 (107.1)	2,720 (107.1)	2,720 (107.1)	2,720 (107.1)
BBC		mm (in.)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)
Cab to axle		mm (in.)	2,149 (84.6)	2,733 (107.6)	3,038 (119.6)	3,495 (137.6)
Rear overhang		mm (in.)	1,270 (50.0)	1,600 (63.0)	1,905 (75.0)	1,905 (75.0)
Frame height at	Front axle	mm (in.)	950 (37.4)	950 (37.4)	950 (37.4)	950 (37.4)
	Rear axle	mm (in.)	1,010 (39.8)	1,010 (39.8)	1,010 (39.8)	1,010 (39.8)
Road clearance (at diff. case)		mm (in.)	285 (11.2)	285 (11.2)	285 (11.2)	285 (11.2)
Tread	Front	mm (in.)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)
	Rear	mm (in.)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)
Turning radius Tire		mm (in.)	6,470 (254.7)	7,330 (288.6)	7,770 (305.9)	8,440 (332.3)
Turning radius Swept		mm (in.)	6,990 (275.2)	7,850 (309.1)	8,290 (326.4)	8,970 (353.1)
<b>CHASSIS WEIGHTS</b> (on std. spec., without spare tire & std. tool set)						
<b>MANUAL T/M</b>						
Total weight	MT	kg (lb.)	4,965 (10,947)	4,940 (10,892)	4,970 (10,957)	5,025 (11,077)
Front axle	MT	kg (lb.)	2,999 (6,613)	3,076 (6,781)	3,103 (6,841)	3,158 (6,963)
Rear axle	MT	kg (lb.)	1,966 (4,334)	1,864 (4,111)	1,867 (4,116)	1,867 (4,114)
Unsprung weight	Front	kg (lb.)	690 (1,520)	690 (1,520)	690 (1,520)	690 (1,520)
	Rear	kg (lb.)	1,125 (2,480)	1,125 (2,480)	1,125 (2,480)	1,125 (2,480)
<b>AUTO T/M</b>						
Total weight	ATM	kg (lb.)	4,914 (10,834)	4,889 (10,779)	4,919 (10,844)	4,974 (10,964)
Front axle	ATM	kg (lb.)	2,957 (6,500)	3,034 (6,692)	2,940 (6,743)	3,112 (6,860)
Rear axle	ATM	kg (lb.)	1,957 (4,314)	1,855 (4,087)	1,827 (4,101)	1,862 (4,104)
Unsprung weight	Front	kg (lb.)	690 (1,520)	690 (1,520)	690 (1,520)	690 (1,520)
	Rear	kg (lb.)	1,125 (2,480)	1,125 (2,480)	1,125 (2,480)	1,125 (2,480)
Center of gravity height from the ground		mm (in.)	795 (31.3)	795 (31.3)	795 (31.3)	795 (31.3)



Model			NV8JPSA	NV8JRSA	NV8JTSA	NV8JVSA
<b>CAPACITY</b>						
GVWR	Manual T/M	kg (lb.)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)
	Auto T/M	kg (lb.)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)
GAWR	Front	kg (lb.)	5,980 (13,200)	5,980 (13,200)	5,980 (13,200)	5,980 (13,200)
	Rear	kg (lb.)	8,620 (19,000)	8,620 (19,000)	8,620 (19,000)	8,620 (19,000)
<b>DIMENSIONS</b> (On standard specifications)						
Wheelbase		mm (in.)	5,512 (217.0)	5,969 (235.0)	6,426 (253.0)	6,883 (271.0)
Overall length		mm (in.)	9,007 (354.6)	9,464 (372.6)	9,921 (390.6)	9,921 (390.6)
Overall width		mm (in.)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)
Overall height		mm (in.)	2,720 (107.1)	2,720 (107.1)	2,720 (107.1)	2,720 (107.1)
BBC		mm (in.)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)
Cab to axle		mm (in.)	3,800 (149.6)	4,257 (167.6)	4,714 (185.6)	5,171 (203.6)
Rear overhang		mm (in.)	2,464 (97.0)	2,464 (97.0)	2,464 (97.0)	2,007 (79.0)
Frame height at	Front axle	mm (in.)	950 (37.4)	950 (37.4)	950 (37.4)	950 (37.4)
	Rear axle	mm (in.)	1,010 (39.8)	1,010 (39.8)	1,010 (39.8)	1,010 (39.8)
Road clearance (at diff. case)		mm (in.)	285 (11.2)	285 (11.2)	285 (11.2)	285 (11.2)
Tread	Front	mm (in.)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)
	Rear	mm (in.)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)
Turning radius Tire		mm (in.)	8,890 (350.0)	9,570 (376.8)	10,240 (403.1)	10,910 (429.5)
Turning radius Swept		mm (in.)	9,410 (370.5)	10,090 (397.2)	10,760 (423.6)	11,430 (450.0)
<b>CHASSIS WEIGHTS</b> (on std. spec., without spare tire & std. tool set)						
<b>MANUAL T/M</b>						
Total weight	MT	kg (lb.)	5,075 (11,187)	5,095 (11,232)	5,115 (11,277)	5,150 (11,352)
Front axle	MT	kg (lb.)	3,168 (6,984)	3,200 (7,055)	3,261 (7,188)	3,271 (7,209)
Rear axle	MT	kg (lb.)	1,907 (4,203)	1,895 (4,177)	1,854 (4,089)	1,879 (4,143)
Unsprung weight	Front	kg (lb.)	690 (1,520)	690 (1,520)	690 (1,520)	690 (1,520)
	Rear	kg (lb.)	1,125 (2,480)	1,125 (2,480)	1,125 (2,480)	1,125 (2,480)
<b>AUTO T/M</b>						
Total weight	ATM	kg (lb.)	5,024 (11,074)	5,044 (11,119)	5,064 (11,164)	5,099 (11,239)
Front axle	ATM	kg (lb.)	3,121 (6,879)	3,156 (6,955)	3,215 (7,089)	3,224 (7,108)
Rear axle	ATM	kg (lb.)	1,903 (4,195)	1,888 (4,164)	1,849 (4,075)	1,875 (4,131)
Unsprung weight	Front	kg (lb.)	690 (1,520)	690 (1,520)	690 (1,520)	690 (1,520)
	Rear	kg (lb.)	1,125 (2,480)	1,125 (2,480)	1,125 (2,480)	1,125 (2,480)
Center of gravity height from the ground		mm (in.)	795 (31.3)	795 (31.3)	795 (31.3)	795 (31.3)

## NV8J

Fr. Axl : MFS10 Fr. Spg : 12,000 lbs

Rr. Axl : RS23 Rr. Spg : 23,000 lbs

Model			NV8JGSA	NV8JJSA	NV8JLSA	NV8JMSA
<b>CAPACITY</b>						
GVWR	Manual T/M	kg (lb.)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)
	Auto T/M	kg (lb.)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)
GAWR	Front	kg (lb.)	4,540 (10,000)	4,540 (10,000)	4,540 (10,000)	4,540 (10,000)
	Rear	kg (lb.)	10,430 (23,000)	10,430 (23,000)	10,430 (23,000)	10,430 (23,000)
<b>DIMENSIONS</b> (On standard specifications)						
Wheelbase		mm (in.)	3,861 (152.0)	4,445 (175.0)	4,750 (187.0)	5,207 (205.0)
Overall length		mm (in.)	6,162 (242.6)	7,076 (278.6)	7,686 (302.6)	8,143 (320.6)
Overall width		mm (in.)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)
Overall height		mm (in.)	2,720 (107.1)	2,720 (107.1)	2,720 (107.1)	2,720 (107.1)
BBC		mm (in.)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)
Cab to axle		mm (in.)	2,149 (84.6)	2,733 (107.6)	3,038 (119.6)	3,495 (137.6)
Rear overhang		mm (in.)	1,270 (50.0)	1,600 (63.0)	1,905 (75.0)	1,905 (75.0)
Frame height at	Front axle	mm (in.)	940 (37.0)	940 (37.0)	940 (37.0)	940 (37.0)
	Rear axle	mm (in.)	1,030 (40.6)	1,030 (40.6)	1,030 (40.6)	1,030 (40.6)
Road clearance (at diff. case)		mm (in.)	255 (10.0)	255 (10.0)	255 (10.0)	255 (10.0)
Tread	Front	mm (in.)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)
	Rear	mm (in.)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)
Turning radius Tire		mm (in.)	6,400 (252.0)	7,240 (285.0)	7,690 (302.8)	8,350 (328.7)
Turning radius Swept		mm (in.)	6,920 (272.4)	7,760 (305.5)	8,210 (323.2)	8,870 (349.2)
<b>CHASSIS WEIGHTS</b> (on std. spec., without spare tire & std. tool set)						
<b>MANUAL T/M</b>						
Total weight	MT	kg (lb.)	5,020 (11,067)	5,070 (11,177)	5,105 (11,252)	5,180 (11,422)
Front axle	MT	kg (lb.)	2,945 (6,494)	3,067 (6,762)	3,094 (6,817)	3,154 (6,954)
Rear axle	MT	kg (lb.)	2,075 (4,573)	2,003 (4,415)	2,011 (4,435)	2,026 (4,468)
Unsprung weight	Front	kg (lb.)	645 (1,420)	645 (1,420)	645 (1,420)	645 (1,420)
	Rear	kg (lb.)	1,225 (2,700)	1,225 (2,700)	1,225 (2,700)	1,225 (2,700)
<b>AUTO T/M</b>						
Total weight	ATM	kg (lb.)	5,100 (11,242)	5,145 (11,342)	5,180 (11,422)	5,260 (11,597)
Front axle	ATM	kg (lb.)	3,000 (6,614)	3,117 (6,872)	3,149 (6,942)	3,214 (7,084)
Rear axle	ATM	kg (lb.)	2,100 (4,628)	2,028 (4,470)	2,031 (4,480)	2,046 (4,513)
Unsprung weight	Front	kg (lb.)	645 (1,420)	645 (1,420)	645 (1,420)	645 (1,420)
	Rear	kg (lb.)	1,225 (2,700)	1,225 (2,700)	1,225 (2,700)	1,225 (2,700)
Center of gravity height from the ground		mm (in.)	795 (31.3)	795 (31.3)	795 (31.3)	795 (31.3)

Model			NV8JPSA	NV8JRSA	NV8JTSA	NV8JVSA
<b>CAPACITY</b>						
GVWR	Manual T/M	kg (lb.)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)
	Auto T/M	kg (lb.)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)
GAWR	Front	kg (lb.)	4,540 (10,000)	4,540 (10,000)	4,540 (10,000)	4,540 (10,000)
	Rear	kg (lb.)	10,430 (23,000)	10,430 (23,000)	10,430 (23,000)	10,430 (23,000)
<b>DIMENSIONS</b> (On standard specifications)						
Wheelbase		mm (in.)	5,512 (217.0)	5,969 (235.0)	6,426 (253.0)	6,883 (271.0)
Overall length		mm (in.)	9,007 (354.6)	9,464 (372.6)	9,921 (390.6)	9,921 (390.6)
Overall width		mm (in.)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)
Overall height		mm (in.)	2,720 (107.1)	2,720 (107.1)	2,720 (107.1)	2,720 (107.1)
BBC		mm (in.)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)
Cab to axle		mm (in.)	3,800 (149.6)	4,257 (167.6)	4,714 (185.6)	5,171 (203.6)
Rear overhang		mm (in.)	2,464 (97.0)	2,464 (97.0)	2,464 (97.0)	2,007 (79.0)
Frame height at	Front axle	mm (in.)	940 (37.0)	940 (37.0)	940 (37.0)	940 (37.0)
	Rear axle	mm (in.)	1,030 (40.6)	1,030 (40.6)	1,030 (40.6)	1,030 (40.6)
Road clearance (at diff. case)		mm (in.)	255 (10.0)	255 (10.0)	255 (10.0)	255 (10.0)
Tread	Front	mm (in.)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)
	Rear	mm (in.)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)
Turning radius Tire		mm (in.)	8,790 (346.1)	9,460 (372.4)	10,120 (398.4)	10,790 (424.8)
Turning radius Swept		mm (in.)	9,310 (366.5)	9,980 (392.9)	10,640 (418.9)	11,310 (445.3)
<b>CHASSIS WEIGHTS</b> (on std. spec., without spare tire & std. tool set)						
<b>MANUAL T/M</b>						
Total weight	MT	kg (lb.)	5,220 (11,507)	5,245 (11,562)	5,270 (11,617)	5,300 (11,682)
Front axle	MT	kg (lb.)	3,154 (6,950)	3,191 (7,036)	3,257 (7,179)	3,262 (7,190)
Rear axle	MT	kg (lb.)	2,066 (4,557)	2,054 (4,526)	2,013 (4,438)	2,038 (4,492)
Unsprung weight	Front	kg (lb.)	645 (1,420)	645 (1,420)	645 (1,420)	645 (1,420)
	Rear	kg (lb.)	1,225 (2,700)	1,225 (2,700)	1,225 (2,700)	1,225 (2,700)
<b>AUTO T/M</b>						
Total weight	ATM	kg (lb.)	5,300 (11,682)	5,325 (11,737)	5,345 (11,782)	5,380 (11,862)
Front axle	ATM	kg (lb.)	3,219 (7,095)	3,256 (7,176)	3,317 (7,309)	3,327 (7,335)
Rear axle	ATM	kg (lb.)	2,081 (4,587)	2,069 (4,561)	2,028 (4,473)	2,053 (4,527)
Unsprung weight	Front	kg (lb.)	645 (1,420)	645 (1,420)	645 (1,420)	645 (1,420)
	Rear	kg (lb.)	1,225 (2,700)	1,225 (2,700)	1,225 (2,700)	1,225 (2,700)
Center of gravity height from the ground		mm (in.)	795 (31.3)	795 (31.3)	795 (31.3)	795 (31.3)

## NV8J

Fr. Axl : MFS10 Fr. Spg : 12,000 lbs

Rr. Axl : RS23 Rr. Spg : 31,000 lbs

Model			NV8JGSA	NV8JJSA	NV8JLSA	NV8JMSA
<b>CAPACITY</b>						
GVWR	Manual T/M	kg (lb.)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)
	Auto T/M	kg (lb.)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)
GAWR	Front	kg (lb.)	4,540 (10,000)	4,540 (10,000)	4,540 (10,000)	4,540 (10,000)
	Rear	kg (lb.)	10,430 (23,000)	10,430 (23,000)	10,430 (23,000)	10,430 (23,000)
<b>DIMENSIONS</b> (On standard specifications)						
Wheelbase		mm (in.)	3,861 (152.0)	4,445 (175.0)	4,750 (187.0)	5,207 (205.0)
Overall length		mm (in.)	6,162 (242.6)	7,076 (278.6)	7,686 (302.6)	8,143 (320.6)
Overall width		mm (in.)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)
Overall height		mm (in.)	2,720 (107.1)	2,720 (107.1)	2,720 (107.1)	2,720 (107.1)
BBC		mm (in.)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)
Cab to axle		mm (in.)	2,149 (84.6)	2,733 (107.6)	3,038 (119.6)	3,495 (137.6)
Rear overhang		mm (in.)	1,270 (50.0)	1,600 (63.0)	1,905 (75.0)	1,905 (75.0)
Frame height at	Front axle	mm (in.)	940 (37.0)	940 (37.0)	940 (37.0)	940 (37.0)
	Rear axle	mm (in.)	1,030 (40.6)	1,030 (40.6)	1,030 (40.6)	1,030 (40.6)
Road clearance (at diff. case)		mm (in.)	255 (10.0)	255 (10.0)	255 (10.0)	255 (10.0)
Tread	Front	mm (in.)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)
	Rear	mm (in.)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)
Turning radius Tire		mm (in.)	6,400 (252.0)	7,240 (285.0)	7,690 (302.8)	8,350 (328.7)
Turning radius Swept		mm (in.)	6,920 (272.4)	7,760 (305.5)	8,210 (323.2)	8,870 (349.2)
<b>CHASSIS WEIGHTS</b> (on std. spec., without spare tire & std. tool set)						
<b>MANUAL T/M</b>						
Total weight	MT	kg (lb.)	5,054 (11,142)	5,104 (11,252)	5,139 (11,332)	5,214 (11,497)
Front axle	MT	kg (lb.)	2,949 (6,503)	3,071 (6,771)	3,098 (6,831)	3,158 (6,963)
Rear axle	MT	kg (lb.)	2,105 (4,639)	2,033 (4,481)	2,041 (4,501)	2,056 (4,534)
Unsprung weight	Front	kg (lb.)	645 (1,420)	645 (1,420)	645 (1,420)	645 (1,420)
	Rear	kg (lb.)	1,225 (2,700)	1,225 (2,700)	1,225 (2,700)	1,225 (2,700)
<b>AUTO T/M</b>						
Total weight	ATM	kg (lb.)	5,134 (11,317)	5,179 (11,417)	5,214 (11,497)	5,294 (11,672)
Front axle	ATM	kg (lb.)	3,004 (6,623)	3,121 (6,881)	3,153 (6,951)	3,218 (7,093)
Rear axle	ATM	kg (lb.)	2,130 (4,694)	2,058 (4,536)	2,061 (4,546)	2,076 (4,579)
Unsprung weight	Front	kg (lb.)	645 (1,420)	645 (1,420)	645 (1,420)	645 (1,420)
	Rear	kg (lb.)	1,225 (2,700)	1,225 (2,700)	1,225 (2,700)	1,225 (2,700)
Center of gravity height from the ground		mm (in.)	795 (31.3)	795 (31.3)	795 (31.3)	795 (31.3)

Model			NV8JPSA	NV8JRSA	NV8JTSA	NV8JVSA
<b>CAPACITY</b>						
GVWR	Manual T/M	kg (lb.)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)
	Auto T/M	kg (lb.)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)
GAWR	Front	kg (lb.)	4,540 (10,000)	4,540 (10,000)	4,540 (10,000)	4,540 (10,000)
	Rear	kg (lb.)	10,430 (23,000)	10,430 (23,000)	10,430 (23,000)	10,430 (23,000)
<b>DIMENSIONS</b> (On standard specifications)						
Wheelbase		mm (in.)	5,512 (217.0)	5,969 (235.0)	6,426 (253.0)	6,883 (271.0)
Overall length		mm (in.)	9,007 (354.6)	9,464 (372.6)	9,921 (390.6)	9,921 (390.6)
Overall width		mm (in.)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)
Overall height		mm (in.)	2,720 (107.1)	2,720 (107.1)	2,720 (107.1)	2,720 (107.1)
BBC		mm (in.)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)
Cab to axle		mm (in.)	3,800 (149.6)	4,257 (167.6)	4,714 (185.6)	5,171 (203.6)
Rear overhang		mm (in.)	2,464 (97.0)	2,464 (97.0)	2,464 (97.0)	2,007 (79.0)
Frame height at	Front axle	mm (in.)	940 (37.0)	940 (37.0)	940 (37.0)	940 (37.0)
	Rear axle	mm (in.)	1,030 (40.6)	1,030 (40.6)	1,030 (40.6)	1,030 (40.6)
Road clearance (at diff. case)		mm (in.)	255 (10.0)	255 (10.0)	255 (10.0)	255 (10.0)
Tread	Front	mm (in.)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)
	Rear	mm (in.)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)
Turning radius Tire		mm (in.)	8,790 (346.1)	9,460 (372.4)	10,120 (398.4)	10,790 (424.8)
Turning radius Swept		mm (in.)	9,310 (366.5)	9,980 (392.9)	10,640 (418.9)	11,310 (445.3)
<b>CHASSIS WEIGHTS</b> (on std. spec., without spare tire & std. tool set)						
<b>MANUAL T/M</b>						
Total weight	MT	kg (lb.)	5,254 (11,582)	5,279 (11,637)	5,304 (11,692)	5,334 (11,757)
Front axle	MT	kg (lb.)	3,158 (6,964)	3,195 (7,045)	3,261 (7,188)	3,266 (7,199)
Rear axle	MT	kg (lb.)	2,096 (4,623)	2,084 (4,592)	2,043 (4,504)	2,068 (4,558)
Unsprung weight	Front	kg (lb.)	645 (1,420)	645 (1,420)	645 (1,420)	645 (1,420)
	Rear	kg (lb.)	1,225 (2,700)	1,225 (2,700)	1,225 (2,700)	1,225 (2,700)
<b>AUTO T/M</b>						
Total weight	ATM	kg (lb.)	5,334 (11,757)	5,359 (11,817)	5,379 (11,857)	5,414 (11,937)
Front axle	ATM	kg (lb.)	3,223 (7,104)	3,260 (7,185)	3,321 (7,323)	3,331 (7,344)
Rear axle	ATM	kg (lb.)	2,111 (4,653)	2,099 (4,627)	2,058 (4,539)	2,083 (4,593)
Unsprung weight	Front	kg (lb.)	645 (1,420)	645 (1,420)	645 (1,420)	645 (1,420)
	Rear	kg (lb.)	1,225 (2,700)	1,225 (2,700)	1,225 (2,700)	1,225 (2,700)
Center of gravity height from the ground		mm (in.)	795 (31.3)	795 (31.3)	795 (31.3)	795 (31.3)

## NV8J

Fr. Axl : MFS12 Fr. Spg : 12,000 lbs

Rr. Axl : RS23 Rr. Spg : 23,000 lbs

Model			NV8JGSA	NV8JJSA	NV8JLSA	NV8JMSA
<b>CAPACITY</b>						
GVWR	Manual T/M	kg (lb.)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)
	Auto T/M	kg (lb.)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)
GAWR	Front	kg (lb.)	5,440 (12,000)	5,440 (12,000)	5,440 (12,000)	5,440 (12,000)
	Rear	kg (lb.)	10,430 (23,000)	10,430 (23,000)	10,430 (23,000)	10,430 (23,000)
<b>DIMENSIONS</b> (On standard specifications)						
Wheelbase		mm (in.)	3,861 (152.0)	4,445 (175.0)	4,750 (187.0)	5,207 (205.0)
Overall length		mm (in.)	6,162 (242.6)	7,076 (278.6)	7,686 (302.6)	8,143 (320.6)
Overall width		mm (in.)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)
Overall height		mm (in.)	2,720 (107.1)	2,720 (107.1)	2,720 (107.1)	2,720 (107.1)
BBC		mm (in.)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)
Cab to axle		mm (in.)	2,149 (84.6)	2,733 (107.6)	3,038 (119.6)	3,495 (137.6)
Rear overhang		mm (in.)	1,270 (50.0)	1,600 (63.0)	1,905 (75.0)	1,905 (75.0)
Frame height at	Front axle	mm (in.)	940 (37.0)	940 (37.0)	940 (37.0)	940 (37.0)
	Rear axle	mm (in.)	1,030 (40.6)	1,030 (40.6)	1,030 (40.6)	1,030 (40.6)
Road clearance (at diff. case)		mm (in.)	255 (10.0)	255 (10.0)	255 (10.0)	255 (10.0)
Tread	Front	mm (in.)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)
	Rear	mm (in.)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)
Turning radius Tire		mm (in.)	6,400 (252.0)	7,240 (285.0)	7,690 (302.8)	8,350 (328.7)
Turning radius Swept		mm (in.)	6,920 (272.4)	7,760 (305.5)	8,210 (323.2)	8,870 (349.2)
<b>CHASSIS WEIGHTS</b> (on std. spec., without spare tire & std. tool set)						
<b>MANUAL T/M</b>						
Total weight	MT	kg (lb.)	5,020 (11,067)	5,070 (11,177)	5,105 (11,252)	5,180 (11,422)
Front axle	MT	kg (lb.)	2,945 (6,494)	3,067 (6,762)	3,094 (6,817)	3,154 (6,954)
Rear axle	MT	kg (lb.)	2,075 (4,573)	2,003 (4,415)	2,011 (4,435)	2,026 (4,468)
Unsprung weight	Front	kg (lb.)	645 (1,420)	645 (1,420)	645 (1,420)	645 (1,420)
	Rear	kg (lb.)	1,225 (2,700)	1,225 (2,700)	1,225 (2,700)	1,225 (2,700)
<b>AUTO T/M</b>						
Total weight	ATM	kg (lb.)	5,100 (11,242)	5,145 (11,342)	5,180 (11,422)	5,260 (11,597)
Front axle	ATM	kg (lb.)	3,000 (6,614)	3,117 (6,872)	3,149 (6,942)	3,214 (7,084)
Rear axle	ATM	kg (lb.)	2,100 (4,628)	2,028 (4,470)	2,031 (4,480)	2,046 (4,513)
Unsprung weight	Front	kg (lb.)	645 (1,420)	645 (1,420)	645 (1,420)	645 (1,420)
	Rear	kg (lb.)	1,225 (2,700)	1,225 (2,700)	1,225 (2,700)	1,225 (2,700)
Center of gravity height from the ground		mm (in.)	795 (31.3)	795 (31.3)	795 (31.3)	795 (31.3)

Model			NV8JPSA	NV8JRSA	NV8JTSA	NV8JVSA
<b>CAPACITY</b>						
GVWR	Manual T/M	kg (lb.)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)
	Auto T/M	kg (lb.)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)
GAWR	Front	kg (lb.)	5,440 (12,000)	5,440 (12,000)	5,440 (12,000)	5,440 (12,000)
	Rear	kg (lb.)	10,430 (23,000)	10,430 (23,000)	10,430 (23,000)	10,430 (23,000)
<b>DIMENSIONS</b> (On standard specifications)						
Wheelbase		mm (in.)	5,512 (217.0)	5,969 (235.0)	6,426 (253.0)	6,883 (271.0)
Overall length		mm (in.)	9,007 (354.6)	9,464 (372.6)	9,921 (390.6)	9,921 (390.6)
Overall width		mm (in.)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)
Overall height		mm (in.)	2,720 (107.1)	2,720 (107.1)	2,720 (107.1)	2,720 (107.1)
BBC		mm (in.)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)
Cab to axle		mm (in.)	3,800 (149.6)	4,257 (167.6)	4,714 (185.6)	5,171 (203.6)
Rear overhang		mm (in.)	2,464 (97.0)	2,464 (97.0)	2,464 (97.0)	2,007 (79.0)
Frame height at	Front axle	mm (in.)	940 (37.0)	940 (37.0)	940 (37.0)	940 (37.0)
	Rear axle	mm (in.)	1,030 (40.6)	1,030 (40.6)	1,030 (40.6)	1,030 (40.6)
Road clearance (at diff. case)		mm (in.)	255 (10.0)	255 (10.0)	255 (10.0)	255 (10.0)
Tread	Front	mm (in.)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)
	Rear	mm (in.)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)
Turning radius Tire		mm (in.)	8,790 (346.1)	9,460 (372.4)	10,120 (398.4)	10,790 (424.8)
Turning radius Swept		mm (in.)	9,310 (366.5)	9,980 (392.9)	10,640 (418.9)	11,310 (445.3)
<b>CHASSIS WEIGHTS</b> (on std. spec., without spare tire & std. tool set)						
<b>MANUAL T/M</b>						
Total weight	MT	kg (lb.)	5,220 (11,507)	5,245 (11,562)	5,270 (11,617)	5,300 (11,682)
Front axle	MT	kg (lb.)	3,154 (6,950)	3,191 (7,036)	3,257 (7,179)	3,262 (7,190)
Rear axle	MT	kg (lb.)	2,066 (4,557)	2,054 (4,526)	2,013 (4,438)	2,038 (4,492)
Unsprung weight	Front	kg (lb.)	645 (1,420)	645 (1,420)	645 (1,420)	645 (1,420)
	Rear	kg (lb.)	1,225 (2,700)	1,225 (2,700)	1,225 (2,700)	1,225 (2,700)
<b>AUTO T/M</b>						
Total weight	ATM	kg (lb.)	5,300 (11,682)	5,325 (11,737)	5,345 (11,782)	5,380 (11,862)
Front axle	ATM	kg (lb.)	3,219 (7,095)	3,256 (7,176)	3,317 (7,309)	3,327 (7,335)
Rear axle	ATM	kg (lb.)	2,081 (4,587)	2,069 (4,561)	2,028 (4,473)	2,053 (4,527)
Unsprung weight	Front	kg (lb.)	645 (1,420)	645 (1,420)	645 (1,420)	645 (1,420)
	Rear	kg (lb.)	1,225 (2,700)	1,225 (2,700)	1,225 (2,700)	1,225 (2,700)
Center of gravity height from the ground		mm (in.)	795 (31.3)	795 (31.3)	795 (31.3)	795 (31.3)



## NV8J

Fr. Axl : MFS12 Fr. Spg : 12,000 lbs

Rr. Axl : RS23 Rr. Spg : 31,000 lbs

Model			NV8JGSA	NV8JJSA	NV8JLSA	NV8JMSA
<b>CAPACITY</b>						
GVWR	Manual T/M	kg (lb.)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)
	Auto T/M	kg (lb.)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)
GAWR	Front	kg (lb.)	5,440 (12,000)	5,440 (12,000)	5,440 (12,000)	5,440 (12,000)
	Rear	kg (lb.)	10,430 (23,000)	10,430 (23,000)	10,430 (23,000)	10,430 (23,000)
<b>DIMENSIONS</b> (On standard specifications)						
Wheelbase		mm (in.)	3,861 (152.0)	4,445 (175.0)	4,750 (187.0)	5,207 (205.0)
Overall length		mm (in.)	6,162 (242.6)	7,076 (278.6)	7,686 (302.6)	8,143 (320.6)
Overall width		mm (in.)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)
Overall height		mm (in.)	2,720 (107.1)	2,720 (107.1)	2,720 (107.1)	2,720 (107.1)
BBC		mm (in.)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)
Cab to axle		mm (in.)	2,149 (84.6)	2,733 (107.6)	3,038 (119.6)	3,495 (137.6)
Rear overhang		mm (in.)	1,270 (50.0)	1,600 (63.0)	1,905 (75.0)	1,905 (75.0)
Frame height at	Front axle	mm (in.)	940 (37.0)	940 (37.0)	940 (37.0)	940 (37.0)
	Rear axle	mm (in.)	1,030 (40.6)	1,030 (40.6)	1,030 (40.6)	1,030 (40.6)
Road clearance (at diff. case)		mm (in.)	255 (10.0)	255 (10.0)	255 (10.0)	255 (10.0)
Tread	Front	mm (in.)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)
	Rear	mm (in.)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)
Turning radius Tire		mm (in.)	6,400 (252.0)	7,240 (285.0)	7,690 (302.8)	8,350 (328.7)
Turning radius Swept		mm (in.)	6,920 (272.4)	7,760 (305.5)	8,210 (323.2)	8,870 (349.2)
<b>CHASSIS WEIGHTS</b> (on std. spec., without spare tire & std. tool set)						
<b>MANUAL T/M</b>						
Total weight	MT	kg (lb.)	5,054 (11,142)	5,104 (11,252)	5,139 (11,332)	5,214 (11,497)
Front axle	MT	kg (lb.)	2,949 (6,503)	3,071 (6,771)	3,098 (6,831)	3,158 (6,963)
Rear axle	MT	kg (lb.)	2,105 (4,639)	2,033 (4,481)	2,041 (4,501)	2,056 (4,534)
Unsprung weight	Front	kg (lb.)	645 (1,420)	645 (1,420)	645 (1,420)	645 (1,420)
	Rear	kg (lb.)	1,225 (2,700)	1,225 (2,700)	1,225 (2,700)	1,225 (2,700)
<b>AUTO T/M</b>						
Total weight	ATM	kg (lb.)	5,134 (11,317)	5,179 (11,417)	5,214 (11,497)	5,294 (11,672)
Front axle	ATM	kg (lb.)	3,004 (6,623)	3,121 (6,881)	3,153 (6,951)	3,218 (7,093)
Rear axle	ATM	kg (lb.)	2,130 (4,694)	2,058 (4,536)	2,061 (4,546)	2,076 (4,579)
Unsprung weight	Front	kg (lb.)	645 (1,420)	645 (1,420)	645 (1,420)	645 (1,420)
	Rear	kg (lb.)	1,225 (2,700)	1,225 (2,700)	1,225 (2,700)	1,225 (2,700)
Center of gravity height from the ground		mm (in.)	795 (31.3)	795 (31.3)	795 (31.3)	795 (31.3)



Model			NV8JPSA	NV8JRSA	NV8JTSA	NV8JVSA
<b>CAPACITY</b>						
GVWR	Manual T/M	kg (lb.)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)
	Auto T/M	kg (lb.)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)
GAWR	Front	kg (lb.)	5,440 (12,000)	5,440 (12,000)	5,440 (12,000)	5,440 (12,000)
	Rear	kg (lb.)	10,430 (23,000)	10,430 (23,000)	10,430 (23,000)	10,430 (23,000)
<b>DIMENSIONS</b> (On standard specifications)						
Wheelbase		mm (in.)	5,512 (217.0)	5,969 (235.0)	6,426 (253.0)	6,883 (271.0)
Overall length		mm (in.)	9,007 (354.6)	9,464 (372.6)	9,921 (390.6)	9,921 (390.6)
Overall width		mm (in.)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)
Overall height		mm (in.)	2,720 (107.1)	2,720 (107.1)	2,720 (107.1)	2,720 (107.1)
BBC		mm (in.)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)
Cab to axle		mm (in.)	3,800 (149.6)	4,257 (167.6)	4,714 (185.6)	5,171 (203.6)
Rear overhang		mm (in.)	2,464 (97.0)	2,464 (97.0)	2,464 (97.0)	2,007 (79.0)
Frame height at	Front axle	mm (in.)	940 (37.0)	940 (37.0)	940 (37.0)	940 (37.0)
	Rear axle	mm (in.)	1,030 (40.6)	1,030 (40.6)	1,030 (40.6)	1,030 (40.6)
Road clearance (at diff. case)		mm (in.)	255 (10.0)	255 (10.0)	255 (10.0)	255 (10.0)
Tread	Front	mm (in.)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)
	Rear	mm (in.)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)
Turning radius Tire		mm (in.)	8,790 (346.1)	9,460 (372.4)	10,120 (398.4)	10,790 (424.8)
Turning radius Swept		mm (in.)	9,310 (366.5)	9,980 (392.9)	10,640 (418.9)	11,310 (445.3)
<b>CHASSIS WEIGHTS</b> (on std. spec., without spare tire & std. tool set)						
<b>MANUAL T/M</b>						
Total weight	MT	kg (lb.)	5,254 (11,582)	5,279 (11,637)	5,304 (11,692)	5,334 (11,757)
Front axle	MT	kg (lb.)	3,158 (6,964)	3,195 (7,045)	3,261 (7,188)	3,266 (7,199)
Rear axle	MT	kg (lb.)	2,096 (4,623)	2,084 (4,592)	2,043 (4,504)	2,068 (4,558)
Unsprung weight	Front	kg (lb.)	645 (1,420)	645 (1,420)	645 (1,420)	645 (1,420)
	Rear	kg (lb.)	1,225 (2,700)	1,225 (2,700)	1,225 (2,700)	1,225 (2,700)
<b>AUTO T/M</b>						
Total weight	ATM	kg (lb.)	5,334 (11,757)	5,359 (11,817)	5,379 (11,857)	5,414 (11,937)
Front axle	ATM	kg (lb.)	3,223 (7,104)	3,260 (7,185)	3,321 (7,323)	3,331 (7,344)
Rear axle	ATM	kg (lb.)	2,111 (4,653)	2,099 (4,627)	2,058 (4,539)	2,083 (4,593)
Unsprung weight	Front	kg (lb.)	645 (1,420)	645 (1,420)	645 (1,420)	645 (1,420)
	Rear	kg (lb.)	1,225 (2,700)	1,225 (2,700)	1,225 (2,700)	1,225 (2,700)
Center of gravity height from the ground		mm (in.)	795 (31.3)	795 (31.3)	795 (31.3)	795 (31.3)

## NV8J

Fr. Axl : MFS14 Fr. Spg : 14,000 lbs

Rr. Axl : RS21 Rr. Spg : 21,000 lbs

Model			NV8JGSA	NV8JJSA	NV8JLSA	NV8JMSA
<b>CAPACITY</b>						
GVWR	Manual T/M	kg (lb.)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)
	Auto T/M	kg (lb.)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)
GAWR	Front	kg (lb.)	5,980 (13,200)	5,980 (13,200)	5,980 (13,200)	5,980 (13,200)
	Rear	kg (lb.)	9,530 (21,000)	9,530 (21,000)	9,530 (21,000)	9,530 (21,000)
<b>DIMENSIONS</b> (On standard specifications)						
Wheelbase		mm (in.)	3,861 (152.0)	4,445 (175.0)	4,750 (187.0)	5,207 (205.0)
Overall length		mm (in.)	6,162 (242.6)	7,076 (278.6)	7,686 (302.6)	8,143 (320.6)
Overall width		mm (in.)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)
Overall height		mm (in.)	2,730 (107.5)	2,730 (107.5)	2,730 (107.5)	2,730 (107.5)
BBC		mm (in.)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)
Cab to axle		mm (in.)	2,149 (84.6)	2,733 (107.6)	3,038 (119.6)	3,495 (137.6)
Rear overhang		mm (in.)	1,270 (50.0)	1,600 (63.0)	1,905 (75.0)	1,905 (75.0)
Frame height at	Front axle	mm (in.)	950 (37.4)	950 (37.4)	950 (37.4)	950 (37.4)
	Rear axle	mm (in.)	1,030 (40.6)	1,030 (40.6)	1,030 (40.6)	1,030 (40.6)
Road clearance (at diff. case)		mm (in.)	285 (11.2)	285 (11.2)	285 (11.2)	285 (11.2)
Tread	Front	mm (in.)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)
	Rear	mm (in.)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)
Turning radius Tire		mm (in.)	6,470 (254.7)	7,330 (288.6)	7,770 (305.9)	8,440 (332.3)
Turning radius Swept		mm (in.)	6,990 (275.2)	7,850 (309.1)	8,290 (326.4)	8,970 (353.1)
<b>CHASSIS WEIGHTS</b> (on std. spec., without spare tire & std. tool set)						
<b>MANUAL T/M</b>						
Total weight	MT	kg (lb.)	4,975 (10,967)	5,020 (11,067)	5,055 (11,142)	5,135 (11,322)
Front axle	MT	kg (lb.)	2,999 (6,613)	3,111 (6,861)	3,138 (6,916)	3,203 (7,063)
Rear axle	MT	kg (lb.)	1,976 (4,354)	1,909 (4,206)	1,917 (4,226)	1,932 (4,259)
Unsprung weight	Front	kg (lb.)	690 (1,520)	690 (1,520)	690 (1,520)	690 (1,520)
	Rear	kg (lb.)	1,135 (2,500)	1,135 (2,500)	1,135 (2,500)	1,135 (2,500)
<b>AUTO T/M</b>						
Total weight	ATM	kg (lb.)	4,924 (10,854)	4,969 (10,954)	5,004 (11,034)	5,084 (11,209)
Front axle	ATM	kg (lb.)	2,952 (6,505)	3,064 (6,757)	3,094 (6,823)	3,157 (6,960)
Rear axle	ATM	kg (lb.)	1,972 (4,349)	1,905 (4,197)	1,910 (4,211)	1,927 (4,249)
Unsprung weight	Front	kg (lb.)	690 (1,520)	690 (1,520)	690 (1,520)	690 (1,520)
	Rear	kg (lb.)	1,135 (2,500)	1,135 (2,500)	1,135 (2,500)	1,135 (2,500)
Center of gravity height from the ground		mm (in.)	795 (31.3)	795 (31.3)	795 (31.3)	795 (31.3)

Model			NV8JPSA	NV8JRSA	NV8JTSA	NV8JVSA
<b>CAPACITY</b>						
GVWR	Manual T/M	kg (lb.)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)
	Auto T/M	kg (lb.)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)
GAWR	Front	kg (lb.)	5,980 (13,200)	5,980 (13,200)	5,980 (13,200)	5,980 (13,200)
	Rear	kg (lb.)	9,530 (21,000)	9,530 (21,000)	9,530 (21,000)	9,530 (21,000)
<b>DIMENSIONS</b> (On standard specifications)						
Wheelbase		mm (in.)	5,512 (217.0)	5,969 (235.0)	6,426 (253.0)	6,883 (271.0)
Overall length		mm (in.)	9,007 (354.6)	9,464 (372.6)	9,921 (390.6)	9,921 (390.6)
Overall width		mm (in.)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)
Overall height		mm (in.)	2,730 (107.5)	2,730 (107.5)	2,730 (107.5)	2,730 (107.5)
BBC		mm (in.)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)
Cab to axle		mm (in.)	3,800 (149.6)	4,257 (167.6)	4,714 (185.6)	5,171 (203.6)
Rear overhang		mm (in.)	2,464 (97.0)	2,464 (97.0)	2,464 (97.0)	2,007 (79.0)
Frame height at	Front axle	mm (in.)	950 (37.4)	950 (37.4)	950 (37.4)	950 (37.4)
	Rear axle	mm (in.)	1,030 (40.6)	1,030 (40.6)	1,030 (40.6)	1,030 (40.6)
Road clearance (at diff. case)		mm (in.)	285 (11.2)	285 (11.2)	285 (11.2)	285 (11.2)
Tread	Front	mm (in.)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)
	Rear	mm (in.)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)
Turning radius Tire		mm (in.)	8,890 (350.0)	9,570 (376.8)	10,240 (403.1)	10,910 (429.5)
Turning radius Swept		mm (in.)	9,410 (370.5)	10,090 (397.2)	10,760 (423.6)	11,430 (450.0)
<b>CHASSIS WEIGHTS</b> (on std. spec., without spare tire & std. tool set)						
<b>MANUAL T/M</b>						
Total weight	MT	kg (lb.)	5,175 (11,407)	5,200 (11,462)	5,220 (11,507)	5,255 (11,587)
Front axle	MT	kg (lb.)	3,208 (7,069)	3,240 (7,140)	3,301 (7,278)	3,311 (7,299)
Rear axle	MT	kg (lb.)	1,967 (4,338)	1,960 (4,322)	1,919 (4,229)	1,944 (4,288)
Unsprung weight	Front	kg (lb.)	690 (1,520)	690 (1,520)	690 (1,520)	690 (1,520)
	Rear	kg (lb.)	1,135 (2,500)	1,135 (2,500)	1,135 (2,500)	1,135 (2,500)
<b>AUTO T/M</b>						
Total weight	ATM	kg (lb.)	5,124 (11,294)	5,149 (11,349)	5,169 (11,394)	5,204 (11,474)
Front axle	ATM	kg (lb.)	3,161 (6,964)	3,196 (7,045)	3,255 (7,174)	3,264 (7,198)
Rear axle	ATM	kg (lb.)	1,963 (4,330)	1,953 (4,304)	1,914 (4,220)	1,940 (4,276)
Unsprung weight	Front	kg (lb.)	690 (1,520)	690 (1,520)	690 (1,520)	690 (1,520)
	Rear	kg (lb.)	1,135 (2,500)	1,135 (2,500)	1,135 (2,500)	1,135 (2,500)
Center of gravity height from the ground		mm (in.)	795 (31.3)	795 (31.3)	795 (31.3)	795 (31.3)

## NV8J

Fr. Axl : MFS14 Fr. Spg : 14,000 lbs

Rr. Axl : RS23 Rr. Spg : 23,000 lbs

Model			NV8JGSA	NV8JJSA	NV8JLSA	NV8JMSA
<b>CAPACITY</b>						
GVWR	Manual T/M	kg (lb.)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)
	Auto T/M	kg (lb.)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)
GAWR	Front	kg (lb.)	5,980 (13,200)	5,980 (13,200)	5,980 (13,200)	5,980 (13,200)
	Rear	kg (lb.)	10,430 (23,000)	10,430 (23,000)	10,430 (23,000)	10,430 (23,000)
<b>DIMENSIONS</b> (On standard specifications)						
Wheelbase		mm (in.)	3,861 (152.0)	4,445 (175.0)	4,750 (187.0)	5,207 (205.0)
Overall length		mm (in.)	6,162 (242.6)	7,076 (278.6)	7,686 (302.6)	8,143 (320.6)
Overall width		mm (in.)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)
Overall height		mm (in.)	2,725 (107.3)	2,725 (107.3)	2,725 (107.3)	2,725 (107.3)
BBC		mm (in.)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)
Cab to axle		mm (in.)	2,149 (84.6)	2,733 (107.6)	3,038 (119.6)	3,495 (137.6)
Rear overhang		mm (in.)	1,270 (50.0)	1,600 (63.0)	1,905 (75.0)	1,905 (75.0)
Frame height at	Front axle	mm (in.)	950 (37.4)	950 (37.4)	950 (37.4)	950 (37.4)
	Rear axle	mm (in.)	1,030 (40.6)	1,030 (40.6)	1,030 (40.6)	1,030 (40.6)
Road clearance (at diff. case)		mm (in.)	255 (10.0)	255 (10.0)	255 (10.0)	255 (10.0)
Tread	Front	mm (in.)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)
	Rear	mm (in.)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)
Turning radius Tire		mm (in.)	6,470 (254.7)	7,330 (288.6)	7,770 (305.9)	8,440 (332.3)
Turning radius Swept		mm (in.)	6,990 (275.2)	7,850 (309.1)	8,290 (326.4)	8,970 (353.1)
<b>CHASSIS WEIGHTS</b> (on std. spec., without spare tire & std. tool set)						
<b>MANUAL T/M</b>						
Total weight	MT	kg (lb.)	5,065 (11,187)	5,110 (11,287)	5,145 (11,362)	5,225 (11,537)
Front axle	MT	kg (lb.)	2,990 (6,603)	3,107 (6,861)	3,134 (6,916)	3,199 (7,058)
Rear axle	MT	kg (lb.)	2,075 (4,584)	2,003 (4,426)	2,011 (4,446)	2,026 (4,479)
Unsprung weight	Front	kg (lb.)	690 (1,520)	690 (1,520)	690 (1,520)	690 (1,520)
	Rear	kg (lb.)	1,225 (2,700)	1,225 (2,700)	1,225 (2,700)	1,225 (2,700)
<b>AUTO T/M</b>						
Total weight	ATM	kg (lb.)	5,140 (11,332)	5,185 (11,432)	5,225 (11,517)	5,300 (11,682)
Front axle	ATM	kg (lb.)	3,040 (6,704)	3,157 (6,962)	3,194 (7,037)	3,254 (7,169)
Rear axle	ATM	kg (lb.)	2,100 (4,628)	2,028 (4,470)	2,031 (4,480)	2,046 (4,513)
Unsprung weight	Front	kg (lb.)	690 (1,520)	690 (1,520)	690 (1,520)	690 (1,520)
	Rear	kg (lb.)	1,225 (2,700)	1,225 (2,700)	1,225 (2,700)	1,225 (2,700)
Center of gravity height from the ground		mm (in.)	795 (31.3)	795 (31.3)	795 (31.3)	795 (31.3)

Model			NV8JPSA	NV8JRSA	NV8JTSA	NV8JVSA
<b>CAPACITY</b>						
GVWR	Manual T/M	kg (lb.)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)
	Auto T/M	kg (lb.)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)
GAWR	Front	kg (lb.)	5,980 (13,200)	5,980 (13,200)	5,980 (13,200)	5,980 (13,200)
	Rear	kg (lb.)	10,430 (23,000)	10,430 (23,000)	10,430 (23,000)	10,430 (23,000)
<b>DIMENSIONS</b> (On standard specifications)						
Wheelbase		mm (in.)	5,512 (217.0)	5,969 (235.0)	6,426 (253.0)	6,883 (271.0)
Overall length		mm (in.)	9,007 (354.6)	9,464 (372.6)	9,921 (390.6)	9,921 (390.6)
Overall width		mm (in.)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)
Overall height		mm (in.)	2,725 (107.3)	2,725 (107.3)	2,725 (107.3)	2,725 (107.3)
BBC		mm (in.)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)
Cab to axle		mm (in.)	3,800 (149.6)	4,257 (167.6)	4,714 (185.6)	5,171 (203.6)
Rear overhang		mm (in.)	2,464 (97.0)	2,464 (97.0)	2,464 (97.0)	2,007 (79.0)
Frame height at	Front axle	mm (in.)	950 (37.4)	950 (37.4)	950 (37.4)	950 (37.4)
	Rear axle	mm (in.)	1,030 (40.6)	1,030 (40.6)	1,030 (40.6)	1,030 (40.6)
Road clearance (at diff. case)		mm (in.)	255 (10.0)	255 (10.0)	255 (10.0)	255 (10.0)
Tread	Front	mm (in.)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)
	Rear	mm (in.)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)
Turning radius Tire		mm (in.)	8,890 (350.0)	9,570 (376.8)	10,240 (403.1)	10,910 (429.5)
Turning radius Swept		mm (in.)	9,410 (370.5)	10,090 (397.2)	10,760 (423.6)	11,430 (450.0)
<b>CHASSIS WEIGHTS</b> (on std. spec., without spare tire & std. tool set)						
<b>MANUAL T/M</b>						
Total weight	MT	kg (lb.)	5,265 (11,627)	5,290 (11,682)	5,310 (11,727)	5,345 (11,802)
Front axle	MT	kg (lb.)	3,199 (7,059)	3,236 (7,145)	3,297 (7,278)	3,307 (7,299)
Rear axle	MT	kg (lb.)	2,066 (4,568)	2,054 (4,537)	2,013 (4,449)	2,038 (4,503)
Unsprung weight	Front	kg (lb.)	690 (1,520)	690 (1,520)	690 (1,520)	690 (1,520)
	Rear	kg (lb.)	1,225 (2,700)	1,225 (2,700)	1,225 (2,700)	1,225 (2,700)
<b>AUTO T/M</b>						
Total weight	ATM	kg (lb.)	5,340 (11,772)	5,365 (11,827)	5,385 (11,872)	5,420 (11,947)
Front axle	ATM	kg (lb.)	3,259 (7,185)	3,296 (7,266)	3,357 (7,399)	3,367 (7,420)
Rear axle	ATM	kg (lb.)	2,081 (4,587)	2,069 (4,561)	2,028 (4,473)	2,053 (4,527)
Unsprung weight	Front	kg (lb.)	690 (1,520)	690 (1,520)	690 (1,520)	690 (1,520)
	Rear	kg (lb.)	1,225 (2,700)	1,225 (2,700)	1,225 (2,700)	1,225 (2,700)
Center of gravity height from the ground		mm (in.)	795 (31.3)	795 (31.3)	795 (31.3)	795 (31.3)

## NV8J

Fr. Axl : MFS14 Fr. Spg : 14,000 lbs

Rr. Axl : RS23 Rr. Spg : 31,000 lbs

Model			NV8JGSA	NV8JJSA	NV8JLSA	NV8JMSA
<b>CAPACITY</b>						
GVWR	Manual T/M	kg (lb.)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)
	Auto T/M	kg (lb.)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)
GAWR	Front	kg (lb.)	5,980 (13,200)	5,980 (13,200)	5,980 (13,200)	5,980 (13,200)
	Rear	kg (lb.)	10,430 (23,000)	10,430 (23,000)	10,430 (23,000)	10,430 (23,000)
<b>DIMENSIONS</b> (On standard specifications)						
Wheelbase		mm (in.)	3,861 (152.0)	4,445 (175.0)	4,750 (187.0)	5,207 (205.0)
Overall length		mm (in.)	6,162 (242.6)	7,076 (278.6)	7,686 (302.6)	8,143 (320.6)
Overall width		mm (in.)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)
Overall height		mm (in.)	2,725 (107.3)	2,725 (107.3)	2,725 (107.3)	2,725 (107.3)
BBC		mm (in.)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)
Cab to axle		mm (in.)	2,149 (84.6)	2,733 (107.6)	3,038 (119.6)	3,495 (137.6)
Rear overhang		mm (in.)	1,270 (50.0)	1,600 (63.0)	1,905 (75.0)	1,905 (75.0)
Frame height at	Front axle	mm (in.)	950 (37.4)	950 (37.4)	950 (37.4)	950 (37.4)
	Rear axle	mm (in.)	1,030 (40.6)	1,030 (40.6)	1,030 (40.6)	1,030 (40.6)
Road clearance (at diff. case)		mm (in.)	255 (10.0)	255 (10.0)	255 (10.0)	255 (10.0)
Tread	Front	mm (in.)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)
	Rear	mm (in.)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)
Turning radius Tire		mm (in.)	6,470 (254.7)	7,330 (288.6)	7,770 (305.9)	8,440 (332.3)
Turning radius Swept		mm (in.)	6,990 (275.2)	7,850 (309.1)	8,290 (326.4)	8,970 (353.1)
<b>CHASSIS WEIGHTS</b> (on std. spec., without spare tire & std. tool set)						
<b>MANUAL T/M</b>						
Total weight	MT	kg (lb.)	5,099 (11,242)	5,144 (11,342)	5,179 (11,417)	5,259 (11,592)
Front axle	MT	kg (lb.)	2,994 (6,598)	3,111 (6,861)	3,138 (6,916)	3,203 (7,063)
Rear axle	MT	kg (lb.)	2,105 (4,639)	2,033 (4,481)	2,041 (4,501)	2,056 (4,534)
Unsprung weight	Front	kg (lb.)	690 (1,520)	690 (1,520)	690 (1,520)	690 (1,520)
	Rear	kg (lb.)	1,225 (2,700)	1,225 (2,700)	1,225 (2,700)	1,225 (2,700)
<b>AUTO T/M</b>						
Total weight	ATM	kg (lb.)	5,174 (11,407)	5,219 (11,507)	5,259 (11,592)	5,334 (11,757)
Front axle	ATM	kg (lb.)	3,044 (6,713)	3,161 (6,971)	3,198 (7,051)	3,258 (7,183)
Rear axle	ATM	kg (lb.)	2,130 (4,694)	2,058 (4,536)	2,061 (4,546)	2,076 (4,579)
Unsprung weight	Front	kg (lb.)	690 (1,520)	690 (1,520)	690 (1,520)	690 (1,520)
	Rear	kg (lb.)	1,225 (2,700)	1,225 (2,700)	1,225 (2,700)	1,225 (2,700)
Center of gravity height from the ground		mm (in.)	795 (31.3)	795 (31.3)	795 (31.3)	795 (31.3)

Model			NV8JPSA	NV8JRSA	NV8JTSA	NV8JVSA
<b>CAPACITY</b>						
GVWR	Manual T/M	kg (lb.)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)
	Auto T/M	kg (lb.)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)
GAWR	Front	kg (lb.)	5,980 (13,200)	5,980 (13,200)	5,980 (13,200)	5,980 (13,200)
	Rear	kg (lb.)	10,430 (23,000)	10,430 (23,000)	10,430 (23,000)	10,430 (23,000)
<b>DIMENSIONS</b> (On standard specifications)						
Wheelbase		mm (in.)	5,512 (217.0)	5,969 (235.0)	6,426 (253.0)	6,883 (271.0)
Overall length		mm (in.)	9,007 (354.6)	9,464 (372.6)	9,921 (390.6)	9,921 (390.6)
Overall width		mm (in.)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)
Overall height		mm (in.)	2,725 (107.3)	2,725 (107.3)	2,725 (107.3)	2,725 (107.3)
BBC		mm (in.)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)
Cab to axle		mm (in.)	3,800 (149.6)	4,257 (167.6)	4,714 (185.6)	5,171 (203.6)
Rear overhang		mm (in.)	2,464 (97.0)	2,464 (97.0)	2,464 (97.0)	2,007 (79.0)
Frame height at	Front axle	mm (in.)	950 (37.4)	950 (37.4)	950 (37.4)	950 (37.4)
	Rear axle	mm (in.)	1,030 (40.6)	1,030 (40.6)	1,030 (40.6)	1,030 (40.6)
Road clearance (at diff. case)		mm (in.)	255 (10.0)	255 (10.0)	255 (10.0)	255 (10.0)
Tread	Front	mm (in.)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)
	Rear	mm (in.)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)
Turning radius Tire		mm (in.)	8,890 (350.0)	9,570 (376.8)	10,240 (403.1)	10,910 (429.5)
Turning radius Swept		mm (in.)	9,410 (370.5)	10,090 (397.2)	10,760 (423.6)	11,430 (450.0)
<b>CHASSIS WEIGHTS</b> (on std. spec., without spare tire & std. tool set)						
<b>MANUAL T/M</b>						
Total weight	MT	kg (lb.)	5,299 (11,682)	5,324 (11,737)	5,344 (11,782)	5,379 (11,857)
Front axle	MT	kg (lb.)	3,203 (7,059)	3,240 (7,145)	3,301 (7,278)	3,311 (7,299)
Rear axle	MT	kg (lb.)	2,096 (4,623)	2,084 (4,592)	2,043 (4,504)	2,068 (4,558)
Unsprung weight	Front	kg (lb.)	690 (1,520)	690 (1,520)	690 (1,520)	690 (1,520)
	Rear	kg (lb.)	1,225 (2,700)	1,225 (2,700)	1,225 (2,700)	1,225 (2,700)
<b>AUTO T/M</b>						
Total weight	ATM	kg (lb.)	5,374 (11,847)	5,399 (11,902)	5,419 (11,947)	5,454 (12,022)
Front axle	ATM	kg (lb.)	3,263 (7,194)	3,300 (7,275)	3,361 (7,408)	3,371 (7,434)
Rear axle	ATM	kg (lb.)	2,111 (4,653)	2,099 (4,627)	2,058 (4,539)	2,083 (4,593)
Unsprung weight	Front	kg (lb.)	690 (1,520)	690 (1,520)	690 (1,520)	690 (1,520)
	Rear	kg (lb.)	1,225 (2,700)	1,225 (2,700)	1,225 (2,700)	1,225 (2,700)
Center of gravity height from the ground		mm (in.)	795 (31.3)	795 (31.3)	795 (31.3)	795 (31.3)



**NV8J (Rr AIR SUS.)****Fr. Axl : MFS12 Fr. Spg : 12,000 lbs****Rr. Axl : RS21 Rr. Spg : 23,000 lbs**

Model			NV8JGSG	
CAPACITY				
GVWR	Manual T/M	kg (lb.)	14,950 (33,000)	
	Auto T/M	kg (lb.)	14,950 (33,000)	
GAWR	Front	kg (lb.)	5,440 (12,000)	
	Rear	kg (lb.)	9,530 (21,000)	
DIMENSIONS (On standard specifications)				
Wheelbase		mm (in.)	3,861 (152.0)	
Overall length		mm (in.)	6,162 (242.6)	
Overall width		mm (in.)	2,450 (96.5)	
Overall height		mm (in.)	2,710 (106.7)	
BBC		mm (in.)	2,743 (108.0)	
Cab to axle		mm (in.)	2,149 (84.6)	
Rear overhang		mm (in.)	1,270 (50.0)	
Frame height at	Front axle	mm (in.)	940 (37.0)	
	Rear axle	mm (in.)	990 (39.0)	
Road clearance (at diff. case)		mm (in.)	285 (11.2)	
Tread	Front	mm (in.)	2,015 (79.3)	
	Rear	mm (in.)	1,835 (72.2)	
Turning radius Tire		mm (in.)	6,400 (252.0)	
Turning radius Swept		mm (in.)	6,920 (272.4)	
CHASSIS WEIGHTS (on std. spec., without spare tire & std. tool set)				
MANUAL T/M				
Total weight	MT	kg (lb.)	4,920 (10,847)	
Front axle	MT	kg (lb.)	2,954 (6,513)	
Rear axle	MT	kg (lb.)	1,966 (4,334)	
Unsprung weight	Front	kg (lb.)	645 (1,420)	
	Rear	kg (lb.)	1,125 (2,480)	
AUTO T/M				
Total weight	ATM	kg (lb.)	4,869 (10,734)	
Front axle	ATM	kg (lb.)	2,912 (6,420)	
Rear axle	ATM	kg (lb.)	1,957 (4,314)	
Unsprung weight	Front	kg (lb.)	645 (1,420)	
	Rear	kg (lb.)	1,125 (2,480)	
Center of gravity height from the ground		mm (in.)	780 (30.7)	



## NV8J (Rr AIR SUS.)

Fr. Axl : MFS12 Fr. Spg : 12,000 lbs

Rr. Axl : RS21 Rr. Spg : 21,000 lbs

Model			NV8JJSG	NV8JLSG	NV8JMSG
<b>CAPACITY</b>					
GVWR	Manual T/M	kg (lb.)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)
	Auto T/M	kg (lb.)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)
GAWR	Front	kg (lb.)	5,440 (12,000)	5,440 (12,000)	5,440 (12,000)
	Rear	kg (lb.)	9,530 (21,000)	9,530 (21,000)	9,530 (21,000)
<b>DIMENSIONS</b> (On standard specifications)					
Wheelbase		mm (in.)	4,445 (175.0)	4,750 (187.0)	5,207 (205.0)
Overall length		mm (in.)	7,076 (278.6)	7,686 (302.6)	8,143 (320.6)
Overall width		mm (in.)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)
Overall height		mm (in.)	2,710 (106.7)	2,710 (106.7)	2,710 (106.7)
BBC		mm (in.)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)
Cab to axle		mm (in.)	2,733 (107.6)	3,038 (119.6)	3,495 (137.6)
Rear overhang		mm (in.)	1,600 (63.0)	1,905 (75.0)	1,905 (75.0)
Frame height at	Front axle	mm (in.)	940 (37.0)	940 (37.0)	940 (37.0)
	Rear axle	mm (in.)	990 (39.0)	990 (39.0)	990 (39.0)
Road clearance (at diff. case)		mm (in.)	285 (11.2)	285 (11.2)	285 (11.2)
Tread	Front	mm (in.)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)
	Rear	mm (in.)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)
Turning radius Tire		mm (in.)	7,240 (285.0)	7,690 (302.8)	8,350 (328.7)
Turning radius Swept		mm (in.)	7,760 (305.5)	8,210 (323.2)	8,870 (349.2)
<b>CHASSIS WEIGHTS</b> (on std. spec., without spare tire & std. tool set)					
<b>MANUAL T/M</b>					
Total weight	MT	kg (lb.)	4,955 (10,922)	4,990 (11,002)	5,070 (11,177)
Front axle	MT	kg (lb.)	3,061 (6,746)	3,088 (6,811)	3,153 (6,953)
Rear axle	MT	kg (lb.)	1,894 (4,176)	1,902 (4,191)	1,917 (4,224)
Unsprung weight	Front	kg (lb.)	645 (1,420)	645 (1,420)	645 (1,420)
	Rear	kg (lb.)	1,125 (2,480)	1,125 (2,480)	1,125 (2,480)
<b>AUTO T/M</b>					
Total weight	ATM	kg (lb.)	4,904 (10,809)	4,939 (10,889)	5,019 (11,064)
Front axle	ATM	kg (lb.)	3,019 (6,652)	3,044 (6,713)	3,112 (6,860)
Rear axle	ATM	kg (lb.)	1,885 (4,157)	1,895 (4,176)	1,907 (4,204)
Unsprung weight	Front	kg (lb.)	645 (1,420)	645 (1,420)	645 (1,420)
	Rear	kg (lb.)	1,125 (2,480)	1,125 (2,480)	1,125 (2,480)
Center of gravity height from the ground		mm (in.)	780 (30.7)	780 (30.7)	780 (30.7)

Model			NV8JPSG	NV8JRSG	NV8JTSG	NV8JVSG
<b>CAPACITY</b>						
GVWR	Manual T/M	kg (lb.)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)
	Auto T/M	kg (lb.)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)
GAWR	Front	kg (lb.)	5,440 (12,000)	5,440 (12,000)	5,440 (12,000)	5,440 (12,000)
	Rear	kg (lb.)	9,530 (21,000)	9,530 (21,000)	9,530 (21,000)	9,530 (21,000)
<b>DIMENSIONS</b> (On standard specifications)						
Wheelbase		mm (in.)	5,512 (217.0)	5,969 (235.0)	6,426 (253.0)	6,883 (271.0)
Overall length		mm (in.)	9,007 (354.6)	9,464 (372.6)	9,921 (390.6)	9,921 (390.6)
Overall width		mm (in.)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)
Overall height		mm (in.)	2,710 (106.7)	2,710 (106.7)	2,710 (106.7)	2,710 (106.7)
BBC		mm (in.)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)
Cab to axle		mm (in.)	3,800 (149.6)	4,257 (167.6)	4,714 (185.6)	5,171 (203.6)
Rear overhang		mm (in.)	2,464 (97.0)	2,464 (97.0)	2,464 (97.0)	2,007 (79.0)
Frame height at	Front axle	mm (in.)	940 (37.0)	940 (37.0)	940 (37.0)	940 (37.0)
	Rear axle	mm (in.)	990 (39.0)	990 (39.0)	990 (39.0)	990 (39.0)
Road clearance (at diff. case)		mm (in.)	285 (11.2)	285 (11.2)	285 (11.2)	285 (11.2)
Tread	Front	mm (in.)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)
	Rear	mm (in.)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)
Turning radius Tire		mm (in.)	8,790 (346.1)	9,460 (372.4)	10,120 (398.4)	10,790 (424.8)
Turning radius Swept		mm (in.)	9,310 (366.5)	9,980 (392.9)	10,640 (418.9)	11,310 (445.3)
<b>CHASSIS WEIGHTS</b> (on std. spec., without spare tire & std. tool set)						
<b>MANUAL T/M</b>						
Total weight	MT	kg (lb.)	5,110 (11,267)	5,135 (11,322)	5,155 (11,367)	5,190 (11,442)
Front axle	MT	kg (lb.)	3,158 (6,964)	3,190 (7,035)	3,251 (7,168)	3,266 (7,199)
Rear axle	MT	kg (lb.)	1,952 (4,303)	1,945 (4,287)	1,904 (4,199)	1,924 (4,243)
Unsprung weight	Front	kg (lb.)	645 (1,420)	645 (1,420)	645 (1,420)	645 (1,420)
	Rear	kg (lb.)	1,125 (2,480)	1,125 (2,480)	1,125 (2,480)	1,125 (2,480)
<b>AUTO T/M</b>						
Total weight	ATM	kg (lb.)	5,059 (11,154)	5,084 (11,209)	5,104 (11,254)	5,139 (11,329)
Front axle	ATM	kg (lb.)	3,111 (6,859)	3,146 (6,935)	3,205 (7,069)	3,214 (7,083)
Rear axle	ATM	kg (lb.)	1,948 (4,295)	1,938 (4,274)	1,899 (4,185)	1,925 (4,246)
Unsprung weight	Front	kg (lb.)	645 (1,420)	645 (1,420)	645 (1,420)	645 (1,420)
	Rear	kg (lb.)	1,125 (2,480)	1,125 (2,480)	1,125 (2,480)	1,125 (2,480)
Center of gravity height from the ground		mm (in.)	780 (30.7)	780 (30.7)	780 (30.7)	780 (30.7)

**NV8J (Rr AIR SUS.)****Fr. Axl : MFS10 Fr. Spg : 12,000 lbs****Rr. Axl : RS21 Rr. Spg : 23,000 lbs**

Model			NV8JGSG	
CAPACITY				
GVWR	Manual T/M	kg (lb.)	11,770 (25,950)	
	Auto T/M	kg (lb.)	11,770 (25,950)	
GAWR	Front	kg (lb.)	4,540 (10,000)	
	Rear	kg (lb.)	9,530 (21,000)	
DIMENSIONS (On standard specifications)				
Wheelbase		mm (in.)	3,861 (152.0)	
Overall length		mm (in.)	6,162 (242.6)	
Overall width		mm (in.)	2,450 (96.5)	
Overall height		mm (in.)	2,710 (106.7)	
BBC		mm (in.)	2,743 (108.0)	
Cab to axle		mm (in.)	2,149 (84.6)	
Rear overhang		mm (in.)	1,270 (50.0)	
Frame height at	Front axle	mm (in.)	940 (37.0)	
	Rear axle	mm (in.)	990 (39.0)	
Road clearance (at diff. case)		mm (in.)	285 (11.2)	
Tread	Front	mm (in.)	2,015 (79.3)	
	Rear	mm (in.)	1,835 (72.2)	
Turning radius Tire		mm (in.)	6,400 (252.0)	
Turning radius Swept		mm (in.)	6,920 (272.4)	
CHASSIS WEIGHTS (on std. spec., without spare tire & std. tool set)				
MANUAL T/M				
Total weight	MT	kg (lb.)	4,920 (10,847)	
Front axle	MT	kg (lb.)	2,954 (6,513)	
Rear axle	MT	kg (lb.)	1,966 (4,334)	
Unsprung weight	Front	kg (lb.)	645 (1,420)	
	Rear	kg (lb.)	1,125 (2,480)	
AUTO T/M				
Total weight	ATM	kg (lb.)	4,869 (10,734)	
Front axle	ATM	kg (lb.)	2,912 (6,420)	
Rear axle	ATM	kg (lb.)	1,957 (4,314)	
Unsprung weight	Front	kg (lb.)	645 (1,420)	
	Rear	kg (lb.)	1,125 (2,480)	
Center of gravity height from the ground		mm (in.)	780 (30.7)	

## NV8J (Rr AIR SUS.)

Fr. Axl : MFS10 Fr. Spg : 12,000 lbs

Rr. Axl : RS21 Rr. Spg : 21,000 lbs

Model			NV8JJSG	NV8JLSG	NV8JMSG
<b>CAPACITY</b>					
GVWR	Manual T/M	kg (lb.)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)
	Auto T/M	kg (lb.)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)
GAWR	Front	kg (lb.)	4,540 (10,000)	4,540 (10,000)	4,540 (10,000)
	Rear	kg (lb.)	9,530 (21,000)	9,530 (21,000)	9,530 (21,000)
<b>DIMENSIONS</b> (On standard specifications)					
Wheelbase		mm (in.)	4,445 (175.0)	4,750 (187.0)	5,207 (205.0)
Overall length		mm (in.)	7,076 (278.6)	7,686 (302.6)	8,143 (320.6)
Overall width		mm (in.)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)
Overall height		mm (in.)	2,710 (106.7)	2,710 (106.7)	2,710 (106.7)
BBC		mm (in.)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)
Cab to axle		mm (in.)	2,733 (107.6)	3,038 (119.6)	3,495 (137.6)
Rear overhang		mm (in.)	1,600 (63.0)	1,905 (75.0)	1,905 (75.0)
Frame height at	Front axle	mm (in.)	940 (37.0)	940 (37.0)	940 (37.0)
	Rear axle	mm (in.)	990 (39.0)	990 (39.0)	990 (39.0)
Road clearance (at diff. case)		mm (in.)	285 (11.2)	285 (11.2)	285 (11.2)
Tread	Front	mm (in.)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)
	Rear	mm (in.)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)
Turning radius Tire		mm (in.)	7,240 (285.0)	7,690 (302.8)	8,350 (328.7)
Turning radius Swept		mm (in.)	7,760 (305.5)	8,210 (323.2)	8,870 (349.2)
<b>CHASSIS WEIGHTS</b> (on std. spec., without spare tire & std. tool set)					
<b>MANUAL T/M</b>					
Total weight	MT	kg (lb.)	4,955 (10,922)	4,990 (11,002)	5,070 (11,177)
Front axle	MT	kg (lb.)	3,061 (6,746)	3,088 (6,811)	3,153 (6,953)
Rear axle	MT	kg (lb.)	1,894 (4,176)	1,902 (4,191)	1,917 (4,224)
Unsprung weight	Front	kg (lb.)	645 (1,420)	645 (1,420)	645 (1,420)
	Rear	kg (lb.)	1,125 (2,480)	1,125 (2,480)	1,125 (2,480)
<b>AUTO T/M</b>					
Total weight	ATM	kg (lb.)	4,904 (10,809)	4,939 (10,889)	5,019 (11,064)
Front axle	ATM	kg (lb.)	3,019 (6,652)	3,044 (6,713)	3,112 (6,860)
Rear axle	ATM	kg (lb.)	1,885 (4,157)	1,895 (4,176)	1,907 (4,204)
Unsprung weight	Front	kg (lb.)	645 (1,420)	645 (1,420)	645 (1,420)
	Rear	kg (lb.)	1,125 (2,480)	1,125 (2,480)	1,125 (2,480)
Center of gravity height from the ground		mm (in.)	780 (30.7)	780 (30.7)	780 (30.7)

Model			NV8JPSG	NV8JRSG	NV8JTSG	NV8JVSG
<b>CAPACITY</b>						
GVWR	Manual T/M	kg (lb.)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)
	Auto T/M	kg (lb.)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)	11,770 (25,950)
GAWR	Front	kg (lb.)	4,540 (10,000)	4,540 (10,000)	4,540 (10,000)	4,540 (10,000)
	Rear	kg (lb.)	9,530 (21,000)	9,530 (21,000)	9,530 (21,000)	9,530 (21,000)
<b>DIMENSIONS</b> (On standard specifications)						
Wheelbase		mm (in.)	5,512 (217.0)	5,969 (235.0)	6,426 (253.0)	6,883 (271.0)
Overall length		mm (in.)	9,007 (354.6)	9,464 (372.6)	9,921 (390.6)	9,921 (390.6)
Overall width		mm (in.)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)
Overall height		mm (in.)	2,710 (106.7)	2,710 (106.7)	2,710 (106.7)	2,710 (106.7)
BBC		mm (in.)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)
Cab to axle		mm (in.)	3,800 (149.6)	4,257 (167.6)	4,714 (185.6)	5,171 (203.6)
Rear overhang		mm (in.)	2,464 (97.0)	2,464 (97.0)	2,464 (97.0)	2,007 (79.0)
Frame height at	Front axle	mm (in.)	940 (37.0)	940 (37.0)	940 (37.0)	940 (37.0)
	Rear axle	mm (in.)	990 (39.0)	990 (39.0)	990 (39.0)	990 (39.0)
Road clearance (at diff. case)		mm (in.)	285 (11.2)	285 (11.2)	285 (11.2)	285 (11.2)
Tread	Front	mm (in.)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)
	Rear	mm (in.)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)
Turning radius Tire		mm (in.)	8,790 (346.1)	9,460 (372.4)	10,120 (398.4)	10,790 (424.8)
Turning radius Swept		mm (in.)	9,310 (366.5)	9,980 (392.9)	10,640 (418.9)	11,310 (445.3)
<b>CHASSIS WEIGHTS</b> (on std. spec., without spare tire & std. tool set)						
<b>MANUAL T/M</b>						
Total weight	MT	kg (lb.)	5,110 (11,267)	5,135 (11,322)	5,155 (11,367)	5,190 (11,442)
Front axle	MT	kg (lb.)	3,158 (6,964)	3,190 (7,035)	3,251 (7,168)	3,266 (7,199)
Rear axle	MT	kg (lb.)	1,952 (4,303)	1,945 (4,287)	1,904 (4,199)	1,924 (4,243)
Unsprung weight	Front	kg (lb.)	645 (1,420)	645 (1,420)	645 (1,420)	645 (1,420)
	Rear	kg (lb.)	1,125 (2,480)	1,125 (2,480)	1,125 (2,480)	1,125 (2,480)
<b>AUTO T/M</b>						
Total weight	ATM	kg (lb.)	5,059 (11,154)	5,084 (11,209)	5,104 (11,254)	5,139 (11,329)
Front axle	ATM	kg (lb.)	3,111 (6,859)	3,146 (6,935)	3,205 (7,069)	3,214 (7,083)
Rear axle	ATM	kg (lb.)	1,948 (4,295)	1,938 (4,274)	1,899 (4,185)	1,925 (4,246)
Unsprung weight	Front	kg (lb.)	645 (1,420)	645 (1,420)	645 (1,420)	645 (1,420)
	Rear	kg (lb.)	1,125 (2,480)	1,125 (2,480)	1,125 (2,480)	1,125 (2,480)
Center of gravity height from the ground		mm (in.)	780 (30.7)	780 (30.7)	780 (30.7)	780 (30.7)

## NV8J (Rr AIR SUS.)

Fr. Axl : MFS10 Fr. Spg : 12,000 lbs

Rr. Axl : RS23 Rr. Spg : 23,000 lbs

Model			NV8JGSG	NV8JJSG	NV8JLSG	NV8JMSG
<b>CAPACITY</b>						
GVWR	Manual T/M	kg (lb.)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)
	Auto T/M	kg (lb.)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)
GAWR	Front	kg (lb.)	4,540 (10,000)	4,540 (10,000)	4,540 (10,000)	4,540 (10,000)
	Rear	kg (lb.)	10,430 (23,000)	10,430 (23,000)	10,430 (23,000)	10,430 (23,000)
<b>DIMENSIONS</b> (On standard specifications)						
Wheelbase		mm (in.)	3,861 (152.0)	4,445 (175.0)	4,750 (187.0)	5,207 (205.0)
Overall length		mm (in.)	6,162 (242.6)	7,076 (278.6)	7,686 (302.6)	8,143 (320.6)
Overall width		mm (in.)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)
Overall height		mm (in.)	2,710 (106.7)	2,710 (106.7)	2,710 (106.7)	2,710 (106.7)
BBC		mm (in.)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)
Cab to axle		mm (in.)	2,149 (84.6)	2,733 (107.6)	3,038 (119.6)	3,495 (137.6)
Rear overhang		mm (in.)	1,270 (50.0)	1,600 (63.0)	1,905 (75.0)	1,905 (75.0)
Frame height at	Front axle	mm (in.)	940 (37.0)	940 (37.0)	940 (37.0)	940 (37.0)
	Rear axle	mm (in.)	990 (39.0)	990 (39.0)	990 (39.0)	990 (39.0)
Road clearance (at diff. case)		mm (in.)	255 (10.0)	255 (10.0)	255 (10.0)	255 (10.0)
Tread	Front	mm (in.)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)
	Rear	mm (in.)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)
Turning radius Tire		mm (in.)	6,400 (252.0)	7,240 (285.0)	7,690 (302.8)	8,350 (328.7)
Turning radius Swept		mm (in.)	6,920 (272.4)	7,760 (305.5)	8,210 (323.2)	8,870 (349.2)
<b>CHASSIS WEIGHTS</b> (on std. spec., without spare tire & std. tool set)						
<b>MANUAL T/M</b>						
Total weight	MT	kg (lb.)	5,005 (11,032)	5,040 (11,112)	5,075 (11,187)	5,155 (11,367)
Front axle	MT	kg (lb.)	2,950 (6,499)	3,057 (6,742)	3,089 (6,807)	3,149 (6,944)
Rear axle	MT	kg (lb.)	2,055 (4,533)	1,983 (4,370)	1,986 (4,380)	2,006 (4,423)
Unsprung weight	Front	kg (lb.)	645 (1,420)	645 (1,420)	645 (1,420)	645 (1,420)
	Rear	kg (lb.)	1,210 (2,670)	1,210 (2,670)	1,210 (2,670)	1,210 (2,670)
<b>AUTO T/M</b>						
Total weight	ATM	kg (lb.)	5,080 (11,197)	5,115 (11,277)	5,150 (11,352)	5,230 (11,532)
Front axle	ATM	kg (lb.)	3,000 (6,609)	3,112 (6,862)	3,139 (6,917)	3,209 (7,074)
Rear axle	ATM	kg (lb.)	2,080 (4,588)	2,003 (4,415)	2,011 (4,435)	2,021 (4,458)
Unsprung weight	Front	kg (lb.)	645 (1,420)	645 (1,420)	645 (1,420)	645 (1,420)
	Rear	kg (lb.)	1,210 (2,670)	1,210 (2,670)	1,210 (2,670)	1,210 (2,670)
Center of gravity height from the ground		mm (in.)	780 (30.7)	780 (30.7)	780 (30.7)	780 (30.7)

Model			NV8JPSG	NV8JRSG	NV8JTSG	NV8JVSG
<b>CAPACITY</b>						
GVWR	Manual T/M	kg (lb.)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)
	Auto T/M	kg (lb.)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)
GAWR	Front	kg (lb.)	4,540 (10,000)	4,540 (10,000)	4,540 (10,000)	4,540 (10,000)
	Rear	kg (lb.)	10,430 (23,000)	10,430 (23,000)	10,430 (23,000)	10,430 (23,000)
<b>DIMENSIONS</b> (On standard specifications)						
Wheelbase		mm (in.)	5,512 (217.0)	5,969 (235.0)	6,426 (253.0)	6,883 (271.0)
Overall length		mm (in.)	9,007 (354.6)	9,464 (372.6)	9,921 (390.6)	9,921 (390.6)
Overall width		mm (in.)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)
Overall height		mm (in.)	2,710 (106.7)	2,710 (106.7)	2,710 (106.7)	2,710 (106.7)
BBC		mm (in.)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)
Cab to axle		mm (in.)	3,800 (149.6)	4,257 (167.6)	4,714 (185.6)	5,171 (203.6)
Rear overhang		mm (in.)	2,464 (97.0)	2,464 (97.0)	2,464 (97.0)	2,007 (79.0)
Frame height at	Front axle	mm (in.)	940 (37.0)	940 (37.0)	940 (37.0)	940 (37.0)
	Rear axle	mm (in.)	990 (39.0)	990 (39.0)	990 (39.0)	990 (39.0)
Road clearance (at diff. case)		mm (in.)	255 (10.0)	255 (10.0)	255 (10.0)	255 (10.0)
Tread	Front	mm (in.)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)
	Rear	mm (in.)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)
Turning radius Tire		mm (in.)	8,790 (346.1)	9,460 (372.4)	10,120 (398.4)	10,790 (424.8)
Turning radius Swept		mm (in.)	9,310 (366.5)	9,980 (392.9)	10,640 (418.9)	11,310 (445.3)
<b>CHASSIS WEIGHTS</b> (on std. spec., without spare tire & std. tool set)						
<b>MANUAL T/M</b>						
Total weight	MT	kg (lb.)	5,195 (11,452)	5,220 (11,507)	5,240 (11,552)	5,275 (11,627)
Front axle	MT	kg (lb.)	3,154 (6,950)	3,186 (7,021)	3,247 (7,159)	3,262 (7,190)
Rear axle	MT	kg (lb.)	2,041 (4,502)	2,034 (4,486)	1,993 (4,393)	2,013 (4,437)
Unsprung weight	Front	kg (lb.)	645 (1,420)	645 (1,420)	645 (1,420)	645 (1,420)
	Rear	kg (lb.)	1,210 (2,670)	1,210 (2,670)	1,210 (2,670)	1,210 (2,670)
<b>AUTO T/M</b>						
Total weight	ATM	kg (lb.)	5,270 (11,617)	5,295 (11,672)	5,315 (11,717)	5,350 (11,797)
Front axle	ATM	kg (lb.)	3,214 (7,085)	3,246 (7,156)	3,307 (7,289)	3,322 (7,325)
Rear axle	ATM	kg (lb.)	2,056 (4,532)	2,049 (4,516)	2,008 (4,428)	2,028 (4,472)
Unsprung weight	Front	kg (lb.)	645 (1,420)	645 (1,420)	645 (1,420)	645 (1,420)
	Rear	kg (lb.)	1,210 (2,670)	1,210 (2,670)	1,210 (2,670)	1,210 (2,670)
Center of gravity height from the ground		mm (in.)	780 (30.7)	780 (30.7)	780 (30.7)	780 (30.7)

## NV8J (Rr AIR SUS.)

Fr. Axl : MFS12 Fr. Spg : 12,000 lbs

Rr. Axl : RS23 Rr. Spg : 23,000 lbs

Model			NV8JGSG	NV8JJSG	NV8JLSG	NV8JMSG
<b>CAPACITY</b>						
GVWR	Manual T/M	kg (lb.)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)
	Auto T/M	kg (lb.)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)
GAWR	Front	kg (lb.)	5,440 (12,000)	5,440 (12,000)	5,440 (12,000)	5,440 (12,000)
	Rear	kg (lb.)	10,430 (23,000)	10,430 (23,000)	10,430 (23,000)	10,430 (23,000)
<b>DIMENSIONS</b> (On standard specifications)						
Wheelbase		mm (in.)	3,861 (152.0)	4,445 (175.0)	4,750 (187.0)	5,207 (205.0)
Overall length		mm (in.)	6,162 (242.6)	7,076 (278.6)	7,686 (302.6)	8,143 (320.6)
Overall width		mm (in.)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)
Overall height		mm (in.)	2,710 (106.7)	2,710 (106.7)	2,710 (106.7)	2,710 (106.7)
BBC		mm (in.)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)
Cab to axle		mm (in.)	2,149 (84.6)	2,733 (107.6)	3,038 (119.6)	3,495 (137.6)
Rear overhang		mm (in.)	1,270 (50.0)	1,600 (63.0)	1,905 (75.0)	1,905 (75.0)
Frame height at	Front axle	mm (in.)	940 (37.0)	940 (37.0)	940 (37.0)	940 (37.0)
	Rear axle	mm (in.)	990 (39.0)	990 (39.0)	990 (39.0)	990 (39.0)
Road clearance (at diff. case)		mm (in.)	255 (10.0)	255 (10.0)	255 (10.0)	255 (10.0)
Tread	Front	mm (in.)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)
	Rear	mm (in.)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)
Turning radius Tire		mm (in.)	6,400 (252.0)	7,240 (285.0)	7,690 (302.8)	8,350 (328.7)
Turning radius Swept		mm (in.)	6,920 (272.4)	7,760 (305.5)	8,210 (323.2)	8,870 (349.2)
<b>CHASSIS WEIGHTS</b> (on std. spec., without spare tire & std. tool set)						
<b>MANUAL T/M</b>						
Total weight	MT	kg (lb.)	5,005 (11,032)	5,040 (11,112)	5,075 (11,187)	5,155 (11,367)
Front axle	MT	kg (lb.)	2,950 (6,499)	3,057 (6,742)	3,089 (6,807)	3,149 (6,944)
Rear axle	MT	kg (lb.)	2,055 (4,533)	1,983 (4,370)	1,986 (4,380)	2,006 (4,423)
Unsprung weight	Front	kg (lb.)	645 (1,420)	645 (1,420)	645 (1,420)	645 (1,420)
	Rear	kg (lb.)	1,210 (2,670)	1,210 (2,670)	1,210 (2,670)	1,210 (2,670)
<b>AUTO T/M</b>						
Total weight	ATM	kg (lb.)	5,080 (11,197)	5,115 (11,277)	5,150 (11,352)	5,230 (11,532)
Front axle	ATM	kg (lb.)	3,000 (6,609)	3,112 (6,862)	3,139 (6,917)	3,209 (7,074)
Rear axle	ATM	kg (lb.)	2,080 (4,588)	2,003 (4,415)	2,011 (4,435)	2,021 (4,458)
Unsprung weight	Front	kg (lb.)	645 (1,420)	645 (1,420)	645 (1,420)	645 (1,420)
	Rear	kg (lb.)	1,210 (2,670)	1,210 (2,670)	1,210 (2,670)	1,210 (2,670)
Center of gravity height from the ground		mm (in.)	780 (30.7)	780 (30.7)	780 (30.7)	780 (30.7)



Model			NV8JPSG	NV8JRSG	NV8JTSG	NV8JVSG
<b>CAPACITY</b>						
GVWR	Manual T/M	kg (lb.)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)
	Auto T/M	kg (lb.)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)
GAWR	Front	kg (lb.)	5,440 (12,000)	5,440 (12,000)	5,440 (12,000)	5,440 (12,000)
	Rear	kg (lb.)	10,430 (23,000)	10,430 (23,000)	10,430 (23,000)	10,430 (23,000)
<b>DIMENSIONS</b> (On standard specifications)						
Wheelbase		mm (in.)	5,512 (217.0)	5,969 (235.0)	6,426 (253.0)	6,883 (271.0)
Overall length		mm (in.)	9,007 (354.6)	9,464 (372.6)	9,921 (390.6)	9,921 (390.6)
Overall width		mm (in.)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)
Overall height		mm (in.)	2,710 (106.7)	2,710 (106.7)	2,710 (106.7)	2,710 (106.7)
BBC		mm (in.)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)
Cab to axle		mm (in.)	3,800 (149.6)	4,257 (167.6)	4,714 (185.6)	5,171 (203.6)
Rear overhang		mm (in.)	2,464 (97.0)	2,464 (97.0)	2,464 (97.0)	2,007 (79.0)
Frame height at	Front axle	mm (in.)	940 (37.0)	940 (37.0)	940 (37.0)	940 (37.0)
	Rear axle	mm (in.)	990 (39.0)	990 (39.0)	990 (39.0)	990 (39.0)
Road clearance (at diff. case)		mm (in.)	255 (10.0)	255 (10.0)	255 (10.0)	255 (10.0)
Tread	Front	mm (in.)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)
	Rear	mm (in.)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)
Turning radius Tire		mm (in.)	8,790 (346.1)	9,460 (372.4)	10,120 (398.4)	10,790 (424.8)
Turning radius Swept		mm (in.)	9,310 (366.5)	9,980 (392.9)	10,640 (418.9)	11,310 (445.3)
<b>CHASSIS WEIGHTS</b> (on std. spec., without spare tire & std. tool set)						
<b>MANUAL T/M</b>						
Total weight	MT	kg (lb.)	5,195 (11,452)	5,220 (11,507)	5,240 (11,552)	5,275 (11,627)
Front axle	MT	kg (lb.)	3,154 (6,950)	3,186 (7,021)	3,247 (7,159)	3,262 (7,190)
Rear axle	MT	kg (lb.)	2,041 (4,502)	2,034 (4,486)	1,993 (4,393)	2,013 (4,437)
Unsprung weight	Front	kg (lb.)	645 (1,420)	645 (1,420)	645 (1,420)	645 (1,420)
	Rear	kg (lb.)	1,210 (2,670)	1,210 (2,670)	1,210 (2,670)	1,210 (2,670)
<b>AUTO T/M</b>						
Total weight	ATM	kg (lb.)	5,270 (11,617)	5,295 (11,672)	5,315 (11,717)	5,350 (11,797)
Front axle	ATM	kg (lb.)	3,214 (7,085)	3,246 (7,156)	3,307 (7,289)	3,322 (7,325)
Rear axle	ATM	kg (lb.)	2,056 (4,532)	2,049 (4,516)	2,008 (4,428)	2,028 (4,472)
Unsprung weight	Front	kg (lb.)	645 (1,420)	645 (1,420)	645 (1,420)	645 (1,420)
	Rear	kg (lb.)	1,210 (2,670)	1,210 (2,670)	1,210 (2,670)	1,210 (2,670)
Center of gravity height from the ground		mm (in.)	780 (30.7)	780 (30.7)	780 (30.7)	780 (30.7)

**NV8J (Rr AIR SUS.)****Fr. Axl : MFS14 Fr. Spg : 14,000 lbs****Rr. Axl : RS21 Rr. Spg : 23,000 lbs**

Model			NV8JGSG	
CAPACITY				
GVWR	Manual T/M	kg (lb.)	14,950 (33,000)	
	Auto T/M	kg (lb.)	14,950 (33,000)	
GAWR	Front	kg (lb.)	5,980 (13,200)	
	Rear	kg (lb.)	9,530 (21,000)	
DIMENSIONS (On standard specifications)				
Wheelbase		mm (in.)	3,861 (152.0)	
Overall length		mm (in.)	6,162 (242.6)	
Overall width		mm (in.)	2,450 (96.5)	
Overall height		mm (in.)	2,715 (106.9)	
BBC		mm (in.)	2,743 (108.0)	
Cab to axle		mm (in.)	2,149 (84.6)	
Rear overhang		mm (in.)	1,270 (50.0)	
Frame height at	Front axle	mm (in.)	950 (37.4)	
	Rear axle	mm (in.)	990 (39.0)	
Road clearance (at diff. case)		mm (in.)	285 (11.2)	
Tread	Front	mm (in.)	2,015 (79.3)	
	Rear	mm (in.)	1,835 (72.2)	
Turning radius Tire		mm (in.)	6,470 (254.7)	
Turning radius Swept		mm (in.)	6,990 (275.2)	
CHASSIS WEIGHTS (on std. spec., without spare tire & std. tool set)				
MANUAL T/M				
Total weight	MT	kg (lb.)	4,960 (10,937)	
Front axle	MT	kg (lb.)	2,994 (6,603)	
Rear axle	MT	kg (lb.)	1,966 (4,334)	
Unsprung weight	Front	kg (lb.)	690 (1,520)	
	Rear	kg (lb.)	1,125 (2,480)	
AUTO T/M				
Total weight	ATM	kg (lb.)	4,909 (10,824)	
Front axle	ATM	kg (lb.)	2,952 (6,510)	
Rear axle	ATM	kg (lb.)	1,957 (4,314)	
Unsprung weight	Front	kg (lb.)	690 (1,520)	
	Rear	kg (lb.)	1,125 (2,480)	
Center of gravity height from the ground		mm (in.)	790 (31.1)	

**NV8J (Rr AIR SUS.)****Fr. Axl : MFS14 Fr. Spg : 14,000 lbs****Rr. Axl : RS21 Rr. Spg : 21,000 lbs**

Model			NV8JJSG	NV8JLSG	NV8JMSG
<b>CAPACITY</b>					
GVWR	Manual T/M	kg (lb.)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)
	Auto T/M	kg (lb.)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)
GAWR	Front	kg (lb.)	5,980 (13,200)	5,980 (13,200)	5,980 (13,200)
	Rear	kg (lb.)	9,530 (21,000)	9,530 (21,000)	9,530 (21,000)
<b>DIMENSIONS</b> (On standard specifications)					
Wheelbase		mm (in.)	4,445 (175.0)	4,750 (187.0)	5,207 (205.0)
Overall length		mm (in.)	7,076 (278.6)	7,686 (302.6)	8,143 (320.6)
Overall width		mm (in.)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)
Overall height		mm (in.)	2,715 (106.9)	2,715 (106.9)	2,715 (106.9)
BBC		mm (in.)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)
Cab to axle		mm (in.)	2,733 (107.6)	3,038 (119.6)	3,495 (137.6)
Rear overhang		mm (in.)	1,600 (63.0)	1,905 (75.0)	1,905 (75.0)
Frame height at	Front axle	mm (in.)	950 (37.4)	950 (37.4)	950 (37.4)
	Rear axle	mm (in.)	990 (39.0)	990 (39.0)	990 (39.0)
Road clearance (at diff. case)		mm (in.)	285 (11.2)	285 (11.2)	285 (11.2)
Tread	Front	mm (in.)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)
	Rear	mm (in.)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)
Turning radius Tire		mm (in.)	7,330 (288.6)	7,770 (305.9)	8,440 (332.3)
Turning radius Swept		mm (in.)	7,850 (309.1)	8,290 (326.4)	8,970 (353.1)
<b>CHASSIS WEIGHTS</b> (on std. spec., without spare tire & std. tool set)					
<b>MANUAL T/M</b>					
Total weight	MT	kg (lb.)	5,000 (11,022)	5,035 (11,102)	5,115 (11,277)
Front axle	MT	kg (lb.)	3,106 (6,846)	3,133 (6,911)	3,198 (7,053)
Rear axle	MT	kg (lb.)	1,894 (4,176)	1,902 (4,191)	1,917 (4,224)
Unsprung weight	Front	kg (lb.)	690 (1,520)	690 (1,520)	690 (1,520)
	Rear	kg (lb.)	1,125 (2,480)	1,125 (2,480)	1,125 (2,480)
<b>AUTO T/M</b>					
Total weight	ATM	kg (lb.)	4,949 (10,909)	4,984 (10,989)	5,064 (11,164)
Front axle	ATM	kg (lb.)	3,064 (6,752)	3,089 (6,813)	3,157 (6,960)
Rear axle	ATM	kg (lb.)	1,885 (4,157)	1,895 (4,176)	1,907 (4,204)
Unsprung weight	Front	kg (lb.)	690 (1,520)	690 (1,520)	690 (1,520)
	Rear	kg (lb.)	1,125 (2,480)	1,125 (2,480)	1,125 (2,480)
Center of gravity height from the ground		mm (in.)	790 (31.1)	790 (31.1)	790 (31.1)

Model			NV8JPSG	NV8JRSG	NV8JTSG	NV8JVSG
<b>CAPACITY</b>						
GVWR	Manual T/M	kg (lb.)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)
	Auto T/M	kg (lb.)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)
GAWR	Front	kg (lb.)	5,980 (13,200)	5,980 (13,200)	5,980 (13,200)	5,980 (13,200)
	Rear	kg (lb.)	9,530 (21,000)	9,530 (21,000)	9,530 (21,000)	9,530 (21,000)
<b>DIMENSIONS</b> (On standard specifications)						
Wheelbase		mm (in.)	5,512 (217.0)	5,969 (235.0)	6,426 (253.0)	6,883 (271.0)
Overall length		mm (in.)	9,007 (354.6)	9,464 (372.6)	9,921 (390.6)	9,921 (390.6)
Overall width		mm (in.)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)
Overall height		mm (in.)	2,715 (106.9)	2,715 (106.9)	2,715 (106.9)	2,715 (106.9)
BBC		mm (in.)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)
Cab to axle		mm (in.)	3,800 (149.6)	4,257 (167.6)	4,714 (185.6)	5,171 (203.6)
Rear overhang		mm (in.)	2,464 (97.0)	2,464 (97.0)	2,464 (97.0)	2,007 (79.0)
Frame height at	Front axle	mm (in.)	950 (37.4)	950 (37.4)	950 (37.4)	950 (37.4)
	Rear axle	mm (in.)	990 (39.0)	990 (39.0)	990 (39.0)	990 (39.0)
Road clearance (at diff. case)		mm (in.)	285 (11.2)	285 (11.2)	285 (11.2)	285 (11.2)
Tread	Front	mm (in.)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)
	Rear	mm (in.)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)
Turning radius Tire		mm (in.)	8,890 (350.0)	9,570 (376.8)	10,240 (403.1)	10,910 (429.5)
Turning radius Swept		mm (in.)	9,410 (370.5)	10,090 (397.2)	10,760 (423.6)	11,430 (450.0)
<b>CHASSIS WEIGHTS</b> (on std. spec., without spare tire & std. tool set)						
<b>MANUAL T/M</b>						
Total weight	MT	kg (lb.)	5,155 (11,367)	5,180 (11,422)	5,200 (11,462)	5,235 (11,542)
Front axle	MT	kg (lb.)	3,203 (7,064)	3,235 (7,135)	3,296 (7,263)	3,311 (7,299)
Rear axle	MT	kg (lb.)	1,952 (4,303)	1,945 (4,287)	1,904 (4,199)	1,924 (4,243)
Unsprung weight	Front	kg (lb.)	690 (1,520)	690 (1,520)	690 (1,520)	690 (1,520)
	Rear	kg (lb.)	1,125 (2,480)	1,125 (2,480)	1,125 (2,480)	1,125 (2,480)
<b>AUTO T/M</b>						
Total weight	ATM	kg (lb.)	5,104 (11,254)	5,129 (11,309)	5,149 (11,349)	5,184 (11,429)
Front axle	ATM	kg (lb.)	3,156 (6,959)	3,191 (7,035)	3,250 (7,164)	3,259 (7,183)
Rear axle	ATM	kg (lb.)	1,948 (4,295)	1,938 (4,274)	1,899 (4,185)	1,925 (4,246)
Unsprung weight	Front	kg (lb.)	690 (1,520)	690 (1,520)	690 (1,520)	690 (1,520)
	Rear	kg (lb.)	1,125 (2,480)	1,125 (2,480)	1,125 (2,480)	1,125 (2,480)
Center of gravity height from the ground		mm (in.)	790 (31.1)	790 (31.1)	790 (31.1)	790 (31.1)

## NV8J (Rr AIR SUS.)

Fr. Axl : MFS14 Fr. Spg : 14,000 lbs

Rr. Axl : RS23 Rr. Spg : 23,000 lbs

Model			NV8JGSG	NV8JJSG	NV8JLSG	NV8JMSG
<b>CAPACITY</b>						
GVWR	Manual T/M	kg (lb.)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)
	Auto T/M	kg (lb.)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)
GAWR	Front	kg (lb.)	5,980 (13,200)	5,980 (13,200)	5,980 (13,200)	5,980 (13,200)
	Rear	kg (lb.)	10,430 (23,000)	10,430 (23,000)	10,430 (23,000)	10,430 (23,000)
<b>DIMENSIONS</b> (On standard specifications)						
Wheelbase		mm (in.)	3,861 (152.0)	4,445 (175.0)	4,750 (187.0)	5,207 (205.0)
Overall length		mm (in.)	6,162 (242.6)	7,076 (278.6)	7,686 (302.6)	8,143 (320.6)
Overall width		mm (in.)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)
Overall height		mm (in.)	2,715 (106.9)	2,715 (106.9)	2,715 (106.9)	2,715 (106.9)
BBC		mm (in.)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)
Cab to axle		mm (in.)	2,149 (84.6)	2,733 (107.6)	3,038 (119.6)	3,495 (137.6)
Rear overhang		mm (in.)	1,270 (50.0)	1,600 (63.0)	1,905 (75.0)	1,905 (75.0)
Frame height at	Front axle	mm (in.)	950 (37.4)	950 (37.4)	950 (37.4)	950 (37.4)
	Rear axle	mm (in.)	990 (39.0)	990 (39.0)	990 (39.0)	990 (39.0)
Road clearance (at diff. case)		mm (in.)	255 (10.0)	255 (10.0)	255 (10.0)	255 (10.0)
Tread	Front	mm (in.)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)
	Rear	mm (in.)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)
Turning radius Tire		mm (in.)	6,470 (254.7)	7,330 (288.6)	7,770 (305.9)	8,440 (332.3)
Turning radius Swept		mm (in.)	6,990 (275.2)	7,850 (309.1)	8,290 (326.4)	8,970 (353.1)
<b>CHASSIS WEIGHTS</b> (on std. spec., without spare tire & std. tool set)						
<b>MANUAL T/M</b>						
Total weight	MT	kg (lb.)	5,045 (11,122)	5,085 (11,212)	5,120 (11,287)	5,195 (11,452)
Front axle	MT	kg (lb.)	2,990 (6,589)	3,102 (6,842)	3,134 (6,907)	3,189 (7,029)
Rear axle	MT	kg (lb.)	2,055 (4,533)	1,983 (4,370)	1,986 (4,380)	2,006 (4,423)
Unsprung weight	Front	kg (lb.)	690 (1,520)	690 (1,520)	690 (1,520)	690 (1,520)
	Rear	kg (lb.)	1,210 (2,670)	1,210 (2,670)	1,210 (2,670)	1,210 (2,670)
<b>AUTO T/M</b>						
Total weight	ATM	kg (lb.)	5,120 (11,287)	5,160 (11,377)	5,195 (11,452)	5,275 (11,627)
Front axle	ATM	kg (lb.)	3,040 (6,699)	3,157 (6,962)	3,184 (7,017)	3,254 (7,169)
Rear axle	ATM	kg (lb.)	2,080 (4,588)	2,003 (4,415)	2,011 (4,435)	2,021 (4,458)
Unsprung weight	Front	kg (lb.)	690 (1,520)	690 (1,520)	690 (1,520)	690 (1,520)
	Rear	kg (lb.)	1,210 (2,670)	1,210 (2,670)	1,210 (2,670)	1,210 (2,670)
Center of gravity height from the ground		mm (in.)	790 (31.1)	790 (31.1)	790 (31.1)	790 (31.1)

Model			NV8JPSG	NV8JRSG	NV8JTSG	NV8JVSG
<b>CAPACITY</b>						
GVWR	Manual T/M	kg (lb.)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)
	Auto T/M	kg (lb.)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)	14,950 (33,000)
GAWR	Front	kg (lb.)	5,980 (13,200)	5,980 (13,200)	5,980 (13,200)	5,980 (13,200)
	Rear	kg (lb.)	10,430 (23,000)	10,430 (23,000)	10,430 (23,000)	10,430 (23,000)
<b>DIMENSIONS</b> (On standard specifications)						
Wheelbase		mm (in.)	5,512 (217.0)	5,969 (235.0)	6,426 (253.0)	6,883 (271.0)
Overall length		mm (in.)	9,007 (354.6)	9,464 (372.6)	9,921 (390.6)	9,921 (390.6)
Overall width		mm (in.)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)
Overall height		mm (in.)	2,715 (106.9)	2,715 (106.9)	2,715 (106.9)	2,715 (106.9)
BBC		mm (in.)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)
Cab to axle		mm (in.)	3,800 (149.6)	4,257 (167.6)	4,714 (185.6)	5,171 (203.6)
Rear overhang		mm (in.)	2,464 (97.0)	2,464 (97.0)	2,464 (97.0)	2,007 (79.0)
Frame height at	Front axle	mm (in.)	950 (37.4)	950 (37.4)	950 (37.4)	950 (37.4)
	Rear axle	mm (in.)	990 (39.0)	990 (39.0)	990 (39.0)	990 (39.0)
Road clearance (at diff. case)		mm (in.)	255 (10.0)	255 (10.0)	255 (10.0)	255 (10.0)
Tread	Front	mm (in.)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)
	Rear	mm (in.)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)
Turning radius Tire		mm (in.)	8,890 (350.0)	9,570 (376.8)	10,240 (403.1)	10,910 (429.5)
Turning radius Swept		mm (in.)	9,410 (370.5)	10,090 (397.2)	10,760 (423.6)	11,430 (450.0)
<b>CHASSIS WEIGHTS</b> (on std. spec., without spare tire & std. tool set)						
<b>MANUAL T/M</b>						
Total weight	MT	kg (lb.)	5,235 (11,542)	5,260 (11,597)	5,285 (11,652)	5,315 (11,717)
Front axle	MT	kg (lb.)	3,194 (7,040)	3,226 (7,111)	3,292 (7,259)	3,302 (7,280)
Rear axle	MT	kg (lb.)	2,041 (4,502)	2,034 (4,486)	1,993 (4,393)	2,013 (4,437)
Unsprung weight	Front	kg (lb.)	690 (1,520)	690 (1,520)	690 (1,520)	690 (1,520)
	Rear	kg (lb.)	1,210 (2,670)	1,210 (2,670)	1,210 (2,670)	1,210 (2,670)
<b>AUTO T/M</b>						
Total weight	ATM	kg (lb.)	5,315 (11,717)	5,340 (11,772)	5,360 (11,817)	5,395 (11,892)
Front axle	ATM	kg (lb.)	3,259 (7,185)	3,291 (7,256)	3,352 (7,389)	3,367 (7,420)
Rear axle	ATM	kg (lb.)	2,056 (4,532)	2,049 (4,516)	2,008 (4,428)	2,028 (4,472)
Unsprung weight	Front	kg (lb.)	690 (1,520)	690 (1,520)	690 (1,520)	690 (1,520)
	Rear	kg (lb.)	1,210 (2,670)	1,210 (2,670)	1,210 (2,670)	1,210 (2,670)
Center of gravity height from the ground		mm (in.)	790 (31.1)	790 (31.1)	790 (31.1)	790 (31.1)

## NH8J

Fr. Axl : MFS12 Fr. Spg : 12,000 lbs

Rr. Axl : RS23 Rr. Spg : 23,000 lbs

Model			NH8JGSA	NH8JJSA	NH8JLSA	NH8JMSA
<b>CAPACITY</b>						
GVWR	Manual T/M	kg (lb.)	15,870 (35,000)	15,870 (35,000)	15,870 (35,000)	15,870 (35,000)
	Auto T/M	kg (lb.)	15,870 (35,000)	15,870 (35,000)	15,870 (35,000)	15,870 (35,000)
GAWR	Front	kg (lb.)	5,440 (12,000)	5,440 (12,000)	5,440 (12,000)	5,440 (12,000)
	Rear	kg (lb.)	10,430 (23,000)	10,430 (23,000)	10,430 (23,000)	10,430 (23,000)
<b>DIMENSIONS</b> (On standard specifications)						
Wheelbase		mm (in.)	3,861 (152.0)	4,445 (175.0)	4,750 (187.0)	5,207 (205.0)
Overall length		mm (in.)	6,162 (242.6)	7,076 (278.6)	7,686 (302.6)	8,143 (320.6)
Overall width		mm (in.)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)
Overall height		mm (in.)	2,720 (107.1)	2,720 (107.1)	2,720 (107.1)	2,720 (107.1)
BBC		mm (in.)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)
Cab to axle		mm (in.)	2,149 (84.6)	2,733 (107.6)	3,038 (119.6)	3,495 (137.6)
Rear overhang		mm (in.)	1,270 (50.0)	1,600 (63.0)	1,905 (75.0)	1,905 (75.0)
Frame height at	Front axle	mm (in.)	940 (37.0)	940 (37.0)	940 (37.0)	940 (37.0)
	Rear axle	mm (in.)	1,030 (40.6)	1,030 (40.6)	1,030 (40.6)	1,030 (40.6)
Road clearance (at diff. case)		mm (in.)	255 (10.0)	255 (10.0)	255 (10.0)	255 (10.0)
Tread	Front	mm (in.)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)
	Rear	mm (in.)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)
Turning radius Tire		mm (in.)	6,400 (252.0)	7,240 (285.0)	7,690 (302.8)	8,350 (328.7)
Turning radius Swept		mm (in.)	6,920 (272.4)	7,760 (305.5)	8,210 (323.2)	8,870 (349.2)
<b>CHASSIS WEIGHTS</b> (on std. spec., without spare tire & std. tool set)						
<b>MANUAL T/M</b>						
Total weight	MT	kg (lb.)	5,020 (11,067)	5,070 (11,177)	5,105 (11,252)	5,180 (11,422)
Front axle	MT	kg (lb.)	2,945 (6,494)	3,067 (6,762)	3,094 (6,817)	3,154 (6,954)
Rear axle	MT	kg (lb.)	2,075 (4,573)	2,003 (4,415)	2,011 (4,435)	2,026 (4,468)
Unsprung weight	Front	kg (lb.)	645 (1,420)	645 (1,420)	645 (1,420)	645 (1,420)
	Rear	kg (lb.)	1,225 (2,700)	1,225 (2,700)	1,225 (2,700)	1,225 (2,700)
<b>AUTO T/M</b>						
Total weight	ATM	kg (lb.)	5,100 (11,242)	5,145 (11,342)	5,180 (11,422)	5,260 (11,597)
Front axle	ATM	kg (lb.)	3,000 (6,614)	3,117 (6,872)	3,149 (6,942)	3,214 (7,084)
Rear axle	ATM	kg (lb.)	2,100 (4,628)	2,028 (4,470)	2,031 (4,480)	2,046 (4,513)
Unsprung weight	Front	kg (lb.)	645 (1,420)	645 (1,420)	645 (1,420)	645 (1,420)
	Rear	kg (lb.)	1,225 (2,700)	1,225 (2,700)	1,225 (2,700)	1,225 (2,700)
Center of gravity height from the ground		mm (in.)	795 (31.3)	795 (31.3)	795 (31.3)	795 (31.3)

Model			NH8JPSA	NH8JRSA	NH8JTSA	NH8JVSA
<b>CAPACITY</b>						
GVWR	Manual T/M	kg (lb.)	15,870 (35,000)	15,870 (35,000)	15,870 (35,000)	15,870 (35,000)
	Auto T/M	kg (lb.)	15,870 (35,000)	15,870 (35,000)	15,870 (35,000)	15,870 (35,000)
GAWR	Front	kg (lb.)	5,440 (12,000)	5,440 (12,000)	5,440 (12,000)	5,440 (12,000)
	Rear	kg (lb.)	10,430 (23,000)	10,430 (23,000)	10,430 (23,000)	10,430 (23,000)
<b>DIMENSIONS</b> (On standard specifications)						
Wheelbase		mm (in.)	5,512 (217.0)	5,969 (235.0)	6,426 (253.0)	6,883 (271.0)
Overall length		mm (in.)	9,007 (354.6)	9,464 (372.6)	9,921 (390.6)	9,921 (390.6)
Overall width		mm (in.)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)
Overall height		mm (in.)	2,720 (107.1)	2,720 (107.1)	2,720 (107.1)	2,720 (107.1)
BBC		mm (in.)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)
Cab to axle		mm (in.)	3,800 (149.6)	4,257 (167.6)	4,714 (185.6)	5,171 (203.6)
Rear overhang		mm (in.)	2,464 (97.0)	2,464 (97.0)	2,464 (97.0)	2,007 (79.0)
Frame height at	Front axle	mm (in.)	940 (37.0)	940 (37.0)	940 (37.0)	940 (37.0)
	Rear axle	mm (in.)	1,030 (40.6)	1,030 (40.6)	1,030 (40.6)	1,030 (40.6)
Road clearance (at diff. case)		mm (in.)	255 (10.0)	255 (10.0)	255 (10.0)	255 (10.0)
Tread	Front	mm (in.)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)
	Rear	mm (in.)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)
Turning radius Tire		mm (in.)	8,790 (346.1)	9,460 (372.4)	10,120 (398.4)	10,790 (424.8)
Turning radius Swept		mm (in.)	9,310 (366.5)	9,980 (392.9)	10,640 (418.9)	11,310 (445.3)
<b>CHASSIS WEIGHTS</b> (on std. spec., without spare tire & std. tool set)						
<b>MANUAL T/M</b>						
Total weight	MT	kg (lb.)	5,220 (11,507)	5,245 (11,562)	5,270 (11,617)	5,300 (11,682)
Front axle	MT	kg (lb.)	3,154 (6,950)	3,191 (7,036)	3,257 (7,179)	3,262 (7,190)
Rear axle	MT	kg (lb.)	2,066 (4,557)	2,054 (4,526)	2,013 (4,438)	2,038 (4,492)
Unsprung weight	Front	kg (lb.)	645 (1,420)	645 (1,420)	645 (1,420)	645 (1,420)
	Rear	kg (lb.)	1,225 (2,700)	1,225 (2,700)	1,225 (2,700)	1,225 (2,700)
<b>AUTO T/M</b>						
Total weight	ATM	kg (lb.)	5,300 (11,682)	5,325 (11,737)	5,345 (11,782)	5,380 (11,862)
Front axle	ATM	kg (lb.)	3,219 (7,095)	3,256 (7,176)	3,317 (7,309)	3,327 (7,335)
Rear axle	ATM	kg (lb.)	2,081 (4,587)	2,069 (4,561)	2,028 (4,473)	2,053 (4,527)
Unsprung weight	Front	kg (lb.)	645 (1,420)	645 (1,420)	645 (1,420)	645 (1,420)
	Rear	kg (lb.)	1,225 (2,700)	1,225 (2,700)	1,225 (2,700)	1,225 (2,700)
Center of gravity height from the ground		mm (in.)	795 (31.3)	795 (31.3)	795 (31.3)	795 (31.3)



## NH8J

Fr. Axl : MFS12 Fr. Spg : 12,000 lbs

Rr. Axl : RS23 Rr. Spg : 31,000 lbs

Model			NH8JGSA	NH8JJSA	NH8JLSA	NH8JMSA
<b>CAPACITY</b>						
GVWR	Manual T/M	kg (lb.)	15,870 (35,000)	15,870 (35,000)	15,870 (35,000)	15,870 (35,000)
	Auto T/M	kg (lb.)	15,870 (35,000)	15,870 (35,000)	15,870 (35,000)	15,870 (35,000)
GAWR	Front	kg (lb.)	5,440 (12,000)	5,440 (12,000)	5,440 (12,000)	5,440 (12,000)
	Rear	kg (lb.)	10,430 (23,000)	10,430 (23,000)	10,430 (23,000)	10,430 (23,000)
<b>DIMENSIONS</b> (On standard specifications)						
Wheelbase		mm (in.)	3,861 (152.0)	4,445 (175.0)	4,750 (187.0)	5,207 (205.0)
Overall length		mm (in.)	6,162 (242.6)	7,076 (278.6)	7,686 (302.6)	8,143 (320.6)
Overall width		mm (in.)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)
Overall height		mm (in.)	2,720 (107.1)	2,720 (107.1)	2,720 (107.1)	2,720 (107.1)
BBC		mm (in.)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)
Cab to axle		mm (in.)	2,149 (84.6)	2,733 (107.6)	3,038 (119.6)	3,495 (137.6)
Rear overhang		mm (in.)	1,270 (50.0)	1,600 (63.0)	1,905 (75.0)	1,905 (75.0)
Frame height at	Front axle	mm (in.)	940 (37.0)	940 (37.0)	940 (37.0)	940 (37.0)
	Rear axle	mm (in.)	1,030 (40.6)	1,030 (40.6)	1,030 (40.6)	1,030 (40.6)
Road clearance (at diff. case)		mm (in.)	255 (10.0)	255 (10.0)	255 (10.0)	255 (10.0)
Tread	Front	mm (in.)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)
	Rear	mm (in.)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)
Turning radius Tire		mm (in.)	6,400 (252.0)	7,240 (285.0)	7,690 (302.8)	8,350 (328.7)
Turning radius Swept		mm (in.)	6,920 (272.4)	7,760 (305.5)	8,210 (323.2)	8,870 (349.2)
<b>CHASSIS WEIGHTS</b> (on std. spec., without spare tire & std. tool set)						
<b>MANUAL T/M</b>						
Total weight	MT	kg (lb.)	5,054 (11,142)	5,104 (11,252)	5,139 (11,332)	5,214 (11,497)
Front axle	MT	kg (lb.)	2,949 (6,503)	3,071 (6,771)	3,098 (6,831)	3,158 (6,963)
Rear axle	MT	kg (lb.)	2,105 (4,639)	2,033 (4,481)	2,041 (4,501)	2,056 (4,534)
Unsprung weight	Front	kg (lb.)	645 (1,420)	645 (1,420)	645 (1,420)	645 (1,420)
	Rear	kg (lb.)	1,225 (2,700)	1,225 (2,700)	1,225 (2,700)	1,225 (2,700)
<b>AUTO T/M</b>						
Total weight	ATM	kg (lb.)	5,134 (11,317)	5,179 (11,417)	5,214 (11,497)	5,294 (11,672)
Front axle	ATM	kg (lb.)	3,004 (6,623)	3,121 (6,881)	3,153 (6,951)	3,218 (7,093)
Rear axle	ATM	kg (lb.)	2,130 (4,694)	2,058 (4,536)	2,061 (4,546)	2,076 (4,579)
Unsprung weight	Front	kg (lb.)	645 (1,420)	645 (1,420)	645 (1,420)	645 (1,420)
	Rear	kg (lb.)	1,225 (2,700)	1,225 (2,700)	1,225 (2,700)	1,225 (2,700)
Center of gravity height from the ground		mm (in.)	795 (31.3)	795 (31.3)	795 (31.3)	795 (31.3)

Model			NH8JPSA	NH8JRSA	NH8JTSA	NH8JVSA
<b>CAPACITY</b>						
GVWR	Manual T/M	kg (lb.)	15,870 (35,000)	15,870 (35,000)	15,870 (35,000)	15,870 (35,000)
	Auto T/M	kg (lb.)	15,870 (35,000)	15,870 (35,000)	15,870 (35,000)	15,870 (35,000)
GAWR	Front	kg (lb.)	5,440 (12,000)	5,440 (12,000)	5,440 (12,000)	5,440 (12,000)
	Rear	kg (lb.)	10,430 (23,000)	10,430 (23,000)	10,430 (23,000)	10,430 (23,000)
<b>DIMENSIONS</b> (On standard specifications)						
Wheelbase		mm (in.)	5,512 (217.0)	5,969 (235.0)	6,426 (253.0)	6,883 (271.0)
Overall length		mm (in.)	9,007 (354.6)	9,464 (372.6)	9,921 (390.6)	9,921 (390.6)
Overall width		mm (in.)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)
Overall height		mm (in.)	2,720 (107.1)	2,720 (107.1)	2,720 (107.1)	2,720 (107.1)
BBC		mm (in.)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)
Cab to axle		mm (in.)	3,800 (149.6)	4,257 (167.6)	4,714 (185.6)	5,171 (203.6)
Rear overhang		mm (in.)	2,464 (97.0)	2,464 (97.0)	2,464 (97.0)	2,007 (79.0)
Frame height at	Front axle	mm (in.)	940 (37.0)	940 (37.0)	940 (37.0)	940 (37.0)
	Rear axle	mm (in.)	1,030 (40.6)	1,030 (40.6)	1,030 (40.6)	1,030 (40.6)
Road clearance (at diff. case)		mm (in.)	255 (10.0)	255 (10.0)	255 (10.0)	255 (10.0)
Tread	Front	mm (in.)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)
	Rear	mm (in.)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)
Turning radius Tire		mm (in.)	8,790 (346.1)	9,460 (372.4)	10,120 (398.4)	10,790 (424.8)
Turning radius Swept		mm (in.)	9,310 (366.5)	9,980 (392.9)	10,640 (418.9)	11,310 (445.3)
<b>CHASSIS WEIGHTS</b> (on std. spec., without spare tire & std. tool set)						
<b>MANUAL T/M</b>						
Total weight	MT	kg (lb.)	5,254 (11,582)	5,279 (11,637)	5,304 (11,692)	5,334 (11,757)
Front axle	MT	kg (lb.)	3,158 (6,964)	3,195 (7,045)	3,261 (7,188)	3,266 (7,199)
Rear axle	MT	kg (lb.)	2,096 (4,623)	2,084 (4,592)	2,043 (4,504)	2,068 (4,558)
Unsprung weight	Front	kg (lb.)	645 (1,420)	645 (1,420)	645 (1,420)	645 (1,420)
	Rear	kg (lb.)	1,225 (2,700)	1,225 (2,700)	1,225 (2,700)	1,225 (2,700)
<b>AUTO T/M</b>						
Total weight	ATM	kg (lb.)	5,334 (11,757)	5,359 (11,817)	5,379 (11,857)	5,414 (11,937)
Front axle	ATM	kg (lb.)	3,223 (7,104)	3,260 (7,185)	3,321 (7,323)	3,331 (7,344)
Rear axle	ATM	kg (lb.)	2,111 (4,653)	2,099 (4,627)	2,058 (4,539)	2,083 (4,593)
Unsprung weight	Front	kg (lb.)	645 (1,420)	645 (1,420)	645 (1,420)	645 (1,420)
	Rear	kg (lb.)	1,225 (2,700)	1,225 (2,700)	1,225 (2,700)	1,225 (2,700)
Center of gravity height from the ground		mm (in.)	795 (31.3)	795 (31.3)	795 (31.3)	795 (31.3)

## NH8J

Fr. Axl : MFS14 Fr. Spg : 14,000 lbs

Rr. Axl : RS23 Rr. Spg : 23,000 lbs

Model			NH8JGSA	NH8JJSA	NH8JLSA	NH8JMSA
<b>CAPACITY</b>						
GVWR	Manual T/M	kg (lb.)	15,870 (35,000)	15,870 (35,000)	15,870 (35,000)	15,870 (35,000)
	Auto T/M	kg (lb.)	15,870 (35,000)	15,870 (35,000)	15,870 (35,000)	15,870 (35,000)
GAWR	Front	kg (lb.)	5,980 (13,200)	5,980 (13,200)	5,980 (13,200)	5,980 (13,200)
	Rear	kg (lb.)	10,430 (23,000)	10,430 (23,000)	10,430 (23,000)	10,430 (23,000)
<b>DIMENSIONS</b> (On standard specifications)						
Wheelbase		mm (in.)	3,861 (152.0)	4,445 (175.0)	4,750 (187.0)	5,207 (205.0)
Overall length		mm (in.)	6,162 (242.6)	7,076 (278.6)	7,686 (302.6)	8,143 (320.6)
Overall width		mm (in.)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)
Overall height		mm (in.)	2,725 (107.3)	2,725 (107.3)	2,725 (107.3)	2,725 (107.3)
BBC		mm (in.)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)
Cab to axle		mm (in.)	2,149 (84.6)	2,733 (107.6)	3,038 (119.6)	3,495 (137.6)
Rear overhang		mm (in.)	1,270 (50.0)	1,600 (63.0)	1,905 (75.0)	1,905 (75.0)
Frame height at	Front axle	mm (in.)	950 (37.4)	950 (37.4)	950 (37.4)	950 (37.4)
	Rear axle	mm (in.)	1,030 (40.6)	1,030 (40.6)	1,030 (40.6)	1,030 (40.6)
Road clearance (at diff. case)		mm (in.)	255 (10.0)	255 (10.0)	255 (10.0)	255 (10.0)
Tread	Front	mm (in.)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)
	Rear	mm (in.)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)
Turning radius Tire		mm (in.)	6,470 (254.7)	7,330 (288.6)	7,770 (305.9)	8,440 (332.3)
Turning radius Swept		mm (in.)	6,990 (275.2)	7,850 (309.1)	8,290 (326.4)	8,970 (353.1)
<b>CHASSIS WEIGHTS</b> (on std. spec., without spare tire & std. tool set)						
<b>MANUAL T/M</b>						
Total weight	MT	kg (lb.)	5,065 (11,187)	5,110 (11,287)	5,145 (11,362)	5,225 (11,537)
Front axle	MT	kg (lb.)	2,990 (6,603)	3,107 (6,861)	3,134 (6,916)	3,199 (7,058)
Rear axle	MT	kg (lb.)	2,075 (4,584)	2,003 (4,426)	2,011 (4,446)	2,026 (4,479)
Unsprung weight	Front	kg (lb.)	690 (1,520)	690 (1,520)	690 (1,520)	690 (1,520)
	Rear	kg (lb.)	1,225 (2,700)	1,225 (2,700)	1,225 (2,700)	1,225 (2,700)
<b>AUTO T/M</b>						
Total weight	ATM	kg (lb.)	5,140 (11,332)	5,185 (11,432)	5,225 (11,517)	5,300 (11,682)
Front axle	ATM	kg (lb.)	3,040 (6,704)	3,157 (6,962)	3,194 (7,037)	3,254 (7,169)
Rear axle	ATM	kg (lb.)	2,100 (4,628)	2,028 (4,470)	2,031 (4,480)	2,046 (4,513)
Unsprung weight	Front	kg (lb.)	690 (1,520)	690 (1,520)	690 (1,520)	690 (1,520)
	Rear	kg (lb.)	1,225 (2,700)	1,225 (2,700)	1,225 (2,700)	1,225 (2,700)
Center of gravity height from the ground		mm (in.)	795 (31.3)	795 (31.3)	795 (31.3)	795 (31.3)

Model			NH8JPSA	NH8JRSA	NH8JTSA	NH8JVSA
<b>CAPACITY</b>						
GVWR	Manual T/M	kg (lb.)	15,870 (35,000)	15,870 (35,000)	15,870 (35,000)	15,870 (35,000)
	Auto T/M	kg (lb.)	15,870 (35,000)	15,870 (35,000)	15,870 (35,000)	15,870 (35,000)
GAWR	Front	kg (lb.)	5,980 (13,200)	5,980 (13,200)	5,980 (13,200)	5,980 (13,200)
	Rear	kg (lb.)	10,430 (23,000)	10,430 (23,000)	10,430 (23,000)	10,430 (23,000)
<b>DIMENSIONS</b> (On standard specifications)						
Wheelbase		mm (in.)	5,512 (217.0)	5,969 (235.0)	6,426 (253.0)	6,883 (271.0)
Overall length		mm (in.)	9,007 (354.6)	9,464 (372.6)	9,921 (390.6)	9,921 (390.6)
Overall width		mm (in.)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)
Overall height		mm (in.)	2,725 (107.3)	2,725 (107.3)	2,725 (107.3)	2,725 (107.3)
BBC		mm (in.)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)
Cab to axle		mm (in.)	3,800 (149.6)	4,257 (167.6)	4,714 (185.6)	5,171 (203.6)
Rear overhang		mm (in.)	2,464 (97.0)	2,464 (97.0)	2,464 (97.0)	2,007 (79.0)
Frame height at	Front axle	mm (in.)	950 (37.4)	950 (37.4)	950 (37.4)	950 (37.4)
	Rear axle	mm (in.)	1,030 (40.6)	1,030 (40.6)	1,030 (40.6)	1,030 (40.6)
Road clearance (at diff. case)		mm (in.)	255 (10.0)	255 (10.0)	255 (10.0)	255 (10.0)
Tread	Front	mm (in.)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)
	Rear	mm (in.)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)
Turning radius Tire		mm (in.)	8,890 (350.0)	9,570 (376.8)	10,240 (403.1)	10,910 (429.5)
Turning radius Swept		mm (in.)	9,410 (370.5)	10,090 (397.2)	10,760 (423.6)	11,430 (450.0)
<b>CHASSIS WEIGHTS</b> (on std. spec., without spare tire & std. tool set)						
<b>MANUAL T/M</b>						
Total weight	MT	kg (lb.)	5,265 (11,627)	5,290 (11,682)	5,310 (11,727)	5,345 (11,802)
Front axle	MT	kg (lb.)	3,199 (7,059)	3,236 (7,145)	3,297 (7,278)	3,307 (7,299)
Rear axle	MT	kg (lb.)	2,066 (4,568)	2,054 (4,537)	2,013 (4,449)	2,038 (4,503)
Unsprung weight	Front	kg (lb.)	690 (1,520)	690 (1,520)	690 (1,520)	690 (1,520)
	Rear	kg (lb.)	1,225 (2,700)	1,225 (2,700)	1,225 (2,700)	1,225 (2,700)
<b>AUTO T/M</b>						
Total weight	ATM	kg (lb.)	5,340 (11,772)	5,365 (11,827)	5,385 (11,872)	5,420 (11,947)
Front axle	ATM	kg (lb.)	3,259 (7,185)	3,296 (7,266)	3,357 (7,399)	3,367 (7,420)
Rear axle	ATM	kg (lb.)	2,081 (4,587)	2,069 (4,561)	2,028 (4,473)	2,053 (4,527)
Unsprung weight	Front	kg (lb.)	690 (1,520)	690 (1,520)	690 (1,520)	690 (1,520)
	Rear	kg (lb.)	1,225 (2,700)	1,225 (2,700)	1,225 (2,700)	1,225 (2,700)
Center of gravity height from the ground		mm (in.)	795 (31.3)	795 (31.3)	795 (31.3)	795 (31.3)

## NH8J

Fr. Axl : MFS14 Fr. Spg : 14,000 lbs

Rr. Axl : RS23 Rr. Spg : 31,000 lbs

Model			NH8JGSA	NH8JJSA	NH8JLSA	NH8JMSA
<b>CAPACITY</b>						
GVWR	Manual T/M	kg (lb.)	15,870 (35,000)	15,870 (35,000)	15,870 (35,000)	15,870 (35,000)
	Auto T/M	kg (lb.)	15,870 (35,000)	15,870 (35,000)	15,870 (35,000)	15,870 (35,000)
GAWR	Front	kg (lb.)	5,980 (13,200)	5,980 (13,200)	5,980 (13,200)	5,980 (13,200)
	Rear	kg (lb.)	10,430 (23,000)	10,430 (23,000)	10,430 (23,000)	10,430 (23,000)
<b>DIMENSIONS</b> (On standard specifications)						
Wheelbase		mm (in.)	3,861 (152.0)	4,445 (175.0)	4,750 (187.0)	5,207 (205.0)
Overall length		mm (in.)	6,162 (242.6)	7,076 (278.6)	7,686 (302.6)	8,143 (320.6)
Overall width		mm (in.)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)
Overall height		mm (in.)	2,725 (107.3)	2,725 (107.3)	2,725 (107.3)	2,725 (107.3)
BBC		mm (in.)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)
Cab to axle		mm (in.)	2,149 (84.6)	2,733 (107.6)	3,038 (119.6)	3,495 (137.6)
Rear overhang		mm (in.)	1,270 (50.0)	1,600 (63.0)	1,905 (75.0)	1,905 (75.0)
Frame height at	Front axle	mm (in.)	950 (37.4)	950 (37.4)	950 (37.4)	950 (37.4)
	Rear axle	mm (in.)	1,030 (40.6)	1,030 (40.6)	1,030 (40.6)	1,030 (40.6)
Road clearance (at diff. case)		mm (in.)	255 (10.0)	255 (10.0)	255 (10.0)	255 (10.0)
Tread	Front	mm (in.)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)
	Rear	mm (in.)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)
Turning radius Tire		mm (in.)	6,470 (254.7)	7,330 (288.6)	7,770 (305.9)	8,440 (332.3)
Turning radius Swept		mm (in.)	6,990 (275.2)	7,850 (309.1)	8,290 (326.4)	8,970 (353.1)
<b>CHASSIS WEIGHTS</b> (on std. spec., without spare tire & std. tool set)						
<b>MANUAL T/M</b>						
Total weight	MT	kg (lb.)	5,099 (11,242)	5,144 (11,342)	5,179 (11,417)	5,259 (11,592)
Front axle	MT	kg (lb.)	2,994 (6,598)	3,111 (6,861)	3,138 (6,916)	3,203 (7,063)
Rear axle	MT	kg (lb.)	2,105 (4,639)	2,033 (4,481)	2,041 (4,501)	2,056 (4,534)
Unsprung weight	Front	kg (lb.)	690 (1,520)	690 (1,520)	690 (1,520)	690 (1,520)
	Rear	kg (lb.)	1,225 (2,700)	1,225 (2,700)	1,225 (2,700)	1,225 (2,700)
<b>AUTO T/M</b>						
Total weight	ATM	kg (lb.)	5,174 (11,407)	5,219 (11,507)	5,259 (11,592)	5,334 (11,757)
Front axle	ATM	kg (lb.)	3,044 (6,713)	3,161 (6,971)	3,198 (7,051)	3,258 (7,183)
Rear axle	ATM	kg (lb.)	2,130 (4,694)	2,058 (4,536)	2,061 (4,546)	2,076 (4,579)
Unsprung weight	Front	kg (lb.)	690 (1,520)	690 (1,520)	690 (1,520)	690 (1,520)
	Rear	kg (lb.)	1,225 (2,700)	1,225 (2,700)	1,225 (2,700)	1,225 (2,700)
Center of gravity height from the ground		mm (in.)	795 (31.3)	795 (31.3)	795 (31.3)	795 (31.3)

Model			NH8JPSA	NH8JRSA	NH8JTSA	NH8JVSA
<b>CAPACITY</b>						
GVWR	Manual T/M	kg (lb.)	15,870 (35,000)	15,870 (35,000)	15,870 (35,000)	15,870 (35,000)
	Auto T/M	kg (lb.)	15,870 (35,000)	15,870 (35,000)	15,870 (35,000)	15,870 (35,000)
GAWR	Front	kg (lb.)	5,980 (13,200)	5,980 (13,200)	5,980 (13,200)	5,980 (13,200)
	Rear	kg (lb.)	10,430 (23,000)	10,430 (23,000)	10,430 (23,000)	10,430 (23,000)
<b>DIMENSIONS</b> (On standard specifications)						
Wheelbase		mm (in.)	5,512 (217.0)	5,969 (235.0)	6,426 (253.0)	6,883 (271.0)
Overall length		mm (in.)	9,007 (354.6)	9,464 (372.6)	9,921 (390.6)	9,921 (390.6)
Overall width		mm (in.)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)
Overall height		mm (in.)	2,725 (107.3)	2,725 (107.3)	2,725 (107.3)	2,725 (107.3)
BBC		mm (in.)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)
Cab to axle		mm (in.)	3,800 (149.6)	4,257 (167.6)	4,714 (185.6)	5,171 (203.6)
Rear overhang		mm (in.)	2,464 (97.0)	2,464 (97.0)	2,464 (97.0)	2,007 (79.0)
Frame height at	Front axle	mm (in.)	950 (37.4)	950 (37.4)	950 (37.4)	950 (37.4)
	Rear axle	mm (in.)	1,030 (40.6)	1,030 (40.6)	1,030 (40.6)	1,030 (40.6)
Road clearance (at diff. case)		mm (in.)	255 (10.0)	255 (10.0)	255 (10.0)	255 (10.0)
Tread	Front	mm (in.)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)
	Rear	mm (in.)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)
Turning radius Tire		mm (in.)	8,890 (350.0)	9,570 (376.8)	10,240 (403.1)	10,910 (429.5)
Turning radius Swept		mm (in.)	9,410 (370.5)	10,090 (397.2)	10,760 (423.6)	11,430 (450.0)
<b>CHASSIS WEIGHTS</b> (on std. spec., without spare tire & std. tool set)						
<b>MANUAL T/M</b>						
Total weight	MT	kg (lb.)	5,299 (11,682)	5,324 (11,737)	5,344 (11,782)	5,379 (11,857)
Front axle	MT	kg (lb.)	3,203 (7,059)	3,240 (7,145)	3,301 (7,278)	3,311 (7,299)
Rear axle	MT	kg (lb.)	2,096 (4,623)	2,084 (4,592)	2,043 (4,504)	2,068 (4,558)
Unsprung weight	Front	kg (lb.)	690 (1,520)	690 (1,520)	690 (1,520)	690 (1,520)
	Rear	kg (lb.)	1,225 (2,700)	1,225 (2,700)	1,225 (2,700)	1,225 (2,700)
<b>AUTO T/M</b>						
Total weight	ATM	kg (lb.)	5,374 (11,847)	5,399 (11,902)	5,419 (11,947)	5,454 (12,022)
Front axle	ATM	kg (lb.)	3,263 (7,194)	3,300 (7,275)	3,361 (7,408)	3,371 (7,434)
Rear axle	ATM	kg (lb.)	2,111 (4,653)	2,099 (4,627)	2,058 (4,539)	2,083 (4,593)
Unsprung weight	Front	kg (lb.)	690 (1,520)	690 (1,520)	690 (1,520)	690 (1,520)
	Rear	kg (lb.)	1,225 (2,700)	1,225 (2,700)	1,225 (2,700)	1,225 (2,700)
Center of gravity height from the ground		mm (in.)	795 (31.3)	795 (31.3)	795 (31.3)	795 (31.3)

**NH8J (Tire size : 295/75R22.5)****Fr. Axl : MFS14 Fr. Spg : 14,000 lbs****Rr. Axl : RS23 Rr. Spg : 23,000 lbs**

Model			NH8JGSA	NH8JJSA	NH8JLSA	NH8JMSA
<b>CAPACITY</b>						
GVWR	Manual T/M	kg (lb.)	15,870 (35,000)	15,870 (35,000)	15,870 (35,000)	15,870 (35,000)
	Auto T/M	kg (lb.)	15,870 (35,000)	15,870 (35,000)	15,870 (35,000)	15,870 (35,000)
GAWR	Front	kg (lb.)	5,980 (13,200)	5,980 (13,200)	5,980 (13,200)	5,980 (13,200)
	Rear	kg (lb.)	10,430 (23,000)	10,430 (23,000)	10,430 (23,000)	10,430 (23,000)
<b>DIMENSIONS</b> (On standard specifications)						
Wheelbase		mm (in.)	3,861 (152.0)	4,445 (175.0)	4,750 (187.0)	5,207 (205.0)
Overall length		mm (in.)	6,162 (242.6)	7,076 (278.6)	7,686 (302.6)	8,143 (320.6)
Overall width		mm (in.)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)
Overall height		mm (in.)	2,725 (107.3)	2,725 (107.3)	2,725 (107.3)	2,725 (107.3)
BBC		mm (in.)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)
Cab to axle		mm (in.)	2,149 (84.6)	2,733 (107.6)	3,038 (119.6)	3,495 (137.6)
Rear overhang		mm (in.)	1,270 (50.0)	1,600 (63.0)	1,905 (75.0)	1,905 (75.0)
Frame height at	Front axle	mm (in.)	950 (37.4)	950 (37.4)	950 (37.4)	950 (37.4)
	Rear axle	mm (in.)	1,030 (40.6)	1,030 (40.6)	1,030 (40.6)	1,030 (40.6)
Road clearance (at diff. case)		mm (in.)	255 (10.0)	255 (10.0)	255 (10.0)	255 (10.0)
Tread	Front	mm (in.)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)
	Rear	mm (in.)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)
Turning radius Tire		mm (in.)	6,470 (254.7)	7,330 (288.6)	7,770 (305.9)	8,440 (332.3)
Turning radius Swept		mm (in.)	6,990 (275.2)	7,850 (309.1)	8,290 (326.4)	8,970 (353.1)
<b>CHASSIS WEIGHTS</b> (on std. spec., without spare tire & std. tool set)						
<b>MANUAL T/M</b>						
Total weight	MT	kg (lb.)	5,065 (11,187)	5,110 (11,287)	5,145 (11,362)	5,225 (11,537)
Front axle	MT	kg (lb.)	2,990 (6,603)	3,107 (6,861)	3,134 (6,916)	3,199 (7,058)
Rear axle	MT	kg (lb.)	2,075 (4,584)	2,003 (4,426)	2,011 (4,446)	2,026 (4,479)
Unsprung weight	Front	kg (lb.)	690 (1,520)	690 (1,520)	690 (1,520)	690 (1,520)
	Rear	kg (lb.)	1,225 (2,700)	1,225 (2,700)	1,225 (2,700)	1,225 (2,700)
<b>AUTO T/M</b>						
Total weight	ATM	kg (lb.)	5,140 (11,332)	5,185 (11,432)	5,225 (11,517)	5,300 (11,682)
Front axle	ATM	kg (lb.)	3,040 (6,704)	3,157 (6,962)	3,194 (7,037)	3,254 (7,169)
Rear axle	ATM	kg (lb.)	2,100 (4,628)	2,028 (4,470)	2,031 (4,480)	2,046 (4,513)
Unsprung weight	Front	kg (lb.)	690 (1,520)	690 (1,520)	690 (1,520)	690 (1,520)
	Rear	kg (lb.)	1,225 (2,700)	1,225 (2,700)	1,225 (2,700)	1,225 (2,700)
Center of gravity height from the ground		mm (in.)	795 (31.3)	795 (31.3)	795 (31.3)	795 (31.3)



Model			NH8JPSA	NH8JRSA	NH8JTSA	NH8JVSA
<b>CAPACITY</b>						
GVWR	Manual T/M	kg (lb.)	15,870 (35,000)	15,870 (35,000)	15,870 (35,000)	15,870 (35,000)
	Auto T/M	kg (lb.)	15,870 (35,000)	15,870 (35,000)	15,870 (35,000)	15,870 (35,000)
GAWR	Front	kg (lb.)	5,980 (13,200)	5,980 (13,200)	5,980 (13,200)	5,980 (13,200)
	Rear	kg (lb.)	10,430 (23,000)	10,430 (23,000)	10,430 (23,000)	10,430 (23,000)
<b>DIMENSIONS</b> (On standard specifications)						
Wheelbase		mm (in.)	5,512 (217.0)	5,969 (235.0)	6,426 (253.0)	6,883 (271.0)
Overall length		mm (in.)	9,007 (354.6)	9,464 (372.6)	9,921 (390.6)	9,921 (390.6)
Overall width		mm (in.)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)
Overall height		mm (in.)	2,725 (107.3)	2,725 (107.3)	2,725 (107.3)	2,725 (107.3)
BBC		mm (in.)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)
Cab to axle		mm (in.)	3,800 (149.6)	4,257 (167.6)	4,714 (185.6)	5,171 (203.6)
Rear overhang		mm (in.)	2,464 (97.0)	2,464 (97.0)	2,464 (97.0)	2,007 (79.0)
Frame height at	Front axle	mm (in.)	950 (37.4)	950 (37.4)	950 (37.4)	950 (37.4)
	Rear axle	mm (in.)	1,030 (40.6)	1,030 (40.6)	1,030 (40.6)	1,030 (40.6)
Road clearance (at diff. case)		mm (in.)	255 (10.0)	255 (10.0)	255 (10.0)	255 (10.0)
Tread	Front	mm (in.)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)
	Rear	mm (in.)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)
Turning radius Tire		mm (in.)	8,890 (350.0)	9,570 (376.8)	10,240 (403.1)	10,910 (429.5)
Turning radius Swept		mm (in.)	9,410 (370.5)	10,090 (397.2)	10,760 (423.6)	11,430 (450.0)
<b>CHASSIS WEIGHTS</b> (on std. spec., without spare tire & std. tool set)						
<b>MANUAL T/M</b>						
Total weight	MT	kg (lb.)	5,265 (11,627)	5,290 (11,682)	5,310 (11,727)	5,345 (11,802)
Front axle	MT	kg (lb.)	3,199 (7,059)	3,236 (7,145)	3,297 (7,278)	3,307 (7,299)
Rear axle	MT	kg (lb.)	2,066 (4,568)	2,054 (4,537)	2,013 (4,449)	2,038 (4,503)
Unsprung weight	Front	kg (lb.)	690 (1,520)	690 (1,520)	690 (1,520)	690 (1,520)
	Rear	kg (lb.)	1,225 (2,700)	1,225 (2,700)	1,225 (2,700)	1,225 (2,700)
<b>AUTO T/M</b>						
Total weight	ATM	kg (lb.)	5,340 (11,772)	5,365 (11,827)	5,385 (11,872)	5,420 (11,947)
Front axle	ATM	kg (lb.)	3,259 (7,185)	3,296 (7,266)	3,357 (7,399)	3,367 (7,420)
Rear axle	ATM	kg (lb.)	2,081 (4,587)	2,069 (4,561)	2,028 (4,473)	2,053 (4,527)
Unsprung weight	Front	kg (lb.)	690 (1,520)	690 (1,520)	690 (1,520)	690 (1,520)
	Rear	kg (lb.)	1,225 (2,700)	1,225 (2,700)	1,225 (2,700)	1,225 (2,700)
Center of gravity height from the ground		mm (in.)	795 (31.3)	795 (31.3)	795 (31.3)	795 (31.3)



**NH8J (Tire size : 295/75R22.5)****Fr. Axl : MFS14 Fr. Spg : 14,000 lbs****Rr. Axl : RS23 Rr. Spg : 31,000 lbs**

Model			NH8JGSA	NH8JJSA	NH8JLSA	NH8JMSA
<b>CAPACITY</b>						
GVWR	Manual T/M	kg (lb.)	15,870 (35,000)	15,870 (35,000)	15,870 (35,000)	15,870 (35,000)
	Auto T/M	kg (lb.)	15,870 (35,000)	15,870 (35,000)	15,870 (35,000)	15,870 (35,000)
GAWR	Front	kg (lb.)	5,980 (13,200)	5,980 (13,200)	5,980 (13,200)	5,980 (13,200)
	Rear	kg (lb.)	10,430 (23,000)	10,430 (23,000)	10,430 (23,000)	10,430 (23,000)
<b>DIMENSIONS</b> (On standard specifications)						
Wheelbase		mm (in.)	3,861 (152.0)	4,445 (175.0)	4,750 (187.0)	5,207 (205.0)
Overall length		mm (in.)	6,162 (242.6)	7,076 (278.6)	7,686 (302.6)	8,143 (320.6)
Overall width		mm (in.)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)
Overall height		mm (in.)	2,725 (107.3)	2,725 (107.3)	2,725 (107.3)	2,725 (107.3)
BBC		mm (in.)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)
Cab to axle		mm (in.)	2,149 (84.6)	2,733 (107.6)	3,038 (119.6)	3,495 (137.6)
Rear overhang		mm (in.)	1,270 (50.0)	1,600 (63.0)	1,905 (75.0)	1,905 (75.0)
Frame height at	Front axle	mm (in.)	950 (37.4)	950 (37.4)	950 (37.4)	950 (37.4)
	Rear axle	mm (in.)	1,030 (40.6)	1,030 (40.6)	1,030 (40.6)	1,030 (40.6)
Road clearance (at diff. case)		mm (in.)	255 (10.0)	255 (10.0)	255 (10.0)	255 (10.0)
Tread	Front	mm (in.)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)
	Rear	mm (in.)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)
Turning radius Tire		mm (in.)	6,470 (254.7)	7,330 (288.6)	7,770 (305.9)	8,440 (332.3)
Turning radius Swept		mm (in.)	6,990 (275.2)	7,850 (309.1)	8,290 (326.4)	8,970 (353.1)
<b>CHASSIS WEIGHTS</b> (on std. spec., without spare tire & std. tool set)						
<b>MANUAL T/M</b>						
Total weight	MT	kg (lb.)	5,099 (11,242)	5,144 (11,342)	5,179 (11,417)	5,259 (11,592)
Front axle	MT	kg (lb.)	2,994 (6,598)	3,111 (6,861)	3,138 (6,916)	3,203 (7,063)
Rear axle	MT	kg (lb.)	2,105 (4,639)	2,033 (4,481)	2,041 (4,501)	2,056 (4,534)
Unsprung weight	Front	kg (lb.)	690 (1,520)	690 (1,520)	690 (1,520)	690 (1,520)
	Rear	kg (lb.)	1,225 (2,700)	1,225 (2,700)	1,225 (2,700)	1,225 (2,700)
<b>AUTO T/M</b>						
Total weight	ATM	kg (lb.)	5,174 (11,407)	5,219 (11,507)	5,259 (11,592)	5,334 (11,757)
Front axle	ATM	kg (lb.)	3,044 (6,713)	3,161 (6,971)	3,198 (7,051)	3,258 (7,183)
Rear axle	ATM	kg (lb.)	2,130 (4,694)	2,058 (4,536)	2,061 (4,546)	2,076 (4,579)
Unsprung weight	Front	kg (lb.)	690 (1,520)	690 (1,520)	690 (1,520)	690 (1,520)
	Rear	kg (lb.)	1,225 (2,700)	1,225 (2,700)	1,225 (2,700)	1,225 (2,700)
Center of gravity height from the ground		mm (in.)	795 (31.3)	795 (31.3)	795 (31.3)	795 (31.3)

Model			NH8JPSA	NH8JRSA	NH8JTSA	NH8JVSA
<b>CAPACITY</b>						
GVWR	Manual T/M	kg (lb.)	15,870 (35,000)	15,870 (35,000)	15,870 (35,000)	15,870 (35,000)
	Auto T/M	kg (lb.)	15,870 (35,000)	15,870 (35,000)	15,870 (35,000)	15,870 (35,000)
GAWR	Front	kg (lb.)	5,980 (13,200)	5,980 (13,200)	5,980 (13,200)	5,980 (13,200)
	Rear	kg (lb.)	10,430 (23,000)	10,430 (23,000)	10,430 (23,000)	10,430 (23,000)
<b>DIMENSIONS</b> (On standard specifications)						
Wheelbase		mm (in.)	5,512 (217.0)	5,969 (235.0)	6,426 (253.0)	6,883 (271.0)
Overall length		mm (in.)	9,007 (354.6)	9,464 (372.6)	9,921 (390.6)	9,921 (390.6)
Overall width		mm (in.)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)
Overall height		mm (in.)	2,725 (107.3)	2,725 (107.3)	2,725 (107.3)	2,725 (107.3)
BBC		mm (in.)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)
Cab to axle		mm (in.)	3,800 (149.6)	4,257 (167.6)	4,714 (185.6)	5,171 (203.6)
Rear overhang		mm (in.)	2,464 (97.0)	2,464 (97.0)	2,464 (97.0)	2,007 (79.0)
Frame height at	Front axle	mm (in.)	950 (37.4)	950 (37.4)	950 (37.4)	950 (37.4)
	Rear axle	mm (in.)	1,030 (40.6)	1,030 (40.6)	1,030 (40.6)	1,030 (40.6)
Road clearance (at diff. case)		mm (in.)	255 (10.0)	255 (10.0)	255 (10.0)	255 (10.0)
Tread	Front	mm (in.)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)
	Rear	mm (in.)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)
Turning radius Tire		mm (in.)	8,890 (350.0)	9,570 (376.8)	10,240 (403.1)	10,910 (429.5)
Turning radius Swept		mm (in.)	9,410 (370.5)	10,090 (397.2)	10,760 (423.6)	11,430 (450.0)
<b>CHASSIS WEIGHTS</b> (on std. spec., without spare tire & std. tool set)						
<b>MANUAL T/M</b>						
Total weight	MT	kg (lb.)	5,299 (11,682)	5,324 (11,737)	5,344 (11,782)	5,379 (11,857)
Front axle	MT	kg (lb.)	3,203 (7,059)	3,240 (7,145)	3,301 (7,278)	3,311 (7,299)
Rear axle	MT	kg (lb.)	2,096 (4,623)	2,084 (4,592)	2,043 (4,504)	2,068 (4,558)
Unsprung weight	Front	kg (lb.)	690 (1,520)	690 (1,520)	690 (1,520)	690 (1,520)
	Rear	kg (lb.)	1,225 (2,700)	1,225 (2,700)	1,225 (2,700)	1,225 (2,700)
<b>AUTO T/M</b>						
Total weight	ATM	kg (lb.)	5,374 (11,847)	5,399 (11,902)	5,419 (11,947)	5,454 (12,022)
Front axle	ATM	kg (lb.)	3,263 (7,194)	3,300 (7,275)	3,361 (7,408)	3,371 (7,434)
Rear axle	ATM	kg (lb.)	2,111 (4,653)	2,099 (4,627)	2,058 (4,539)	2,083 (4,593)
Unsprung weight	Front	kg (lb.)	690 (1,520)	690 (1,520)	690 (1,520)	690 (1,520)
	Rear	kg (lb.)	1,225 (2,700)	1,225 (2,700)	1,225 (2,700)	1,225 (2,700)
Center of gravity height from the ground		mm (in.)	795 (31.3)	795 (31.3)	795 (31.3)	795 (31.3)

**NH8J (Rr AIR SUS.)****Fr. Axl : MFS12 Fr. Spg : 12,000 lbs****Rr. Axl : RS23 Rr. Spg : 23,000 lbs**

Model			NH8JGSG	NH8JJSG	NH8JLSG	NH8JMSG
<b>CAPACITY</b>						
GVWR	Manual T/M	kg (lb.)	15,870 (35,000)	15,870 (35,000)	15,870 (35,000)	15,870 (35,000)
	Auto T/M	kg (lb.)	15,870 (35,000)	15,870 (35,000)	15,870 (35,000)	15,870 (35,000)
GAWR	Front	kg (lb.)	5,440 (12,000)	5,440 (12,000)	5,440 (12,000)	5,440 (12,000)
	Rear	kg (lb.)	10,430 (23,000)	10,430 (23,000)	10,430 (23,000)	10,430 (23,000)
<b>DIMENSIONS</b> (On standard specifications)						
Wheelbase		mm (in.)	3,861 (152.0)	4,445 (175.0)	4,750 (187.0)	5,207 (205.0)
Overall length		mm (in.)	6,162 (242.6)	7,076 (278.6)	7,686 (302.6)	8,143 (320.6)
Overall width		mm (in.)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)
Overall height		mm (in.)	2,710 (106.7)	2,710 (106.7)	2,710 (106.7)	2,710 (106.7)
BBC		mm (in.)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)
Cab to axle		mm (in.)	2,149 (84.6)	2,733 (107.6)	3,038 (119.6)	3,495 (137.6)
Rear overhang		mm (in.)	1,270 (50.0)	1,600 (63.0)	1,905 (75.0)	1,905 (75.0)
Frame height at	Front axle	mm (in.)	940 (37.0)	940 (37.0)	940 (37.0)	940 (37.0)
	Rear axle	mm (in.)	990 (39.0)	990 (39.0)	990 (39.0)	990 (39.0)
Road clearance (at diff. case)		mm (in.)	255 (10.0)	255 (10.0)	255 (10.0)	255 (10.0)
Tread	Front	mm (in.)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)
	Rear	mm (in.)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)
Turning radius Tire		mm (in.)	6,400 (252.0)	7,240 (285.0)	7,690 (302.8)	8,350 (328.7)
Turning radius Swept		mm (in.)	6,920 (272.4)	7,760 (305.5)	8,210 (323.2)	8,870 (349.2)
<b>CHASSIS WEIGHTS</b> (on std. spec., without spare tire & std. tool set)						
<b>MANUAL T/M</b>						
Total weight	MT	kg (lb.)	5,005 (11,032)	5,040 (11,112)	5,075 (11,187)	5,155 (11,367)
Front axle	MT	kg (lb.)	2,950 (6,499)	3,057 (6,742)	3,089 (6,807)	3,149 (6,944)
Rear axle	MT	kg (lb.)	2,055 (4,533)	1,983 (4,370)	1,986 (4,380)	2,006 (4,423)
Unsprung weight	Front	kg (lb.)	645 (1,420)	645 (1,420)	645 (1,420)	645 (1,420)
	Rear	kg (lb.)	1,210 (2,670)	1,210 (2,670)	1,210 (2,670)	1,210 (2,670)
<b>AUTO T/M</b>						
Total weight	ATM	kg (lb.)	5,080 (11,197)	5,115 (11,277)	5,150 (11,352)	5,230 (11,532)
Front axle	ATM	kg (lb.)	3,000 (6,609)	3,112 (6,862)	3,139 (6,917)	3,209 (7,074)
Rear axle	ATM	kg (lb.)	2,080 (4,588)	2,003 (4,415)	2,011 (4,435)	2,021 (4,458)
Unsprung weight	Front	kg (lb.)	645 (1,420)	645 (1,420)	645 (1,420)	645 (1,420)
	Rear	kg (lb.)	1,210 (2,670)	1,210 (2,670)	1,210 (2,670)	1,210 (2,670)
Center of gravity height from the ground		mm (in.)	780 (30.7)	780 (30.7)	780 (30.7)	780 (30.7)

Model			NH8JPSG	NH8JRSG	NH8JTSG	NH8JVSG
<b>CAPACITY</b>						
GVWR	Manual T/M	kg (lb.)	15,870 (35,000)	15,870 (35,000)	15,870 (35,000)	15,870 (35,000)
	Auto T/M	kg (lb.)	15,870 (35,000)	15,870 (35,000)	15,870 (35,000)	15,870 (35,000)
GAWR	Front	kg (lb.)	5,440 (12,000)	5,440 (12,000)	5,440 (12,000)	5,440 (12,000)
	Rear	kg (lb.)	10,430 (23,000)	10,430 (23,000)	10,430 (23,000)	10,430 (23,000)
<b>DIMENSIONS</b> (On standard specifications)						
Wheelbase		mm (in.)	5,512 (217.0)	5,969 (235.0)	6,426 (253.0)	6,883 (271.0)
Overall length		mm (in.)	9,007 (354.6)	9,464 (372.6)	9,921 (390.6)	9,921 (390.6)
Overall width		mm (in.)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)
Overall height		mm (in.)	2,710 (106.7)	2,710 (106.7)	2,710 (106.7)	2,710 (106.7)
BBC		mm (in.)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)
Cab to axle		mm (in.)	3,800 (149.6)	4,257 (167.6)	4,714 (185.6)	5,171 (203.6)
Rear overhang		mm (in.)	2,464 (97.0)	2,464 (97.0)	2,464 (97.0)	2,007 (79.0)
Frame height at	Front axle	mm (in.)	940 (37.0)	940 (37.0)	940 (37.0)	940 (37.0)
	Rear axle	mm (in.)	990 (39.0)	990 (39.0)	990 (39.0)	990 (39.0)
Road clearance (at diff. case)		mm (in.)	255 (10.0)	255 (10.0)	255 (10.0)	255 (10.0)
Tread	Front	mm (in.)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)
	Rear	mm (in.)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)
Turning radius Tire		mm (in.)	8,790 (346.1)	9,460 (372.4)	10,120 (398.4)	10,790 (424.8)
Turning radius Swept		mm (in.)	9,310 (366.5)	9,980 (392.9)	10,640 (418.9)	11,310 (445.3)
<b>CHASSIS WEIGHTS</b> (on std. spec., without spare tire & std. tool set)						
<b>MANUAL T/M</b>						
Total weight	MT	kg (lb.)	5,195 (11,452)	5,220 (11,507)	5,240 (11,552)	5,275 (11,627)
Front axle	MT	kg (lb.)	3,154 (6,950)	3,186 (7,021)	3,247 (7,159)	3,262 (7,190)
Rear axle	MT	kg (lb.)	2,041 (4,502)	2,034 (4,486)	1,993 (4,393)	2,013 (4,437)
Unsprung weight	Front	kg (lb.)	645 (1,420)	645 (1,420)	645 (1,420)	645 (1,420)
	Rear	kg (lb.)	1,210 (2,670)	1,210 (2,670)	1,210 (2,670)	1,210 (2,670)
<b>AUTO T/M</b>						
Total weight	ATM	kg (lb.)	5,270 (11,617)	5,295 (11,672)	5,315 (11,717)	5,350 (11,797)
Front axle	ATM	kg (lb.)	3,214 (7,085)	3,246 (7,156)	3,307 (7,289)	3,322 (7,325)
Rear axle	ATM	kg (lb.)	2,056 (4,532)	2,049 (4,516)	2,008 (4,428)	2,028 (4,472)
Unsprung weight	Front	kg (lb.)	645 (1,420)	645 (1,420)	645 (1,420)	645 (1,420)
	Rear	kg (lb.)	1,210 (2,670)	1,210 (2,670)	1,210 (2,670)	1,210 (2,670)
Center of gravity height from the ground		mm (in.)	780 (30.7)	780 (30.7)	780 (30.7)	780 (30.7)

**NH8J (Rr AIR SUS.)****Fr. Axl : MFS14 Fr. Spg : 14,000 lbs****Rr. Axl : RS23 Rr. Spg : 23,000 lbs**

Model			NH8JGSG	NH8JJSG	NH8JLSG	NH8JMSG
<b>CAPACITY</b>						
GVWR	Manual T/M	kg (lb.)	15,870 (35,000)	15,870 (35,000)	15,870 (35,000)	15,870 (35,000)
	Auto T/M	kg (lb.)	15,870 (35,000)	15,870 (35,000)	15,870 (35,000)	15,870 (35,000)
GAWR	Front	kg (lb.)	5,980 (13,200)	5,980 (13,200)	5,980 (13,200)	5,980 (13,200)
	Rear	kg (lb.)	10,430 (23,000)	10,430 (23,000)	10,430 (23,000)	10,430 (23,000)
<b>DIMENSIONS</b> (On standard specifications)						
Wheelbase		mm (in.)	3,861 (152.0)	4,445 (175.0)	4,750 (187.0)	5,207 (205.0)
Overall length		mm (in.)	6,162 (242.6)	7,076 (278.6)	7,686 (302.6)	8,143 (320.6)
Overall width		mm (in.)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)
Overall height		mm (in.)	2,715 (106.9)	2,715 (106.9)	2,715 (106.9)	2,715 (106.9)
BBC		mm (in.)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)
Cab to axle		mm (in.)	2,149 (84.6)	2,733 (107.6)	3,038 (119.6)	3,495 (137.6)
Rear overhang		mm (in.)	1,270 (50.0)	1,600 (63.0)	1,905 (75.0)	1,905 (75.0)
Frame height at	Front axle	mm (in.)	950 (37.4)	950 (37.4)	950 (37.4)	950 (37.4)
	Rear axle	mm (in.)	990 (39.0)	990 (39.0)	990 (39.0)	990 (39.0)
Road clearance (at diff. case)		mm (in.)	255 (10.0)	255 (10.0)	255 (10.0)	255 (10.0)
Tread	Front	mm (in.)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)
	Rear	mm (in.)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)
Turning radius Tire		mm (in.)	6,470 (254.7)	7,330 (288.6)	7,770 (305.9)	8,440 (332.3)
Turning radius Swept		mm (in.)	6,990 (275.2)	7,850 (309.1)	8,290 (326.4)	8,970 (353.1)
<b>CHASSIS WEIGHTS</b> (on std. spec., without spare tire & std. tool set)						
<b>MANUAL T/M</b>						
Total weight	MT	kg (lb.)	5,045 (11,122)	5,085 (11,212)	5,120 (11,287)	5,195 (11,452)
Front axle	MT	kg (lb.)	2,990 (6,589)	3,102 (6,842)	3,134 (6,907)	3,189 (7,029)
Rear axle	MT	kg (lb.)	2,055 (4,533)	1,983 (4,370)	1,986 (4,380)	2,006 (4,423)
Unsprung weight	Front	kg (lb.)	690 (1,520)	690 (1,520)	690 (1,520)	690 (1,520)
	Rear	kg (lb.)	1,210 (2,670)	1,210 (2,670)	1,210 (2,670)	1,210 (2,670)
<b>AUTO T/M</b>						
Total weight	ATM	kg (lb.)	5,120 (11,287)	5,160 (11,377)	5,195 (11,452)	5,275 (11,627)
Front axle	ATM	kg (lb.)	3,040 (6,699)	3,157 (6,962)	3,184 (7,017)	3,254 (7,169)
Rear axle	ATM	kg (lb.)	2,080 (4,588)	2,003 (4,415)	2,011 (4,435)	2,021 (4,458)
Unsprung weight	Front	kg (lb.)	690 (1,520)	690 (1,520)	690 (1,520)	690 (1,520)
	Rear	kg (lb.)	1,210 (2,670)	1,210 (2,670)	1,210 (2,670)	1,210 (2,670)
Center of gravity height from the ground		mm (in.)	790 (31.1)	790 (31.1)	790 (31.1)	790 (31.1)

Model			NH8JPSG	NH8JRSG	NH8JTSG	NH8JVSG
<b>CAPACITY</b>						
GVWR	Manual T/M	kg (lb.)	15,870 (35,000)	15,870 (35,000)	15,870 (35,000)	15,870 (35,000)
	Auto T/M	kg (lb.)	15,870 (35,000)	15,870 (35,000)	15,870 (35,000)	15,870 (35,000)
GAWR	Front	kg (lb.)	5,980 (13,200)	5,980 (13,200)	5,980 (13,200)	5,980 (13,200)
	Rear	kg (lb.)	10,430 (23,000)	10,430 (23,000)	10,430 (23,000)	10,430 (23,000)
<b>DIMENSIONS</b> (On standard specifications)						
Wheelbase		mm (in.)	5,512 (217.0)	5,969 (235.0)	6,426 (253.0)	6,883 (271.0)
Overall length		mm (in.)	9,007 (354.6)	9,464 (372.6)	9,921 (390.6)	9,921 (390.6)
Overall width		mm (in.)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)
Overall height		mm (in.)	2,715 (106.9)	2,715 (106.9)	2,715 (106.9)	2,715 (106.9)
BBC		mm (in.)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)
Cab to axle		mm (in.)	3,800 (149.6)	4,257 (167.6)	4,714 (185.6)	5,171 (203.6)
Rear overhang		mm (in.)	2,464 (97.0)	2,464 (97.0)	2,464 (97.0)	2,007 (79.0)
Frame height at	Front axle	mm (in.)	950 (37.4)	950 (37.4)	950 (37.4)	950 (37.4)
	Rear axle	mm (in.)	990 (39.0)	990 (39.0)	990 (39.0)	990 (39.0)
Road clearance (at diff. case)		mm (in.)	255 (10.0)	255 (10.0)	255 (10.0)	255 (10.0)
Tread	Front	mm (in.)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)
	Rear	mm (in.)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)
Turning radius Tire		mm (in.)	8,890 (350.0)	9,570 (376.8)	10,240 (403.1)	10,910 (429.5)
Turning radius Swept		mm (in.)	9,410 (370.5)	10,090 (397.2)	10,760 (423.6)	11,430 (450.0)
<b>CHASSIS WEIGHTS</b> (on std. spec., without spare tire & std. tool set)						
<b>MANUAL T/M</b>						
Total weight	MT	kg (lb.)	5,235 (11,542)	5,260 (11,597)	5,285 (11,652)	5,315 (11,717)
Front axle	MT	kg (lb.)	3,194 (7,040)	3,226 (7,111)	3,292 (7,259)	3,302 (7,280)
Rear axle	MT	kg (lb.)	2,041 (4,502)	2,034 (4,486)	1,993 (4,393)	2,013 (4,437)
Unsprung weight	Front	kg (lb.)	690 (1,520)	690 (1,520)	690 (1,520)	690 (1,520)
	Rear	kg (lb.)	1,210 (2,670)	1,210 (2,670)	1,210 (2,670)	1,210 (2,670)
<b>AUTO T/M</b>						
Total weight	ATM	kg (lb.)	5,315 (11,717)	5,340 (11,772)	5,360 (11,817)	5,395 (11,892)
Front axle	ATM	kg (lb.)	3,259 (7,185)	3,291 (7,256)	3,352 (7,389)	3,367 (7,420)
Rear axle	ATM	kg (lb.)	2,056 (4,532)	2,049 (4,516)	2,008 (4,428)	2,028 (4,472)
Unsprung weight	Front	kg (lb.)	690 (1,520)	690 (1,520)	690 (1,520)	690 (1,520)
	Rear	kg (lb.)	1,210 (2,670)	1,210 (2,670)	1,210 (2,670)	1,210 (2,670)
Center of gravity height from the ground		mm (in.)	790 (31.1)	790 (31.1)	790 (31.1)	790 (31.1)

**NH8J (Rr AIR SUS.)**

(Tire size : 295/75R22.5)

**Fr. Axl : MFS14 Fr. Spg : 14,000 lbs****Rr. Axl : RS23 Rr. Spg : 23,000 lbs**

Model			NH8JGSG	NH8JJSG	NH8JLSG	NH8JMSG
<b>CAPACITY</b>						
GVWR	Manual T/M	kg (lb.)	15,870 (35,000)	15,870 (35,000)	15,870 (35,000)	15,870 (35,000)
	Auto T/M	kg (lb.)	15,870 (35,000)	15,870 (35,000)	15,870 (35,000)	15,870 (35,000)
GAWR	Front	kg (lb.)	5,980 (13,200)	5,980 (13,200)	5,980 (13,200)	5,980 (13,200)
	Rear	kg (lb.)	10,430 (23,000)	10,430 (23,000)	10,430 (23,000)	10,430 (23,000)
<b>DIMENSIONS</b> (On standard specifications)						
Wheelbase		mm (in.)	3,861 (152.0)	4,445 (175.0)	4,750 (187.0)	5,207 (205.0)
Overall length		mm (in.)	6,162 (242.6)	7,076 (278.6)	7,686 (302.6)	8,143 (320.6)
Overall width		mm (in.)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)
Overall height		mm (in.)	2,715 (106.9)	2,715 (106.9)	2,715 (106.9)	2,715 (106.9)
BBC		mm (in.)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)
Cab to axle		mm (in.)	2,149 (84.6)	2,733 (107.6)	3,038 (119.6)	3,495 (137.6)
Rear overhang		mm (in.)	1,270 (50.0)	1,600 (63.0)	1,905 (75.0)	1,905 (75.0)
Frame height at	Front axle	mm (in.)	950 (37.4)	950 (37.4)	950 (37.4)	950 (37.4)
	Rear axle	mm (in.)	990 (39.0)	990 (39.0)	990 (39.0)	990 (39.0)
Road clearance (at diff. case)		mm (in.)	255 (10.0)	255 (10.0)	255 (10.0)	255 (10.0)
Tread	Front	mm (in.)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)
	Rear	mm (in.)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)
Turning radius Tire		mm (in.)	6,470 (254.7)	7,330 (288.6)	7,770 (305.9)	8,440 (332.3)
Turning radius Swept		mm (in.)	6,990 (275.2)	7,850 (309.1)	8,290 (326.4)	8,970 (353.1)
<b>CHASSIS WEIGHTS</b> (on std. spec., without spare tire & std. tool set)						
<b>MANUAL T/M</b>						
Total weight	MT	kg (lb.)	5,044 (11,120)	5,084 (11,210)	5,119 (11,285)	5,194 (11,450)
Front axle	MT	kg (lb.)	2,986 (6,581)	3,098 (6,833)	3,130 (6,898)	3,185 (7,020)
Rear axle	MT	kg (lb.)	2,058 (4,539)	1,986 (4,377)	1,989 (4,386)	2,009 (4,429)
Unsprung weight	Front	kg (lb.)	690 (1,520)	690 (1,520)	690 (1,520)	690 (1,520)
	Rear	kg (lb.)	1,210 (2,670)	1,210 (2,670)	1,210 (2,670)	1,210 (2,670)
<b>AUTO T/M</b>						
Total weight	ATM	kg (lb.)	5,119 (11,285)	5,159 (11,375)	5,194 (11,450)	5,274 (11,625)
Front axle	ATM	kg (lb.)	3,036 (6,691)	3,153 (6,953)	3,180 (7,008)	3,250 (7,160)
Rear axle	ATM	kg (lb.)	2,083 (4,594)	2,006 (4,422)	2,014 (4,441)	2,024 (4,464)
Unsprung weight	Front	kg (lb.)	690 (1,520)	690 (1,520)	690 (1,520)	690 (1,520)
	Rear	kg (lb.)	1,210 (2,670)	1,210 (2,670)	1,210 (2,670)	1,210 (2,670)
Center of gravity height from the ground		mm (in.)	790 (31.1)	790 (31.1)	790 (31.1)	790 (31.1)



Model			NH8JPSG	NH8JRSG	NH8JTSG	NH8JVSG
<b>CAPACITY</b>						
GVWR	Manual T/M	kg (lb.)	15,870 (35,000)	15,870 (35,000)	15,870 (35,000)	15,870 (35,000)
	Auto T/M	kg (lb.)	15,870 (35,000)	15,870 (35,000)	15,870 (35,000)	15,870 (35,000)
GAWR	Front	kg (lb.)	5,980 (13,200)	5,980 (13,200)	5,980 (13,200)	5,980 (13,200)
	Rear	kg (lb.)	10,430 (23,000)	10,430 (23,000)	10,430 (23,000)	10,430 (23,000)
<b>DIMENSIONS</b> (On standard specifications)						
Wheelbase		mm (in.)	5,512 (217.0)	5,969 (235.0)	6,426 (253.0)	6,883 (271.0)
Overall length		mm (in.)	9,007 (354.6)	9,464 (372.6)	9,921 (390.6)	9,921 (390.6)
Overall width		mm (in.)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)	2,450 (96.5)
Overall height		mm (in.)	2,715 (106.9)	2,715 (106.9)	2,715 (106.9)	2,715 (106.9)
BBC		mm (in.)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)	2,743 (108.0)
Cab to axle		mm (in.)	3,800 (149.6)	4,257 (167.6)	4,714 (185.6)	5,171 (203.6)
Rear overhang		mm (in.)	2,464 (97.0)	2,464 (97.0)	2,464 (97.0)	2,007 (79.0)
Frame height at	Front axle	mm (in.)	950 (37.4)	950 (37.4)	950 (37.4)	950 (37.4)
	Rear axle	mm (in.)	990 (39.0)	990 (39.0)	990 (39.0)	990 (39.0)
Road clearance (at diff. case)		mm (in.)	255 (10.0)	255 (10.0)	255 (10.0)	255 (10.0)
Tread	Front	mm (in.)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)	2,015 (79.3)
	Rear	mm (in.)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)	1,835 (72.2)
Turning radius Tire		mm (in.)	8,890 (350.0)	9,570 (376.8)	10,240 (403.1)	10,910 (429.5)
Turning radius Swept		mm (in.)	9,410 (370.5)	10,090 (397.2)	10,760 (423.6)	11,430 (450.0)
<b>CHASSIS WEIGHTS</b> (on std. spec., without spare tire & std. tool set)						
<b>MANUAL T/M</b>						
Total weight	MT	kg (lb.)	5,234 (11,540)	5,259 (11,595)	5,284 (11,650)	5,314 (11,715)
Front axle	MT	kg (lb.)	3,190 (7,031)	3,222 (7,102)	3,288 (7,250)	3,298 (7,271)
Rear axle	MT	kg (lb.)	2,044 (4,508)	2,037 (4,493)	1,996 (4,400)	2,016 (4,444)
Unsprung weight	Front	kg (lb.)	690 (1,520)	690 (1,520)	690 (1,520)	690 (1,520)
	Rear	kg (lb.)	1,210 (2,670)	1,210 (2,670)	1,210 (2,670)	1,210 (2,670)
<b>AUTO T/M</b>						
Total weight	ATM	kg (lb.)	5,314 (11,715)	5,339 (11,770)	5,359 (11,815)	5,394 (11,890)
Front axle	ATM	kg (lb.)	3,255 (7,176)	3,287 (7,247)	3,348 (7,380)	3,363 (7,411)
Rear axle	ATM	kg (lb.)	2,059 (4,538)	2,052 (4,523)	2,011 (4,435)	2,031 (4,479)
Unsprung weight	Front	kg (lb.)	690 (1,520)	690 (1,520)	690 (1,520)	690 (1,520)
	Rear	kg (lb.)	1,210 (2,670)	1,210 (2,670)	1,210 (2,670)	1,210 (2,670)
Center of gravity height from the ground		mm (in.)	790 (31.1)	790 (31.1)	790 (31.1)	790 (31.1)



### 3. WEIGHT DISTRIBUTION OF THE OPTION EQUIPMENT

The table of option weight shows the difference weight with standard specifications.

SERIES NE, NJ, NF, NV & NH

CONTENT OF OPTION		WEIGHT kg (lb.)	GRAVITY POSITION FROM F.A.C. m (ft.)	MOMENT FROM F.A.C. kg·m (lb·ft)	W/B	REMARKS
SEATING CAPACITY	2	-4 (-9)	1.157 (3.80)	-4.628 (-33.47)	ALL	
FUEL TANK	50gal X 2	205 (452)	2.47 (8.10)	506.35 (3662.43)	ALL	
	90gal X 1	154 (340)	1.96 (6.43)	301.84 (2183.21)	ALL	
REAR SUSPENSION	WITH D/SHOCK	33 (73)	At rear axle datum line		ALL	Unsprung weight
	WITH STABI..	86 (190)	At rear axle datum line		ALL	Unsprung weight
	WITH D/SHOCK & STABI.	108 (238)	At rear axle datum line		ALL	Unsprung weight
	HELPER LEAF WITH	21 (46)	At rear axle datum line		ALL	Unsprung weight Except 31000lbs spring
	HELPER RUBBER WITH	26 (57)	At rear axle datum line		ALL	Unsprung weight Except 21000lbs spring
	REINFORCED AIR SUS.	37 (82)	At rear axle datum line		ALL	Unsprung weight Except 23000lbs spring
BATTERY	BCI GR27 X 3	20 (44)	0.81 (2.66)	16.2 (117.17)	ALL	
	AGM GR31 X 2	20 (44)	0.81 (2.66)	16.2 (117.17)	ALL	
	BCI GR31 X 2	8 (18)	0.81 (2.66)	6.48 (46.87)	ALL	
	BCI GR31 X 3	32 (71)	0.81 (2.66)	25.92 (187.48)	ALL	
BUMPER	+4" 3P	14 (31)	-0.96 (-3.15)	-13.44 (-97.21)	ALL	
	3P	2 (4)	-0.96 (-3.15)	-1.92 (-13.89)	ALL	
	+4"	11 (24)	-0.96 (-3.15)	-10.56 (-76.38)	ALL	
	LESS	-30 (-66)	-0.96 (-3.15)	28.8 (208.31)	ALL	
CLUTCH	EATON SAS1402	15 (33)	0.59 (1.94)	8.85 (64.01)	ALL	Only model NE, NJ
DIFF. LOCK		9 (20)	At rear axle datum line		ALL	Unsprung weight Only model NJ, NV, NH
EXHAUST SYSTEM	STACK	48 (106)	1.2 (3.94)	57.6 (416.62)	ALL	

Detail of option tire

STD /OPT	Model	Tire size	Fr		Rr		The difference [kg]	
			RIB/LUG	Maker_Pattern	RIB/LUG	Maker_Pattern	Fr Axle	Rr Axle
STD	ALL	11R22.5-14	RIB	BS_R268FZ	LUG	M726GZ		
OPT	NE	10R22.5-14	RIB	BS_R250FZ	RIB	BS_R250FZ	- 19	- 59
					LUG	BS_M726EZ		- 53
	ALL	11R22.5-14	RIB	BS_R268FZ	RIB	BS_R268FZ	±0	- 21
	NV NH	11R22.5-16	RIB	BS_R250HZ	LUG	BS_M770Z	- 4	- 5
					RIB	BS_R250HZ		- 30
			RIB	GY_G662 RSA FUEL MAX	RIB	GY_G662 RSA FUEL MAX	±0	- 21
					LUG	GY_RHDII G137		+ 45
	NE NJ	255/70R22.5-16	RIB	BS_R250HZ	LUG	BS_M726BZ	- 25	- 60
	NH	295/75R22.5 _F7160_R14PR	RIB	BS_R283Z	LUG	BS_M770Z	- 8	- 2
	NE NF NJ NV	295/75R22.5-14	RIB	BS_R268FZ	RIB	BS_R268FZ	- 4	- 29
					LUG	BS_M726GZ		- 12
						BS_M770Z		- 2
			RIB	GY_G662 RSA FUEL MAX	RIB	GY_G662 RSA FUEL MAX	±0	- 21
					LUG	GY_G182 RSD		- 23

## 4. BODY TYPE

---

Flat Bed and Van may be approved by HMC.



### WARNING

When you intend to install other types of body, equipment or device on Hino chassis other than the body mentioned above, please contact to HINO MOTORS CANADA or Hino authorized dealer in advance to avoid death or a serious injury in an accident or damage to the vehicle.